PolyOne

## MATERIAL SAFETY DATA SHEET *IMPET 137330*

Version Number 1.1 Revision Date 03/21/2014 Page 1 of 6 Print Date 3/25/2014

1. PRODUCT AND COMPANY IDENTIFICATION				
POLYONE CORPORATI	ON			
33587 Walker Road, Avor	n Lake,	OH 44012		
Talaahaaa		1 (440) 020 1000 1 (866) DOI VONE		
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure		
Emergency telephone number	·	or accident).		
Product name	:	IMPET 137330		
Product code	:	CC10137330		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
2,3-Epoxypropyl methacrylate	106-91-2	1 - 5
Butyl acrylate	141-32-2	1 - 5

## **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

**POLYONE CORPORATION** 

# MATERIAL SAFETY DATA SHEET *IMPET 137330*

Version Number 1.1 Revision Date 03/21/2014 Page 2 of 6 Print Date 3/25/2014

PolyOne.

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



# MATERIAL SAFETY DATA SHEET *IMPET 137330*

Version Number 1.1 Revision Date 03/21/2014 Page 3 of 6 Print Date 3/25/2014

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	: No personal respiratory protective equipment normally required.	
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Butyl acrylate	2 ppm	Time Weighted Average (TWA):		ACGIH
	10 ppm 55 mg/m3	Recommended exposure limit (REL):		NIOSH
	10 ppm 55 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 ppm 55 mg/m3	Time Weighted Average (TWA):		MX OEL

9. PHYSICAL AND	CHEMICAL PROPERTIES
-----------------	---------------------

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility solid
pellets
NO PIGMENT
very faint
Not determined
not applicable
insoluble

- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  not applicable
  not applicable
  not applicable

#### **10. STABILITY AND REACTIVITY**

Stability

: The product is stable if stored and handled as prescribed.

PolyOne

Page 4 of 6

## POLYONE CORPORATION

## **MATERIAL SAFETY DATA SHEET IMPET 137330**

Version Number 1.1 Print Date 3/25/2014 Revision Date 03/21/2014 Hazardous Polymerization : Will not occur.

Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
106-91-2	2,3-Epoxypropyl	Chronic effects	Kidney, central nervous system
	methacrylate		(CNS).
		Irritant	Eyes, Skin, Respiratory
			system.
141-32-2	Butyl acrylate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

## LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
106-91-2	2,3-Epoxypropyl methacrylate	Oral LD50Oral LD50Oral	597 mg/kg390 mg/kg697 mg/kg	ratmouseguinea pig rabbit
		LD50 Dermal LD50	469 mg/kg	luoon
141-32-2	Butyl acrylate	LC50	2730 ppm/4H	rat
		Oral LD50 Dermal LD50	900 mg/kg 2 ml/kg	rat rabbit

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.



# MATERIAL SAFETY DATA SHEET *IMPET 137330*

Version Number 1.1 Revision Date 03/21/2014 Page 5 of 6 Print Date 3/25/2014

Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	is Substances (40 CFR 302)
not applicable	
California Proposition 65	a : Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulati
SARA Title III Section 313 T	oxic Chemicals:

PolyOne

# MATERIAL SAFETY DATA SHEET *IMPET 137330*

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulatio Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name CAS-No. Weight NPRI ID# percent Butyl acrylate 141-32-2 0.10 - 1.00 WHMIS Classification : D1A WHMIS Ingredient Disclosure List CAS-No. 141-32-2
Chemical Name       CAS-No.       Weight percent       NPRI ID#         Butyl acrylate       141-32-2       0.10 - 1.00
Butyl acrylate       141-32-2       0.10 - 1.00         WHMIS Classification : D1A         WHMIS Ingredient Disclosure List         CAS-No.
WHMIS Ingredient Disclosure List
DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:
Australia AICS: Not determined
China IECS : Not determined
Europe EINECS : Listed
Japan ENCS : Not determined
Korea KECI : Not determined
Philippines PICCS : Not determined
16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.