# MATERIAL SAFETY DATA SHEET **FLOURESCENT YELLOW PC**

Version Number 1.1 Revision Date 03/21/2014 Page 1 of 6 Print Date 3/25/2014

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FLOURESCENT YELLOW PC
Product code	:	CC10137948
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact
: Resin particles, like other inert materials, can be mechanically irritating.
: May be harmful if swallowed.
: Resin particles, like other inert materials, are mechanically irritating to eyes.
: Experience shows no unusual dermatitis hazard from routine handling.
: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET **FLOURESCENT YELLOW PC**

Version Number 1.1 Revision Date 03/21/2014 Page 2 of 6 Print Date 3/25/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION

PolyOne

# MATERIAL SAFETY DATA SHEET **FLOURESCENT YELLOW PC**

Version Number 1.1 Revision Date 03/21/2014 Page 3 of 6 Print Date 3/25/2014

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour : solid: pellets: YELLOW

Evapouration rate Specific Gravity Bulk density

Not applicableNot determinedNot established

# MATERIAL SAFETY DATA SHEET **FLOURESCENT YELLOW PC**

Version Number 1.1 Revision Date 03/21/2014 Page 4 of 6 Print Date 3/25/2014

Odour Melting point/range Boiling Point: Water solubility	<ul><li>very faint</li><li>Not determined</li><li>not applicable</li><li>insoluble</li></ul>	Vapour pressure Vapour density pH	<ul><li>not applicable</li><li>not applicable</li><li>not applicable</li></ul>
	10. STABILITY AND	REACTIVITY	
Stability	: The product is stabl	e if stored and handled as	s prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from ox decomposition, do r	idizing agents and open f not overheat.	lame. To avoid thermal
Incompatible Materials	: Incompatible with s	trong acids and oxidizing	agents.
Hazardous decomposition products		02), carbon monoxide (CO lous materials, and smoke	6

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.

PolyOne.

# MATERIAL SAFETY DATA SHEET **FLOURESCENT YELLOW PC**

not readily available as they are bound within the c. not readily available as they are bound within the c. le <b>CONSIDERATIONS</b>
x. not readily available as they are bound within the x. le <b>CONSIDERATIONS</b>
de CONSIDERATIONS
CONSIDERATIONS
monlastic plastics the product car be received. With the
moplastic plastics the product can be recycled. Where ing is preferred to disposal or incineration. The aste material has the responsibility for proper waste ransportation and disposal in accordance with eral, state/provincial and local regulations.
referred when possible. The generator of waste e responsibility for proper waste classification, and disposal in accordance with applicable federal, l and local regulations.
T INFORMATION
for transportation.
ic regulation.
ic regulation.
RY INFORMATION
azardous based on components.
ts of this product are listed on or exempt from the ry.
302)
562)
502)

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET FLOURESCENT YELLOW PC

Version Number 1.1 R

of 6 )14

vision Date 03/21/2014		Page 6 Print Date 3/25/20
SARA Title III Section 302 E	xtremely Hazardous Substance	
	identified under this section, this product	is Not Applicable under this regulat
SARA Title III Section 313 T	oxic Chemicals:	
Unless specific chemicals are	identified under this section, this product	is Not Applicable under this regulat
Canadian Regulations:		
National Pollutant Rele	ease Inventory (NPRI)	
not applicable		
WHMIS Classification	n : D2A	
WHMIS Ingredient Di	sclosure List	
CAS-No. 7631-86-9		
DSL	: All components of this product ar Substances List (DSL) or are exem	
National Inventories:		
Australia AICS	: Not determined	
China IECS	: Listed	
Europe EINECS	: Listed	
Japan ENCS	: Not determined	
Korea KECI	: Listed	
Philippines PICCS	: Listed	
	16. OTHER INFORMATION	

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.