PolyOne.

### MATERIAL SAFETY DATA SHEET NAVAJO BEIGE

Version Number 1.1 Revision Date 03/23/2014 Page 1 of 8 Print Date 3/26/2014

| 1. PRODUCT AND COMPANY IDENTIFI                               | CATION |
|---|--------|
| POLYONE CORPORATION<br>33587 Walker Road, Avon Lake, OH 44012 |        |

| Telephone                     | : | 1 (440) 930-1000 or 1 (866) POLYONE  |
|-------------------------------|---|--|
| Emergency telephone<br>number | : | CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
| inum of                       |   |  |
| Product name                  | : | NAVAJO BEIGE   |
| Product code                  | : | CC10138237   |
| Chemical Name                 | : | Mixture  |
| CAS-No.                       | : | Mixture  |
| Product Use                   | : | Industrial Applications  |

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components                     | CAS-No.    | Weight percent |
|--------------------------------|------------|----------------|
| Rutile, antimony chromium buff | 68186-90-3 | 1 - 5          |
| Silica, amorphous              | 7631-86-9  | 1 - 5          |
| Titanium dioxide               | 13463-67-7 | 30 - 60        |

#### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact  |
|---------------------|--|
| Acute exposure      |  |
| Inhalation          | : Particulates, like other inert materials can be mechanically irritating.<br>Excessive inhalation of product vapors, especially during heating or<br>processing, may be irritating to respiratory system. |
| Ingestion           | : May be harmful if swallowed.   |
| Eyes                | : Particulates, like other inert materials can be mechanically irritating.   |
| Skin                | : Experience shows no unusual dermatitis hazard from routine handling.   |

**POLYONE CORPORATION** 

PolyOne.

## MATERIAL SAFETY DATA SHEET **NAVAJO BEIGE**

Version Number 1.1 Revision Date 03/23/2014 Page 2 of 8 Print Date 3/26/2014

| Medical Conditions<br>Aggravated by Exposure:   | : None known.  |
|---|--|
|   | 4. FIRST AID MEASURES  |
| Inhalation  | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.   |
| Ingestion   | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.   |
| Eyes  | : Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.  |
| Skin  | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.  |
|   | 5. FIREFIGHTING MEASURES   |
| Flash point   | : not applicable   |
| Flammable Limits<br>Upper explosion limit<br>Lower explosion limit<br>Auto-ignition temperature<br>Suitable extinguishing media<br>Special Fire Fighting<br>Procedures<br>Unusual Fire/Explosion<br>Hazards | <ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive<br/>pressure mode should be worn to prevent inhalation of airborne<br/>contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen<br/>(NOx), other hazardous materials, and smoke are all possible. May<br/>emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire<br/>conditions.</li> </ul> |
|   | 0. ACCIDENTAL RELEASE MEASURES   |
| Personal precautions  | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.   |
| Environmental precautions   | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.   |
| Methods for cleaning up   | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.  |

**POLYONE CORPORATION** 

PolyOne.

## MATERIAL SAFETY DATA SHEET **NAVAJO BEIGE**

Version Number 1.1 Revision Date 03/23/2014 Page 3 of 8 Print Date 3/26/2014

| Handling                          | :    | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.    |
|-----------------------------------|------|--|
| Storage                           | :    | Keep containers dry and tightly closed to avoid moisture absorption<br>and contamination. Keep in a dry, cool place.       |
| 8. EXI                            | POSU | RE CONTROLS/PERSONAL PROTECTION  |
| Respiratory protection            | :    | No personal respiratory protective equipment normally required.  |
| Eye/Face Protection               | :    | Safety glasses with side-shields   |
| Hand protection                   | :    | Protective gloves  |
| Skin and body protection          | :    | Long sleeved clothing  |
| Additional Protective<br>Measures | :    | Safety shoes   |
| General Hygiene<br>Considerations | :    | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures              | :    | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.             |

PolyOne

## MATERIAL SAFETY DATA SHEET **NAVAJO BEIGE**

Version Number 1.1 Revision Date 03/23/2014 Page 4 of 8 Print Date 3/26/2014

| Components                     | Value     | Exposure time                        | Exposure type          | List:    |
|--------------------------------|-----------|--------------------------------------|------------------------|----------|
| Rutile, antimony chromium buff | 0.5 mg/m3 | Recommended exposure limit (REL):    | as Cr                  | NIOSH    |
|                                | 0.5 mg/m3 | PEL:                                 | as Cr                  | OSHA Z1  |
|                                | 0.5 mg/m3 | Time Weighted Average (TWA):         | as Sb                  | ACGIH    |
|                                | 0.5 mg/m3 | Recommended exposure<br>limit (REL): | as Sb                  | NIOSH    |
|                                | 0.5 mg/m3 | PEL:                                 | as Sb                  | OSHA Z1  |
|                                | 0.5 mg/m3 | Time Weighted Average (TWA):         | as Sb                  | OSHA Z1A |
|                                | 0.5 mg/m3 | Time Weighted Average (TWA):         | as Sb                  | MX OEL   |
| Silica, amorphous              | 6 mg/m3   | Recommended exposure<br>limit (REL): |                        | NIOSH    |
|                                | 0.8 mg/m3 | Time Weighted Average<br>(TWA):      |                        | Z3       |
|                                | 10 mg/m3  | Time Weighted Average (TWA):         | Inhalable particulate. | MX OEL   |
|                                | 3 mg/m3   | Time Weighted Average (TWA):         | Respirable dust.       | MX OEL   |
| Titanium dioxide               | 10 mg/m3  | Time Weighted Average (TWA):         |                        | ACGIH    |
|                                | 15 mg/m3  | PEL:                                 | Total dust.            | OSHA Z1  |
|                                | 10 mg/m3  | Time Weighted Average<br>(TWA):      | Total dust.            | OSHA Z1A |
|                                | 10 mg/m3  | Time Weighted Average<br>(TWA):      | as Ti                  | MX OEL   |
|                                | 20 mg/m3  | Short Term Exposure Limit (STEL):    | as Ti                  | MX OEL   |

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
  pellets
  TAN
  very faint
  Not determined
  not applicable
  insoluble

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- Not applicableNot determinedNot establishednot applicablenot applicable
- : not applicable

#### **10. STABILITY AND REACTIVITY**

| Stability                | : | The product is stable if stored and handled as prescribed.                                       |
|--------------------------|---|--|
| Hazardous Polymerization | : | Will not occur.  |
| Conditions to avoid      | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |

## MATERIAL SAFETY DATA SHEET **NAVAJO BEIGE**

| Version Number 1.1<br>Revision Date 03/23/2014 | Page 5 of 8<br>Print Date <i>3/26/2014</i>   |
|--|--|
|  |  |
| Incompatible Materials                         | : Avoid contact with strong oxidizers. Also, avoid contact with acetal<br>or acetal copolymers and with amine containing materials during<br>processing. At processing conditions, these materials are mutually<br>destructive and involve rapid degradation. Thoroughly purge and<br>mechanically clean processing equipment to avoid even trace<br>quantities of these materials from coming in contact with each other.<br>Prevent cross contamination of feedstocks. |
| Hazardous decomposition products               | <ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.</li> </ul>  |

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name     | Effect           | Target Organ              |
|------------|-------------------|------------------|---------------------------|
| 68186-90-3 | Rutile, antimony  | Irritant         | Eyes, Skin, Respiratory   |
|            | chromium buff     |                  | system.                   |
| 7631-86-9  | Silica, amorphous | Irritant         | Eyes, Respiratory system. |
| 13463-67-7 | Titanium dioxide  | Systemic effects | Respiratory system.       |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No.    | Chemical Name    | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no   | 2B   | no  |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.



# MATERIAL SAFETY DATA SHEET **NAVAJO BEIGE**

| ion Number 1.1<br>sion Date 03/23/2014 | Page of Page of Print Date 3/26/2   |
|--|---|
|  |   |
| Environmental Toxicity                 | : Chemicals are not readily available as they are bound within the polymer matrix.  |
| Bioaccumulation Potential              | : Chemicals are not readily available as they are bound within the polymer matrix.  |
| Additional advice                      | : no data available   |
|  | 13. DISPOSAL CONSIDERATIONS   |
| Product                                | : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging                 | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.  |
|  | 14. TRANSPORT INFORMATION   |
| U.S. DOT Classification                | : Not regulated for transportation.   |
| ICAO/IATA                              | : Refer to specific regulation.   |
| IMO/IMDG (maritime)                    | : Refer to specific regulation.   |
|  | 15. REGULATORY INFORMATION  |
| US Regulations:                        |   |
| OSHA Status                            | : Classified as hazardous based on components.  |
| TSCA Status                            | : All components of this product are listed on or exempt from the TSCA Inventory.   |
| US. EPA CERCLA Hazardous               | Substances (40 CFR 302)   |
| not applicable                         |   |
| California Proposition<br>65           | : WARNING! This product contains a chemical known to the State o California to cause cancer.  |
| SARA Title III Section 302 Ex          | tremely Hazardous Substance   |
|  |   |

PolyOne.

### MATERIAL SAFETY DATA SHEET NAVAJO BEIGE

Version Number 1.1 Revision Date 03/23/2014 Page 7 of 8 Print Date 3/26/2014

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name                      | CAS-No.    | Weight percent |
|------------------------------------|------------|----------------|
| MANGANESE COMPOUNDSMANGANESE       | 68412-38-4 | 0.10 - 1.00    |
| COMPOUNDSANTIMONY COMPOUNDS        |            |                |
| CHROMIUM III COMPOUNDSCHROMIUM III | 68186-90-3 | 1.00 - 5.00    |
| COMPOUNDSANTIMONY                  |            |                |
| COMPOUNDSCHROMIUM COMPOUNDS        |            |                |
| CHROMIUM III COMPOUNDSCHROMIUM     | 12737-27-8 | 0.10 - 1.00    |
| COMPOUNDS                          |            |                |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name                                  | CAS-No.    | Weight      | NPRI ID# |
|--|------------|-------------|----------|
|  |            | percent     |          |
| Manganese antimony titanium brown rutile (C.I. | 68412-38-4 | 0.10 - 1.00 |          |
| Pigment Yellow 164)                            |            |             |          |
|  |            | 0.10 - 1.00 |          |
| Rutile, antimony chromium buff                 | 68186-90-3 | 1.00 - 5.00 |          |
| Iron chromite brown spinel                     | 12737-27-8 | 0.10 - 1.00 |          |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No.    |  |
|------------|--|
| 68186-90-3 |  |
| 7631-86-9  |  |

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS | : | Listed         |
|----------------|---|----------------|
| China IECS     | : | Listed         |
| Europe EINECS  | : | Listed         |
| Japan ENCS     | : | Not determined |

:

PolyOne

## MATERIAL SAFETY DATA SHEET **NAVAJO BEIGE**

Version Number 1.1 Revision Date 03/23/2014 Page 8 of 8 Print Date 3/26/2014

Korea KECI

: Listed

: Not determined

Philippines PICCS

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.