PolvOne

MATERIAL SAFETY DATA SHEET SHERWOOD GREEN TPP

Version Number 1.1 Revision Date 03/23/2014

Page 1 of 6 Print Date 3/31/2014

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	SHERWOOD GREEN TPP		
Product code	:	CC10141326		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Rutile, antimony chromium buff	68186-90-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET SHERWOOD GREEN TPP

Version Number 1.1 Revision Date 03/23/2014 Page 2 of 6 Print Date 3/31/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET SHERWOOD GREEN TPP

Version Number 1.1 Revision Date 03/23/2014 Page 3 of 6 Print Date 3/31/2014

Storage : Keep containers dry and tightly closed to avoid me and contamination. Keep in a dry, cool place.		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure	as Cr	NIOSH
	0.5 / 2	limit (REL):	0	00114 771
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid
 : pellets
 : GREEN
 : very faint
 : Not determined
 : not applicable
 : insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable

10. STABILITY AND REACTIVITY

PolyOne

MATERIAL SAFETY DATA SHEET SHERWOOD GREEN TPP

Version Number 1.1 Revision Date 03/23/2014 Page 4 of 6 Print Date 3/31/2014

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	0	Themical Name	Effect	Target Organ			
68186-90-3	Rutile, antimony chromium buff		Irritant	Eyes, Skin, Respiratory system.			
			CAL INFORMATIO)N			
		12. ECOLOGIC	AL INFORMATIC	JIN			
Persistence and deg	radability	: Not readily b	iodegradable.				
Environmental Toxi	icity		Chemicals are not readily available as they are bound within the polymer matrix.				
Bioaccumulation Potential		: Chemicals are not readily available as they are bound within the polymer matrix.					
Additional advice		: no data availa	no data available				
		13. DISPOSAL	CONSIDERATION	NS			
Product		possible recyc generator of v classification	Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging		material has t transportation	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				

PolyOne.

MATERIAL SAFETY DATA SHEET SHERWOOD GREEN TPP

Version Number 1.1 Revision Date 03/23/2014 Page 5 of 6 Print Date 3/31/2014

	14	4. TRANSPORT I	NFOR	MATIO	N		
U.S. DOT Classification	:	Not regulated for t	ranspo	rtation.			
ICAO/IATA	:	Refer to specific re	egulatio	on.			
IMO/IMDG (maritime)	:	Refer to specific re	egulatio	on.			
	15.	REGULATORY	INFO	RMATIO	ON		
US Regulations:							
OSHA Status	:	Classified as hazar	dous b	ased on c	component	ts.	
TSCA Status	:	All components or TSCA Inventory.	f this p	roduct ar	e listed on	or exen	pt from the
US. EPA CERCLA Hazardo	us Subs	tances (40 CFR 302	2)				
not applicable							
California Propositio 65		Not applicable					
SARA Title III Section 302	Extreme	ely Hazardous Subs	tance				
Unless specific chemicals are	e identif	ied under this section	on, this	s product	is Not Ap	plicable	under this regula
SARA Title III Section 313	Foxic C	hemicals:					
Unless specific chemicals are	e identif	ied under this section	on, this	s product	is Not Ap	plicable	under this regula
Chemical Name				CAS-N			percent
CHROMIUM III COMPO COMPOUNDSANTIMO		CHROMIUM III		68186-9	0-3	10.00 -	30.00
COMPOUNDSCHROMI		MPOUNDS					
Canadian Regulations:							
National Pollutant Re	10000 In	ventory (NDDI)					
Chemical Name	10050 111		CAS-N	0.	Weight	t	NPRI ID#
					percen	t	
Phthalocyanine green Rutile, antimony chromiun	n huff		1328-5 58186-		5.00 -		

PolyOne

MATERIAL SAFETY DATA SHEET SHERWOOD GREEN TPP

Version Number 1.1 Revision Date 03/23/2014 Page 6 of 6 Print Date 3/31/2014

	WHMIS Classification	:	D2B			
	WHMIS Ingredient Disclosure List					
	CAS-No. 1328-53-6 68186-90-3					
	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
Ν	ational Inventories:					
	Australia AICS	:	Listed			
	China IECS	:	Listed			
	Europe EINECS	:	Listed			
	Japan ENCS	:	Listed			
	Korea KECI	:	Listed			
	Philippines PICCS	:	Listed			
			16 OTHED INFORMATION			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.