MATERIAL SAFETY DATA SHEET CEDAR 1

Version Number 1.1 Revision Date 03/23/2014

Product Use

Page 1 of 8 Print Date 3/31/2014

1. PRODUCT AND COMPANY IDENTIFICATION	

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	CEDAR 1
Product code	:	CC10142080
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Mixture : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
1,3,5-Triazine-2,4,6-triamine,N,N ^{'''} -1,2- ethanediylbis[N-[3-[[4,6-bis[butyl(1,2,2,6,6- pentamethyl-4-piperidinyl)amino]-1,3,5- triazin	106990-43-6	1 - 5
	25973-55-1	5 - 10
Phenol, 2-(2H-benzotriazol-2-yl)-4,6- bis(1,1-dimethylpropyl)-	23975-35-1	5 - 10
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Iron oxide	1309-37-1	5 - 10
Titanium dioxide	13463-67-7	5 - 10
Iron chromite brown spinel	12737-27-8	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Ingestion, Skin contact

Acute exposure



MATERIAL SAFETY DATA SHEET **CEDAR 1**

sion Date 03/23/2014	Page 2 Print Date 3/31/2
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
M. R 1 C P.C	No
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Auto-ignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion	contaminants.Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not



MATERIAL SAFETY DATA SHEET **CEDAR 1**

ersion Number 1.1 Vevision Date 03/23/2014		Page 3 of 8 Print Date <i>3/31/2014</i>
Methods for cleaning up	: C	e allowed to enter drains, water courses or the soil. Clean up promptly by sweeping or vacuum. Package all material in lastic, cardboard or metal containers for disposal.
	7.	HANDLING AND STORAGE
Handling		ake measures to prevent the build up of electrostatic charge. Heat nly in areas with appropriate exhaust ventilation.
Storage		Leep containers dry and tightly closed to avoid moisture absorption nd contamination. Keep in a dry, cool place.
8. EX	POSURE	C CONTROLS/PERSONAL PROTECTION
Respiratory protection	: N	to personal respiratory protective equipment normally required.
Eye/Face Protection	: S	afety glasses with side-shields
Hand protection	: P	Protective gloves
Skin and body protection	: L	ong sleeved clothing
Additional Protective Measures	: S	afety shoes
General Hygiene Considerations		Iandle in accordance with good industrial hygiene and safety ractice. Wash hands before breaks and at the end of workday.
Engineering measures		leat only in areas with appropriate exhaust ventilation. Provide ppropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne.

MATERIAL SAFETY DATA SHEET **CEDAR 1**

Version Number 1.1

Revision Date 03/23/2014

Page 4 of 8 Print Date 3/31/2014

Components	Value	Exposure time	Exposure type	List:
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Xylenes (o-, m-, p- isomers)	100 ppm	Time Weighted Average (TWA):		ACGIH
	150 ppm	Short Term Exposure Limit (STEL):		ACGIH
	100 ppm 435 mg/m3	PEL:		OSHA Z1
	100 ppm 435 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	100 ppm 435 mg/m3	Time Weighted Average (TWA):		MX OEL
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Iron chromite brown spinel	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility : solid
: pellets
: BROWN
: very faint
: Not determined
: not applicable
: insoluble

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- Not applicableNot determinedNot established
- : not applicable
- : not applicable
- : not applicable

10. STABILITY AND REACTIVITY

Stability

: The product is stable if stored and handled as prescribed.



MATERIAL SAFETY DATA SHEET **CEDAR 1**

Version Number 1.1 Revision Date 03/23/2014 Page 5 of 8 Print Date 3/31/2014

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
25973-55-1	Phenol, 2-(2H- benzotriazol-2-yl)-4,6- bis(1,1-dimethylpropyl)-	Systemic effects	Kidney, Liver, reproductive system.
1330-20-7	Xylenes (o-, m-, p- isomers)	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, blood and blood forming system, Liver, Kidney, central nervous system (CNS), digestive system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12737-27-8	Iron chromite brown spinel	Irritant	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1330-20-7	Xylenes (o-, m-, p-	LC50	5000 ppm/4H	rat
	isomers)	LC50		rat
		Oral	4,300	ratrat
		LD50Oral	mg/kg4,300	rabbit
		LD50	mg/kg	rabbit
		Dermal LD50	> 1,700 mg/kg	
		Dermal LD50	43 g/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne

MATERIAL SAFETY DATA SHEET **CEDAR 1**

Version Number 1.1

Revision Date 03/23/2014

Page 6 of 8 Print Date 3/31/2014

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Iron chromite brown spinel 12737-27-8 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

le.
y available as they are bound within the
y available as they are bound within the
ERATIONS
plastics the product can be recycled. Wher ferred to disposal or incineration. The tial has the responsibility for proper waste tion and disposal in accordance with provincial and local regulations. Then possible. The generator of waste ibility for proper waste classification, sal in accordance with applicable federal, l regulations.
RMATION
ortation.
ion.
ion.

PolyOne.

MATERIAL SAFETY DATA SHEET **CEDAR 1**

Version Number 1.1 Revision Date 03/23/2014 Page 7 of 8 Print Date 3/31/2014

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status :

: All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	RQ for
			Mixture/Product
Xylenes (o-, m-, p-	1330-20-7	100 lbs	2,727 LB
isomers)			

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
ZINC COMPOUNDS	68187-51-9	10.00 - 30.00
XYLENE (MIXED ISOMERS)	1330-20-7	1.00 - 5.00
CHROMIUM III COMPOUNDSCHROMIUM	12737-27-8	10.00 - 30.00
COMPOUNDS		

Canadian Regulations:

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Zinc ferrite brown spinel (C.I. Pigment Yellow	68187-51-9	10.00 - 30.00	
119)			
Xylenes (o-, m-, p- isomers)	1330-20-7	1.00 - 5.00	
Manganese oxide (MnO2)	1313-13-9	0.10 - 1.00	
Iron chromite brown spinel	12737-27-8	10.00 - 30.00	

POLYONE CORPORATION

PolvOne

MATERIAL SAFETY DATA SHEET **CEDAR 1**

Version Number 1.1 Revision Date 03/23/2014 Page 8 of 8 Print Date 3/31/2014

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1309-37-1
12737-27-8

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.