## MATERIAL SAFETY DATA SHEET NARANJA TRASLUCIDO PE (165C)

Version Number 1.1 Revision Date 03/23/2014 Page 1 of 6 Print Date 3/31/2014

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	NARANJA TRASLUCIDO PE (165C)		
Product code	:	CC10142129		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET NARANJA TRASLUCIDO PE (165C)

Version Number 1.1 Revision Date 03/23/2014 Page 2 of 6 Print Date 3/31/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne

## MATERIAL SAFETY DATA SHEET NARANJA TRASLUCIDO PE (165C)

Version Number 1.1 Revision Date 03/23/2014 Page 3 of 6 Print Date 3/31/2014

Storage		teep containers dry and tightly nd contamination. Keep in a contamination.		absorption	
8. ]	EXPOSURE	CONTROLS/PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protect	ive equipment normally re	equired.	
Eye/Face Protection	: S	afety glasses with side-shields	S		
Hand protection	: P	rotective gloves			
Skin and body protection	: L	Long sleeved clothing			
Additional Protective Measures	: S	: Safety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)	aj	ppropriate exhaust ventilation	at machinery.		
Exposure limit(s) Components	aj Value	ppropriate exhaust ventilation Exposure time		List:	
Exposure limit(s)	aj Value 6 mg/m3	ppropriate exhaust ventilation Exposure time Recommended exposure limit (REL):	at machinery.	List: NIOSH	
Exposure limit(s) Components	aj Value	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA):	at machinery.	List:	
Exposure limit(s) Components	aj Value 6 mg/m3	Exposure time Recommended exposure limit (REL): Time Weighted Average	at machinery.	List: NIOSH	
Exposure limit(s) Components	aj Value 6 mg/m3 0.8 mg/m3	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average	at machinery.           Exposure type	List: NIOSH Z3	
Exposure limit(s) Components	aj Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	at machinery.          Exposure type         Inhalable particulate.         Respirable dust.	List: NIOSH Z3 MX OEL	
Exposure limit(s) Components Silica, amorphous	aj Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	at machinery.          Exposure type         Inhalable particulate.         Respirable dust.	List: NIOSH Z3 MX OEL MX OEL	
Exposure limit(s) Components Silica, amorphous Form	ay Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : solid	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	at machinery.         Exposure type         Inhalable particulate.         Respirable dust.         OPERTIES         puration rate       : Not a	List: NIOSH Z3 MX OEL MX OEL	
Exposure limit(s) Components Silica, amorphous Form Appearance	ay Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : solid : pelle	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO Evaports Specific	at machinery.         Exposure type         Inhalable particulate.         Respirable dust.         OPERTIES         puration rate       : Not a fic Gravity	List: NIOSH Z3 MX OEL MX OEL	
Exposure limit(s) Components Silica, amorphous Form Appearance Colour	aj Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : solid : pelle : ORA	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Built CHEMICAL PRO	at machinery.         Exposure type         Inhalable particulate.         Respirable dust.         OPERTIES         puration rate       : Not a fic Gravity         ic Gravity       : Not a fic density	List: NIOSH Z3 MX OEL MX OEL applicable determined established	
Exposure limit(s)  Components Silica, amorphous  Form Appearance Colour Odour	aj Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 3 mg/m3 9. PHYSIC : solid : pelle : ORA : very	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Built Generation Evaports Specification NGE Built Generation faint Vaport	at machinery.         Exposure type         Inhalable particulate.         Respirable dust.         OPERTIES         ouration rate : Not a fic Gravity : Not a density : not	List: NIOSH Z3 MX OEL MX OEL applicable determined established pplicable	
Exposure limit(s) Components Silica, amorphous Form Appearance Colour	aj Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 3 mg/m3 9. PHYSIC : solid : pelle : ORA : very : Not of	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Built Generation Evaports Specification NGE Built Generation faint Vaport	at machinery.         Exposure type         Inhalable particulate.         Respirable dust.         OPERTIES         ouration rate : Not a fic Gravity : Not o density : Not o density : Not o density : not a ur density : not a ur density : not a	List: NIOSH Z3 MX OEL MX OEL applicable determined established	

#### 10. STABILITY AND REACTIVITY

: The product is stable if stored and handled as prescribed.

Stability

Hazardous Polymerization

: Will not occur.

3/6

PolyOne.

# MATERIAL SAFETY DATA SHEET NARANJA TRASLUCIDO PE (165C)

sion Date 03/23/20	14			Page Print Date 3/31		
Conditions to avoid			om oxidizing agents and on the overheat.	and open flame. To avoid therma		
Incompatible Materia	als	: Incompatible	Incompatible with strong acids and oxidizing agents.			
Hazardous decompos products	sition			noxide (CO), oxides of nitrogen and smoke are all possible.		
	1	1. TOXICOLOG	ICAL INFORMAT	ION		
health data for the ind	dividual con	nponents which co	mprise the mixture.	osure effects listed are based on e		
-			-	m have the following characteris		
CAS-No. 7631-86-9		emical Name morphous	Effect Irritant	Target OrganEyes, Respiratory system.		
7031-80-9	Silica, a	morphous	IIIItalit	Eyes, Respiratory system.		
Environmental Toxicity Bioaccumulation Potential Additional advice		<ul> <li>Chemicals are not readily available as they are bound within the polymer matrix.</li> <li>Chemicals are not readily available as they are bound within the polymer matrix.</li> <li>no data available</li> </ul>				
Additional advice		: no data availal	ble			
Additional advice			ble CONSIDERATION	IS		
		<ul> <li>13. DISPOSAL (</li> <li>Like most ther possible recyc generator of w classification,</li> </ul>	CONSIDERATION moplastic plastics the ling is preferred to de vaste material has the transportation and d			
	ging	<ul> <li>13. DISPOSAL</li> <li>Like most ther possible recyc generator of w classification, applicable fed</li> <li>Recycling is p material has th transportation</li> </ul>	CONSIDERATION rmoplastic plastics the ling is preferred to de vaste material has the transportation and de eral, state/provincial referred when possible the responsibility for p	te product can be recycled. When isposal or incineration. The e responsibility for proper waste isposal in accordance with and local regulations. ble. The generator of waste proper waste classification, rdance with applicable federal,		
Product	<u>ş</u> ing	<ul> <li>13. DISPOSAL (</li> <li>Like most then possible recyc generator of w classification, applicable fed.</li> <li>Recycling is p material has th transportation state/provincia</li> </ul>	CONSIDERATION rmoplastic plastics the ling is preferred to de vaste material has the transportation and de eral, state/provincial referred when possible the responsibility for p and disposal in accord	te product can be recycled. When isposal or incineration. The responsibility for proper waste isposal in accordance with and local regulations. ble. The generator of waste proper waste classification, rdance with applicable federal, ns.		
Product		<ul> <li>13. DISPOSAL (</li> <li>Like most ther possible recyc generator of w classification, applicable fed</li> <li>Recycling is p material has th transportation state/provincia</li> <li>14. TRANSPORT</li> </ul>	CONSIDERATION rmoplastic plastics the ling is preferred to de vaste material has the transportation and de eral, state/provincial referred when possible the responsibility for p and disposal in account and local regulation	te product can be recycled. Whe isposal or incineration. The responsibility for proper waste isposal in accordance with and local regulations. ble. The generator of waste proper waste classification, rdance with applicable federal, ns.		

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET NARANJA TRASLUCIDO PE (165C)

Version Number 1.1 Revision Date 03/23/2014 Page 5 of 6 Print Date 3/31/2014

IMO/IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
not applicable		
California Proposition 65	:	Not applicable
SARA Title III Section 302 Ext		
Unless specific chemicals are id	enti	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 Tox	tic C	Chemicals:
Unless specific chemicals are id	enti	fied under this section, this product is Not Applicable under this regulation
Canadian Regulations:		
National Pollutant Releas	se Ir	nventory (NPRI)
not applicable		
WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
DSL National Inventories:	:	
	:	
National Inventories:	:	Substances List (DSL) or are exempt.
National Inventories: Australia AICS	::	Substances List (DSL) or are exempt.

PolyOne

## MATERIAL SAFETY DATA SHEET NARANJA TRASLUCIDO PE (165C)

Version Number 1.1 Revision Date 03/23/2014 Page 6 of 6 Print Date 3/31/2014

Japan ENCS

: Not determined

Korea KECI : Listed

Philippines PICCS : Listed

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.