

### MATERIAL SAFETY DATA SHEET

## **GARNET METALLIC**

Version Number 1.2 Page 1 of 7
Revision Date 03/23/2014 Print Date 3/31/2014

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : GARNET METALLIC

Product code : CC10142346 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No.   | Weight percent |
|------------|-----------|----------------|
| Aluminum   | 7429-90-5 | 10 - 30        |

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

# POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically

irritating.

Ingestion : May be harmful if swallowed.

Eyes : Particulates, like other inert materials can be mechanically irritating.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.



#### MATERIAL SAFETY DATA SHEET

## **GARNET METALLIC**

Version Number 1.2 Page 2 of 7
Revision Date 03/23/2014 Print Date 3/31/2014

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIREFIGHTING MEASURES

Flash point : not applicable

Flammable Limits

Upper explosion limit : not applicable Lower explosion limit : not applicable Auto-ignition temperature : not applicable

Suitable extinguishing media : Class D special powder against metal fire, Dry chemical.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

: Dust containing aluminum powder can be explosive. Do not use a solid water stream as it may scatter and spread fire. Carbon dioxide

(CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other

hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat



## MATERIAL SAFETY DATA SHEET

# **GARNET METALLIC**

Version Number 1.2 Page 3 of 7
Revision Date 03/23/2014 Print Date 3/31/2014

only in areas with appropriate exhaust ventilation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required. If

dusty conditions occur wear appropriate respiratory protection.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves. Refer to equipment supplier to ensure protection.

Skin and body protection : Long sleeved clothing

Additional Protective

Measures

Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures

: Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



## MATERIAL SAFETY DATA SHEET

# **GARNET METALLIC**

 Version Number 1.2
 Page 4 of 7

 Revision Date 03/23/2014
 Print Date 3/31/2014

| Components      | Value    | Exposure time                     | Exposure type                         | List:    |
|-----------------|----------|-----------------------------------|---------------------------------------|----------|
| Aluminum 1 mg/n |          | Time Weighted Average (TWA):      | Respirable fraction.                  | ACGIH    |
|                 | 10 mg/m3 | Recommended exposure limit (REL): | Total                                 | NIOSH    |
|                 | 5 mg/m3  | Recommended exposure limit (REL): | Respirable.                           | NIOSH    |
|                 | 5 mg/m3  | Recommended exposure limit (REL): | Welding fume or pyrophoric powder. as | NIOSH    |
|                 | 15 mg/m3 | PEL:                              | Total dust. as Al                     | OSHA Z1  |
|                 | 5 mg/m3  | PEL:                              | Respirable dust. as Al                | OSHA Z1  |
|                 | 15 mg/m3 | Time Weighted Average (TWA):      | Total dust. as Al                     | OSHA Z1A |
|                 | 5 mg/m3  | Time Weighted Average (TWA):      | Respirable dust. as Al                | OSHA Z1A |
|                 | 5 mg/m3  | Time Weighted Average (TWA):      | Pyrophoric powder. as<br>Al           | OSHA Z1A |
|                 | 5 mg/m3  | Time Weighted Average (TWA):      | Fume. as Al                           | OSHA Z1A |
|                 | 5 mg/m3  | Time Weighted Average (TWA):      | Welding fume.                         | MX OEL   |
|                 | 10 mg/m3 | Time Weighted Average (TWA):      | Dust.                                 | MX OEL   |
|                 | 5 mg/m3  | Time Weighted Average (TWA):      | Pyrophoric powder.                    | MX OEL   |

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : solid Evapouration rate Not applicable Appearance powder, granular Specific Gravity Not determined Colour Bulk density Not determined : RED Odour : very faint Vapour pressure not applicable Melting point/range Not determined Vapour density not applicable **Boiling Point:** not applicable pН not applicable

Water solubility : insoluble

# 10. STABILITY AND REACTIVITY

Stability : The product is stable if stored and handled as prescribed.

Hazardous Polymerization : Will not occur.

Conditions to avoid : To avoid thermal decomposition, do not overheat. Keep away from

oxidizing agents and open flame.

Incompatible Materials : Incompatible with acids and bases., Oxidizing agents, Halogenated

compounds



## MATERIAL SAFETY DATA SHEET

## **GARNET METALLIC**

Version Number 1.2 Page 5 of 7
Revision Date 03/23/2014 Print Date 3/31/2014

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.   | Chemical Name | Effect           | Target Organ              |
|-----------|---------------|------------------|---------------------------|
| 7429-90-5 | Aluminum      | Irritant         | Skin, Respiratory system. |
|           |               | Systemic effects | Eyes, Skin, Respiratory   |
|           |               |                  | system.                   |

#### 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the

polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the

polymer matrix.

Additional advice : no data available

#### 13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

## 14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Refer to specific regulation.

IMO/IMDG (maritime) : Refer to specific regulation.

# 15. REGULATORY INFORMATION



### MATERIAL SAFETY DATA SHEET

# **GARNET METALLIC**

 Version Number 1.2
 Page 6 of 7

 Revision Date 03/23/2014
 Print Date 3/31/2014

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name                         | CAS-No.   | Weight percent |
|---------------------------------------|-----------|----------------|
| ALUMINUM (FUME OR DUST)ALUMINUM (FUME | 7429-90-5 | 10.00 - 30.00  |
| OR DUST)                              |           |                |

### Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No.   | Weight        | NPRI ID# |
|---------------|-----------|---------------|----------|
|               |           | percent       |          |
| Aluminum      | 7429-90-5 | 10.00 - 30.00 |          |

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No. 7429-90-5

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.



### MATERIAL SAFETY DATA SHEET

# **GARNET METALLIC**

Version Number 1.2 Page 7 of 7
Revision Date 03/23/2014 Print Date 3/31/2014

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Listed

Philippines PICCS : Listed

## 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.