MATERIAL SAFETY DATA SHEET PINK VANISH CORP

Version Number 1.1 Revision Date 03/23/2014

Page 1 of 7 Print Date 3/31/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PINK VANISH CORP
Product code	:	CC10142921
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Miscellaneous Zinc Compounds	0-05-5	1 - 5
Miscellaneous Zinc Compounds	0-31-7	10 - 30
Silica, amorphous	7631-86-9	1 - 5
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.

PolyOne.

MATERIAL SAFETY DATA SHEET PINK VANISH CORP

Version Number 1.1 Revision Date 03/23/2014 Page 2 of 7 Print Date 3/31/2014

	: Experience shows no unusual dermatitis hazard from routine handling				
Chronic exposure	: Refer to Section 11 for Toxicological Information.				
Medical Conditions : None known. Aggravated by Exposure: :					
	4. FIRST AID MEASURES				
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.				
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
	5. FIREFIGHTING MEASURES				
Flash point	: not applicable				
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 				
Upper explosion limit Lower explosion limit Auto-ignition temperature	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne 				
Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive 				
Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen 				
Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 				
Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES Wear appropriate personal protection during cleanup, such as 				

PolyOne.

MATERIAL SAFETY DATA SHEET PINK VANISH CORP

Version Number 1.1 Revision Date 03/23/2014 Page 3 of 7 Print Date 3/31/2014

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	:	: Keep containers dry and tightly closed to avoid moisture absorpti and contamination. Keep in a dry, cool place.			
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields			
Hand protection	:	Protective gloves			
Skin and body protection	:	Long sleeved clothing			
Additional Protective Measures	:	Safety shoes			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

PolyOne

MATERIAL SAFETY DATA SHEET **PINK VANISH CORP**

Version Number 1.1 Revision Date 03/23/2014 Page 4 of 7 Print Date 3/31/2014

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

: pellets
: PINK
: very faint
: Not determined
: not applicable
: insoluble

: solid

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- Not applicableNot determinedNot established
- : not applicable
- : not applicable
- : not applicable

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

MATERIAL SAFETY DATA SHEET PINK VANISH CORP

Version Number 1.1 Revision Date 03/23/2014

Page 5 of 7 Print Date 3/31/2014

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
0-05-5	Miscellaneous Zinc	Systemic effects	Eyes, Skin, Respiratory
	Compounds		system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET PINK VANISH CORP

applic ontaminated packaging : Recyc materi transp state/p IA. TRA S. DOT Classification : Not re CAO/IATA : Refer MO/IMDG (maritime) : Refer IS. REGU S Regulations: OSHA Status : Classi TSCA Status : All cc TSCA S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not ap 65 ARA Title III Section 302 Extremely Haz	ification, transportation and disposal in accordance with cable federal, state/provincial and local regulations. reling is preferred when possible. The generator of waste rial has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, /provincial and local regulations. ANSPORT INFORMATION regulated for transportation. r to specific regulation. r to specific regulation. BULATORY INFORMATION sified as hazardous based on components. components of this product are listed on or exempt from the A Inventory.
materi transp state/p 14. TRA S. DOT Classification : Not re CAO/IATA : Refer MO/IMDG (maritime) : Refer 15. REGI S Regulations: OSHA Status : Classi TSCA Status : All co TSCA S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not ap 65 ARA Title III Section 302 Extremely Haz	rial has the responsibility for proper waste classification, portation and disposal in accordance with applicable federal, /provincial and local regulations. ANSPORT INFORMATION regulated for transportation. r to specific regulation. r to specific regulation. SULATORY INFORMATION sified as hazardous based on components. components of this product are listed on or exempt from the A Inventory.
T.S. DOT Classification : Not re CAO/IATA : Refer MO/IMDG (maritime) : Refer IS Regulations: IS Regulations: OSHA Status : Classi TSCA Status : All constances Not regulations: : Status California Proposition : Not applicable California Proposition : Not applicable ARA Title III Section 302 Extremely Haz	regulated for transportation. r to specific regulation. r to specific regulation. SULATORY INFORMATION sified as hazardous based on components. components of this product are listed on or exempt from the A Inventory.
CAO/IATA : Refer MO/IMDG (maritime) : Refer IS Regulations: OSHA Status : Classi TSCA Status : All co TSCA S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not ap 65 ARA Title III Section 302 Extremely Haz	r to specific regulation. r to specific regulation. GULATORY INFORMATION sified as hazardous based on components. components of this product are listed on or exempt from the A Inventory.
MO/IMDG (maritime) : Refer 15. REGI S Regulations: OSHA Status : Classi TSCA Status : All co TSCA S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not ap 65 ARA Title III Section 302 Extremely Haz	r to specific regulation. GULATORY INFORMATION sified as hazardous based on components. components of this product are listed on or exempt from the A Inventory.
15. REGUE 'S Regulations: OSHA Status : Classi TSCA Status : All cc TSCA Status : All cc 'S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not applicable ARA Title III Section 302 Extremely Hazardous	SULATORY INFORMATION sified as hazardous based on components. components of this product are listed on or exempt from the A Inventory.
S Regulations: OSHA Status : Classi TSCA Status : All co TSCA S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not ap 65	sified as hazardous based on components. components of this product are listed on or exempt from the A Inventory.
OSHA Status : Classi TSCA Status : All co TSCA S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not ap 65	components of this product are listed on or exempt from the A Inventory.
TSCA Status : All co TSCA S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not ap 65 ARA Title III Section 302 Extremely Haz	components of this product are listed on or exempt from the A Inventory.
TSCA S. EPA CERCLA Hazardous Substances not applicable California Proposition : Not ap 65 ARA Title III Section 302 Extremely Haz	A Inventory.
not applicable California Proposition : Not ap 65 ARA Title III Section 302 Extremely Haz	
California Proposition : Not ap 65 ARA Title III Section 302 Extremely Haz	s (40 CFR 302)
65 ARA Title III Section 302 Extremely Haz	
	applicable
nless specific chemicals are identified une	zardous Substance
	nder this section, this product is Not Applicable under this regula
ARA Title III Section 313 Toxic Chemica	
	cals:
Chemical Name ZINC COMPOUNDS	nder this section, this product is Not Applicable under this regula
ZINC COMPOUNDS	nder this section, this product is Not Applicable under this regula CAS-No. Weight percent
ZINC COMPOUNDS	nder this section, this product is Not Applicable under this regula

PolyOne

MATERIAL SAFETY DATA SHEET PINK VANISH CORP

Version Number 1.1 Revision Date 03/23/2014 Page 7 of 7 Print Date 3/31/2014

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Miscellaneous Zinc Compounds	0-05-5	1.00 - 5.00	241
	0-31-7	10.00 - 30.00	241
Xanthylium, 3,6-bis(diethylamino)-9-[2-	73398-89-7	0.10 - 1.00	
(methoxycarbonyl)phenyl]-, (T-4)-			
tetrachlorozincate(2-) (2:1)			

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
7631-86-9	

DSL

DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

ot determined
ot determined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.