*PolyOne* 

## MATERIAL SAFETY DATA SHEET **WETLANDS**

Version Number 1.1 Revision Date 03/23/2014

Page 1 of 8 Print Date 3/31/2014

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WETLANDS
Product code	:	CC10143264
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium stearate	1592-23-0	1 - 5
Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	68412-38-4	10 - 30
Rutile, antimony chromium buff	68186-90-3	10 - 30
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion Eyes	<ul><li>May be harmful if swallowed.</li><li>Particulates, like other inert materials can be mechanically irritating.</li></ul>



# MATERIAL SAFETY DATA SHEET **WETLANDS**

sion Date 03/23/2014	Page 2 Print Date 3/31/2
Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
em onic exposure	
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Auto-ignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in



# MATERIAL SAFETY DATA SHEET **WETLANDS**

		plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat
		only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne.

## MATERIAL SAFETY DATA SHEET **WETLANDS**

Version Number 1.1 Revision Date 03/23/2014 Page 4 of 8 Print Date 3/31/2014

Components	Value	Exposure time	Exposure type	List:
Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	1 mg/m3	Recommended exposure limit (REL):	Fume. as Mn	NIOSH
	3 mg/m3	Short Term Exposure Limit (STEL):	Fume. as Mn	NIOSH
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range
- : solid
  : pellets
  : BROWN
  : very faint
  : Not determined
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicableNot determinedNot established
- : not applicable
- : not applicable



## MATERIAL SAFETY DATA SHEET **WETLANDS**

#### Version Number 1.1 Revision Date 03/23/2014

Page 5 of 8 Print Date 3/31/2014

Boiling Point: Water solubility	: not applicable pH : not applicable : insoluble
	10. STABILITY AND REACTIVITY
Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.</li> </ul>

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68412-38-4	Manganese antimony	Irritant	Eyes, Skin.
	titanium brown rutile (C.I.		
	Pigment Yellow 164)		
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat

Carcinogenicity

PolyOne

## MATERIAL SAFETY DATA SHEET **WETLANDS**

#### Version Number 1.1 Revision Date 03/23/2014

Page 6 of 8 Print Date 3/31/2014

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	<ul> <li>Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> <li>Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> </ul>
	state/provincial and local regulations. 14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION

POLYONE CORPORATION

PolyOne.

# MATERIAL SAFETY DATA SHEET **WETLANDS**

sion Date 03/23/2014				Pr	int Date	Page 7 3/31/2
US Regulations:						
OSHA Status : Classified as ha	zardous b	ased on co	mponent	s.		
TSCA Status : All component TSCA Inventor		roduct are	listed on	or exen	npt from t	the
US. EPA CERCLA Hazardous Substances (40 CFR	302)					
not applicable						
California Proposition : WARNING! T 65 California to ca			a chemio	cal knov	vn to the s	State of
SARA Title III Section 302 Extremely Hazardous Su	ubstance					
Unless specific chemicals are identified under this se	action this	nroduct i	Not Am	liceble	under thi	c rooul
	ection, this	s product is CAS-No			under thi percent	s regula
Unless specific chemicals are identified under this se	ection, this		•		percent	s regula
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III		CAS-No	-4	Weight	percent - 30.00	s regula
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS		CAS-No 68412-38	-4	Weight 10.00 -	percent - 30.00	s regula
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS		CAS-No 68412-38	-4	Weight 10.00 -	percent - 30.00	s regula
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations:		CAS-No 68412-38	-4	Weight 10.00 -	percent - 30.00	s regula
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS		CAS-No 68412-38 68186-90	-4 -3 Weight	Weight 10.00 - 10.00 -	percent - 30.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI)	[	CAS-No 68412-38 68186-90 0.	-4 -3	Weight 10.00 - 10.00 -	percent · 30.00 · 30.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum oxide Manganese antimony titanium brown rutile (C.I.	CAS-N	CAS-No 68412-38 68186-90 o.	-4 -3 Weight percent	Weight 10.00 - 10.00 - .00	percent · 30.00 · 30.00	
MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum oxide	CAS-N	CAS-No 68412-38 68186-90 o.	-4 -3 Weight percent 0.10 - 1 10.00 -	Weight 10.00 - 10.00 - .00 30.00	percent · 30.00 · 30.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum oxide Manganese antimony titanium brown rutile (C.I.	CAS-N	CAS-No 68412-38 68186-90 0. 8-1 38-4	-4 -3 Weight percent 0.10 - 1	Weight 10.00 - 10.00 - .00 30.00 30.00	percent · 30.00 · 30.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum oxide Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	CAS-N 1344-22 68412-2	CAS-No 68412-38 68186-90 0. 8-1 38-4	-4 -3 Weight percent 0.10 - 1 10.00 -	Weight 10.00 - 10.00 - .00 30.00 30.00	percent · 30.00 · 30.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Aluminum oxide Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	CAS-N 1344-22 68412-2	CAS-No 68412-38 68186-90 0. 8-1 38-4	-4 -3 Weight percent 0.10 - 1 10.00 -	Weight 10.00 - 10.00 - .00 30.00 30.00	percent · 30.00 · 30.00	

PolvOne

## MATERIAL SAFETY DATA SHEET **WETLANDS**

Version Number 1.1 Page 8 of 8 Print Date 3/31/2014 Revision Date 03/23/2014 CAS-No. 68412-38-4 68186-90-3 DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. National Inventories: Australia AICS Listed : China IECS Listed : **Europe EINECS** : Listed Japan ENCS Not determined • Korea KECI Listed : **Philippines PICCS** : Listed **16. OTHER INFORMATION** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.