PolvOne

MATERIAL SAFETY DATA SHEET LC COWLES MIX RMC TEST

Version Number 1.1 Revision Date 03/30/2014 Page 1 of 7 Print Date 4/8/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LC COWLES MIX RMC TEST
Product code	:	CC10144598
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Iron oxide	1309-37-1	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Calcium carbonate	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion Eyes Skin	May be harmful if swallowed.Irritating to eyes and respiratory system.Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET LC COWLES MIX RMC TEST

Version Number 1.1 Revision Date 03/30/2014 Page 2 of 7 Print Date 4/8/2014

n of fumes from tion after significant . Seek medical east 15 minutes. If ey irritation persists
tion after significant •. Seek medical east 15 minutes. If ey
east 15 minutes. If ey
irritation persists
BA) used in positive tion of airborne
oxides of nitrogen re all possible.
eanup, such as
ns, water courses or nment.
, silica gel, acid material in

PolyOne.

MATERIAL SAFETY DATA SHEET LC COWLES MIX RMC TEST

Version Number 1.1 Revision Date 03/30/2014 Page 3 of 7 Print Date 4/8/2014

Handling	: Heat only in areas with appropriate exhaust ventilation.	
Storage	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.	
8. EXI	POSURE CONTROLS/PERSONAL PROTECTION	
Respiratory protection	: Under normal handling conditions a respirator may not be required.	
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	
Exposure limit(s)		

PolyOne

MATERIAL SAFETY DATA SHEET LC COWLES MIX RMC TEST

Version Number 1.1 Revision Date 03/30/2014 Page 4 of 7 Print Date <u>4/8/2014</u>

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range **Boiling Point:** Water solubility

: liquid : viscous, liquid : RED : very faint : not applicable : not applicable : immiscible

:

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pН

: Not established Not determined : Not applicable : not determined :

Not determined

: not applicable :

10. STABILITY AND REACTIVITY

Stability The product is stable if stored and handled as prescribed. : Hazardous Polymerization Will not occur. :

Conditions to avoid

Keep away from oxidizing agents and open flame.

MATERIAL SAFETY DATA SHEET LC COWLES MIX RMC TEST

Version Number 1.1 Revision Date 03/30/2014 Page 5 of 7 Print Date 4/8/2014

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	Does not bioaccumulate.
Additional advice	:	no data available

13. DISPOSAL CONSIDERATIONS

PolyOne.

MATERIAL SAFETY DATA SHEET LC COWLES MIX RMC TEST

Version Number 1.1 Revision Date 03/30/2014	Page 6 of 7 Print Date <i>4/8/2014</i>
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO/IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 Ex	stremely Hazardous Substance
Unless specific chemicals are	dentified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic Chemicals:
Unless specific chemicals are	dentified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	

PolyOne

MATERIAL SAFETY DATA SHEET LC COWLES MIX RMC TEST

Version Number 1.1 Revision Date 03/30/2014

_

Page 7 of 7 Print Date 4/8/2014

Chemical Name		iventory (NPRI)	AS-No.	Weight	NPRI ID#
				percent	
Phenol, nonyl-, phosphite (3:	1)	26	5523-78-4	1.00 - 5.00	
				1.00 - 5.00	
				1.00 - 5.00	
WHMIS Classification WHMIS Ingredient Disc CAS-No. 1309-37-1 7631-86-9 DSL					n Domestic
ational Inventories:			2) of the end	F	
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Listed			
		Net let me 'n d			
Japan ENCS	:	Not determined			
Japan ENCS Korea KECI	:	Not determined			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.