PolvOne

MATERIAL SAFETY DATA SHEET **PG 145799.00 PU LC UV**

Version Number 1.1 Revision Date 03/30/2014 Page 1 of 6 Print Date 4/8/2014

1.	PROD	UCT AND COMPANY IDENTIFICATION	
POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012			
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	PG 145799.00 PU LC UV	
Product code	:	CC10145799	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: Irritating to eyes and respiratory system.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 145799.00 PU LC UV**

Version Number 1.1 Revision Date 03/30/2014 Page 2 of 6 Print Date 4/8/2014

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable Not applicable Carbon dioxide blanket, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation.

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 145799.00 PU LC UV**

Version Number 1.1 Revision Date 03/30/2014

_

Page 3 of 6 Print Date 4/8/2014

Storage	:	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.	
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION	
Respiratory protection	:	Under normal handling conditions a respirator may not be required.	
Eye/Face Protection	:	Safety glasses with side-shields	
Hand protection	:	Protective gloves	
Skin and body protection	:	Long sleeved clothing	
Additional Protective Measures	:	Safety shoes	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	
Exposure limit(s)			

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous,	0.8 mg/m3	Time Weighted Average		Z3
fumed, crystal-free		(TWA):		
	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Colour
Odour
Melting point/range
Boiling Point:
Water solubility

liquid viscous, liquid PURPLE very faint not applicable not applicable immiscible

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH

Not established
Not determined
Not applicable
not determined
Not determined
not applicable

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame.

PolvOne.

MATERIAL SAFETY DATA SHEET PG 145799.00 PU LC UV

Version Number 1.1 Revision Date 03/30/2014 Page 4 of 6 Print Date <u>4</u>/8/2014

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed,	Irritant	Eyes, Respiratory system.
	crystal-free		

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.	
Bioaccumulation Potential	: Does not bioaccumulate.	
Additional advice	: no data available	
	13. DISPOSAL CONSIDERATIONS	
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
	14. TRANSPORT INFORMATION	

olyOne

MATERIAL SAFETY DATA SHEET **PG 145799.00 PU LC UV**

Page 5 of 6 Print Date 4/8/2014 Version Number 1.1 Revision Date 03/30/2014 U.S. DOT Classification : Not regulated for transportation. ICAO/IATA Not regulated for transportation. : IMO/IMDG (maritime) : Not regulated for transportation. **15. REGULATORY INFORMATION US Regulations: OSHA** Status : Classified as hazardous based on components. **TSCA Status** : All components of this product are listed on or exempt from the TSCA Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name CAS-No. Weight NPRI ID# percent Bis (2-ethylhexyl) adipate 103-23-1 10.00 - 30.00 WHMIS Classification : Not controlled. DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt.

National Inventories:

PolyOne

MATERIAL SAFETY DATA SHEET **PG 145799.00 PU LC UV**

Version Number 1.1 Revision Date 03/30/2014 Page 6 of 6 Print Date 4/8/2014

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.