PolvOne

MATERIAL SAFETY DATA SHEET LT GRAY TPE #2

Version Number 1.1 Revision Date 03/29/2014

Page 1 of 8 Print Date 4/6/2014

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012			
Product name		LT GRAY TPE #2	
Product code	-	CC10146240	
Chemical Name	•	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Amines, bis(hydrogenated tallow alkyl), oxidized	143925-92-2	1 - 5
Rutile, antimony chromium buff	68186-90-3	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Zinc stearate	557-05-1	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Ingestion, Skin contact

Acute exposure



MATERIAL SAFETY DATA SHEET LT GRAY TPE #2

es. perience shows no unusual dermatitis hazard from routine handling. fer to Section 11 for Toxicological Information. one known. 4. FIRST AID MEASURES love to fresh air in case of accidental inhalation of fumes from verheating or combustion. When symptoms persist or in all cases of pubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice.
 itating. ay be harmful if swallowed. sin particles, like other inert materials, are mechanically irritating to es. perience shows no unusual dermatitis hazard from routine handling. fer to Section 11 for Toxicological Information. one known. 4. FIRST AID MEASURES Iove to fresh air in case of accidental inhalation of fumes from verheating or combustion. When symptoms persist or in all cases of pubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice.
ay be harmful if swallowed. sin particles, like other inert materials, are mechanically irritating to es. perience shows no unusual dermatitis hazard from routine handling. fer to Section 11 for Toxicological Information. one known. 4. FIRST AID MEASURES love to fresh air in case of accidental inhalation of fumes from verheating or combustion. When symptoms persist or in all cases of pubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice. inse immediately with plenty of water, also under the eyelids, for at
es. perience shows no unusual dermatitis hazard from routine handling. fer to Section 11 for Toxicological Information. one known. 4. FIRST AID MEASURES love to fresh air in case of accidental inhalation of fumes from verheating or combustion. When symptoms persist or in all cases of bubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice. inse immediately with plenty of water, also under the eyelids, for at
perience shows no unusual dermatitis hazard from routine handling. fer to Section 11 for Toxicological Information. one known. 4. FIRST AID MEASURES love to fresh air in case of accidental inhalation of fumes from verheating or combustion. When symptoms persist or in all cases of bubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice. inse immediately with plenty of water, also under the eyelids, for at
A. FIRST AID MEASURES Iove to fresh air in case of accidental inhalation of fumes from verheating or combustion. When symptoms persist or in all cases of pubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice. inse immediately with plenty of water, also under the eyelids, for at
 4. FIRST AID MEASURES Iove to fresh air in case of accidental inhalation of fumes from verheating or combustion. When symptoms persist or in all cases of pubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice. inse immediately with plenty of water, also under the eyelids, for at
love to fresh air in case of accidental inhalation of fumes from verheating or combustion. When symptoms persist or in all cases of bubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice. inse immediately with plenty of water, also under the eyelids, for at
verheating or combustion. When symptoms persist or in all cases of pubt seek medical advice. o not induce vomiting without medical advice. When symptoms ersist or in all cases of doubt seek medical advice. inse immediately with plenty of water, also under the eyelids, for at
ersist or in all cases of doubt seek medical advice. inse immediately with plenty of water, also under the eyelids, for at
Vash off with soap and plenty of water. If skin irritation persists eek medical attention.
FIREFIGHTING MEASURES
ot applicable
ot applicable
ot applicable
ot applicable
arbon dioxide blanket, Water spray, Dry powder, Foam.
ullface self-contained breathing apparatus (SCBA) used in positive ressure mode should be worn to prevent inhalation of airborne
ontaminants. arbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
NOx), other hazardous materials, and smoke are all possible.
IDENTAL RELEASE MEASURES
Vear appropriate personal protection during cleanup, such as
npervious gloves, boots and coveralls.



MATERIAL SAFETY DATA SHEET LT GRAY TPE #2

ersion Number 1.1 evision Date 03/29/2014	Page 3 o Print Date <i>4/6/20</i>
Methods for cleaning up	be allowed to enter drains, water courses or the soil.Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	OSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET LT GRAY TPE #2

Version Number 1.1 Revision Date 03/29/2014 Page 4 of 8 Print Date 4/6/2014

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Zinc stearate	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	10 mg/m3	Time Weighted Average (TWA):		ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

PolyOne

MATERIAL SAFETY DATA SHEET LT GRAY TPE #2

Version Number 1.1 Revision Date 03/29/2014

Page 5 of 8 Print Date <u>4/6/2014</u>

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	:::::::::::::::::::::::::::::::::::::::	solid pellets GREY very faint Not determined not applicable insoluble	Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH		Not determined Not established not applicable not applicable
		10. STABILITY AND RE	ACTIVITY		
Stability		: The product is stable if s	stored and handled as p	resc	ribed.
Hazardous Polymerization		: Will not occur.			
Conditions to avoid		: Keep away from oxidizi decomposition, do not o		ne.	To avoid thermal
Incompatible Materials		: Incompatible with strong	g acids and oxidizing ag	gent	s.
Hazardous decomposition products		: Carbon dioxide (CO2), o (NOx), other hazardous			-

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-	Irritant	Eyes, Skin, Respiratory
	bis(2,2,6,6-tetramethyl-4-		system.
	piperidinyl)-,polymer with		
	2,4,6-trichloro-1,3,5-		
	triazine, reaction products		
143925-92-2	Amines, bis(hydrogenated	sensitizer	Skin.
	tallow alkyl), oxidized		
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
557-05-1	Zinc stearate	Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
---------	---------------	-------	-------	---------

PolyOne

MATERIAL SAFETY DATA SHEET LT GRAY TPE #2

Version Number 1.1

Page 6 of 8 Print Date 4/6/2014

version	NUMD	er 1.1	
Revision	Date	03/29/201	4

70624-18-9	1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5- triazine, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat
557-05-1	Zinc stearate	Oral LD50	> 10 gm/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET LT GRAY TPE #2

rsion Number 1.1 vision Date 03/29/2014				Page 7 of 8 Print Date <i>4/6/2014</i>			
U.S. DOT Classification	: Not regulated for	Not regulated for transportation.					
ICAO/IATA	: Refer to specific	Refer to specific regulation.					
IMO/IMDG (maritime)	: Refer to specific	Refer to specific regulation.					
	15. REGULATOR	RY INFO	RMATION	I			
US Regulations:							
OSHA Status : Classified as hazardous based on components.							
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.							
US. EPA CERCLA Hazardous S	ubstances (40 CFR	302)					
not applicable							
California Proposition 65	: Not applicable						
SARA Title III Section 302 Extra	emely Hazardous Su	ibstance					
Unless specific chemicals are ide	-		s product is	Not Applic	able under this	regulation	
e mess specific chemicals are lac	interioù under une se	etion, tim	product is	itot rippilo		regulation	
SARA Title III Section 313 Toxi	c Chemicals:						
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation							
CHECKING CHECKING CHECKING CHECKING			CAS-No.		Weight percent 1.00 - 5.00		
CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY			68186-90-3		1.00 - 3.00		
COMPOUNDSCHROMIUM COMPOUNDS							
ZINC COMPOUNDS		557-05-1	1.0	00 - 5.00			
Canadian Regulations:							
National Pollutant Release	e Inventory (NPRI)						
Chemical Name	<u> </u>	CAS-N	0.	Weight percent	NPRI ID	¥	
Rutile, antimony chromium bu	ff	68186-	90-3	1.00 - 5.00)	_	
Zinc stearate			557-05-1		1.00 - 5.00		

PolvOne

MATERIAL SAFETY DATA SHEET LT GRAY TPE #2

Version Number 1.1 Revision Date 03/29/2014

Page 8 of 8 Print Date 4/6/2014

WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 68186-90-3 7631-86-9 557-05-1 DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS : Listed China IECS : Listed Europe EINECS : Listed Japan ENCS Not determined : Korea KECI : Not determined **Philippines PICCS** : Not determined **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.