PolvOne.

### **MATERIAL SAFETY DATA SHEET** PC STOCK GRAY #101

Version Number 1.2 Revision Date 10/19/2012

Page 1 of 7 Print Date 10/22/2012

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	PC STOCK GRAY #101			
Product code	:	CC10146583			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

#### : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium carbonate	1317-65-3	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne

## MATERIAL SAFETY DATA SHEET **PC STOCK GRAY #101**

Version Number 1.2 Revision Date 10/19/2012 Page 2 of 7 Print Date 10/22/2012

Medical Conditions	: None known.			
Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
	5. FIREFIGHTING MEASURES			
Flash point	: not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> </ul>			
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.			
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.			
Unusual Fire/Explosion Hazards	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.			
	7. HANDLING AND STORAGE			

PolyOne.

## MATERIAL SAFETY DATA SHEET **PC STOCK GRAY #101**

sion Number 1.2 vision Date 10/19/2012		Page 3 of Print Date 10/22/201
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

## MATERIAL SAFETY DATA SHEET **PC STOCK GRAY #101**

Version Number 1.2 Revision Date 10/19/2012 Page 4 of 7 Print Date 10/22/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

## : solid Evaporation rate

pellets
GREY
very faint
Not determined
not applicable
insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- Not applicableNot determined
- : Not established
- : not applicable
- : not applicable
- : not applicable

#### **10. STABILITY AND REACTIVITY**

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

## MATERIAL SAFETY DATA SHEET **PC STOCK GRAY #101**

#### Version Number 1.2 Revision Date 10/19/2012

Page 5 of 7 Print Date 10/22/2012

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	Not readily biodegradable.	
Environmental Toxicity	Chemicals are not readily available as they are bound within polymer matrix.	ı the
Bioaccumulation Potential	Chemicals are not readily available as they are bound within polymer matrix.	the
Additional advice	no data available	
	DISPOSAL CONSIDERATIONS	
Product	Like most thermoplastic plastics the product can be recycled possible recycling is preferred to disposal or incineration. T generator of waste material has the responsibility for proper classification, transportation and disposal in accordance with	The waste

PolyOne.

# MATERIAL SAFETY DATA SHEET **PC STOCK GRAY #101**

ision Date 10/19/2012		Page 6 of Print Date 10/22/20			
	8	applicable federal, state/provincial and local regulations.			
Contaminated packaging	r t	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14.	TRANSPORT INFORMATION			
U.S. DOT Classification	: 1	Not regulated for transportation.			
ICAO/IATA	: I	Refer to specific regulation.			
IMO/IMDG (maritime)	: I	Refer to specific regulation.			
	15.	REGULATORY INFORMATION			
US Regulations:					
OSHA Status	: (	Classified as hazardous based on components.			
TSCA Status		All components of this product are listed on or exempt from the			
		ΓSCA Inventory.			
		i SCA niventory.			
US. EPA CERCLA Hazardov					
US. EPA CERCLA Hazardon not applicable					
	us Substa				
not applicable California Proposition	us Substa n : 1	ances (40 CFR 302) Not applicable			
not applicable California Proposition 65 SARA Title III Section 302 H	us Substa n : 1 Extremely	ances (40 CFR 302) Not applicable y Hazardous Substance			
not applicable California Proposition 65 SARA Title III Section 302 H	us Substa n : 1 Extremely	ances (40 CFR 302) Not applicable y Hazardous Substance			
not applicable California Proposition 65 SARA Title III Section 302 H Unless specific chemicals are	us Substa n : 1 Extremely e identific	ances (40 CFR 302) Not applicable y Hazardous Substance ed under this section, this product is Not Applicable under this regulat			
not applicable California Proposition 65 SARA Title III Section 302 H Unless specific chemicals are SARA Title III Section 313 T	us Substa n : 1 Extremely e identific Foxic Ch	ances (40 CFR 302) Not applicable y Hazardous Substance ed under this section, this product is Not Applicable under this regulati emicals:			
not applicable California Proposition 65 SARA Title III Section 302 H Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are	us Substa n : 1 Extremely e identific Foxic Ch	ances (40 CFR 302) Not applicable y Hazardous Substance ed under this section, this product is Not Applicable under this regulati emicals:			
not applicable California Proposition 65 SARA Title III Section 302 H Unless specific chemicals are SARA Title III Section 313 T	us Substa n : 1 Extremely e identific Foxic Ch	ances (40 CFR 302) Not applicable y Hazardous Substance ed under this section, this product is Not Applicable under this regulati			
not applicable California Proposition 65 SARA Title III Section 302 H Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are	us Substa n : M Extremely e identific Foxic Ch e identific	ances (40 CFR 302) Not applicable y Hazardous Substance ed under this section, this product is Not Applicable under this regulati emicals: ed under this section, this product is Not Applicable under this regulati			

PolyOne

## MATERIAL SAFETY DATA SHEET **PC STOCK GRAY #101**

Version Number 1.2 Revision Date 10/19/2012 Page 7 of 7 Print Date 10/22/2012

Chromium (III) oxide			1308-38-9	0.10 - 1.00	
WHMIS Classification	n :	D2A			
WHMIS Ingredient Dis	sclosu	re List			
CAS-No. 7631-86-9					
DSL	:		s of this product (DSL) or are exe	are on the Canadian empt.	Domestic
National Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16 OTHER I	NFORMATION	I	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.