PolyOne

MATERIAL SAFETY DATA SHEET **PX7 NUTRIA BEIGE**

Version Number 1.2 Revision Date 03/29/2014

Page 1 of 8 Print Date 4/6/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PX7 NUTRIA BEIGE
Product code	:	CC10146770
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.

PolyOne.

MATERIAL SAFETY DATA SHEET **PX7 NUTRIA BEIGE**

Version Number 1.2 Revision Date 03/29/2014 Page 2 of 8 Print Date 4/6/2014

	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIREFIGHTING MEASURES		
Flash point	: not applicable		
Flash point Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature	 not applicable not applicable not applicable carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne 		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive 		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen 		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES Wear appropriate personal protection during cleanup, such as 		

PolyOne.

MATERIAL SAFETY DATA SHEET **PX7 NUTRIA BEIGE**

Version Number 1.2 Revision Date 03/29/2014

	Page 3 of 8
Print Date	e 4/6/2014

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	age : Keep containers dry and tightly closed to avoid moistur and contamination. Keep in a dry, cool place.	
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET **PX7 NUTRIA BEIGE**

Version Number 1.2 Revision Date 03/29/2014 Page 4 of 8 Print Date 4/6/2014

Components	Value	Exposure time	Exposure type	List:
Nickel antimony	0.015	Recommended exposure	as Ni	NIOSH
yellow rutile (C.I. Pigment Yellow 53)	mg/m3	limit (REL):		
rightent renow 55)	1 mg/m3	PEL:	as Ni	OSHA Z1
	1 mg/m3	Time Weighted Average	as Ni	OSHA ZIA
	8	(TWA):		
	0.2 mg/m3	Time Weighted Average	Inhalable fraction. as	ACGIH
		(TWA):	Ni	
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range
- : solid : pellets : TAN
- : very faint
- : Not determined
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicableNot determinedNot establishednot applicable
- : not applicable



MATERIAL SAFETY DATA SHEET **PX7 NUTRIA BEIGE**

Version Number 1.2 Revision Date 03/29/2014

_

_

Page 5 of 8 Print Date 4/6/2014

Boiling Point: Water solubility	: not applicable : insoluble	pH	: not applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: The product is sta	ble if stored and hand	dled as prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	00	open flame. To avoid thermal
Incompatible Materials	: Incompatible with	strong acids and oxid	dizing agents.
Hazardous decomposition products		,.	de (CO), oxides of nitrogen smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.
8007-18-9	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	Irritant	Eyes, Skin.
		sensitizer	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
8007-18-9	Nickel antimony yellow rutile	no	1	no
	(C.I. Pigment Yellow 53)			
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

PolyOne

MATERIAL SAFETY DATA SHEET **PX7 NUTRIA BEIGE**

Version Number 1.2 Revision Date 03/29/2014 Page 6 of 8 Print Date 4/6/2014

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Nickel antimony yellow rutile (C.I. Pigment Yellow 53) 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney and muscle effects.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
	6/8

olvOne

MATERIAL SAFETY DATA SHEET **PX7 NUTRIA BEIGE**

Version Number 1.2 Revision Date 03/29/2014 Page 7 of 8 Print Date <u>4/6/2014</u>

not applicable

California Proposition:WARNING! This product contains a chemical known to the State of
California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent	
NICKEL COMPOUNDSNICKEL	8007-18-9	10.00 - 30.00	
COMPOUNDSANTIMONY COMPOUNDS			

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Nickel antimony yellow rutile (C.I. Pigment	8007-18-9	10.00 - 30.00	
Yellow 53)			
		10.00 - 30.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
8007-18-9
7631-86-9

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed

:

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **PX7 NUTRIA BEIGE**

Version Number 1.2 Revision Date 03/29/2014 Page 8 of 8 Print Date 4/6/2014

Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.