MATERIAL SAFETY DATA SHEET 030RD2045 NEW RED HMF

Version Number 1.1 Revision Date 03/29/2014 Page 1 of 6 Print Date <u>4/7/2014</u>

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number		1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	030RD2045 NEW RED HMF
Product code	:	CC10149037
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
C.I. Pigment red 48, calcium salt	7023-61-2	10 - 30
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET 030RD2045 NEW RED HMF

Version Number 1.1 Revision Date 03/29/2014 Page 2 of 6 Print Date 4/7/2014

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 030RD2045 NEW RED HMF

ion Number 1.1 sion Date 03/29/2014			Prin	Page 3 t Date 4/7/2		
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.					
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.					
8.1	EXPOSURE	CONTROLS/PERSONA	AL PROTECTION			
Respiratory protection	: N	lo personal respiratory prot	ective equipment normally	required.		
Eye/Face Protection	: S	afety glasses with side-shie	elds			
Hand protection	: P	rotective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	: Safety shoes				
General Hygiene Considerations			good industrial hygiene and a breaks and at the end of we			
Engineering measures		leat only in areas with appr ppropriate exhaust ventilat	opriate exhaust ventilation.	Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1		
	15 mg/m3	PEL:	Total dust.	OSHA Z1		
	10 mg/m3	Time Weighted Averag (TWA):	e	MX OEL		
	20 mg/m3	Short Term Exposure Lin (STEL):	nit	MX OEL		
	9. PHYSI	CAL AND CHEMICAL I	PROPERTIES			
Form	: solid	l Ev	apouration rate : Not	applicable		
Appearance	: pelle		-	determined		
Colour	: RED		5	established		
Odour	•			applicable		
Melting point/range	ЪТ.	determined Va	pour density : not	applicable		

10. STABILITY AND REACTIVITY

: not applicable

: insoluble

Stability

Boiling Point:

Water solubility

: The product is stable if stored and handled as prescribed.

pН

not applicable

:

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 030RD2045 NEW RED HMF

Version Number 1.1 Revision Date 03/29/2014 Page 4 of 6 Print Date 4/7/2014

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7023-61-2	C.I. Pigment red 48,	Irritant	Eyes, Skin, Respiratory
	calcium salt		system.
		Toxic	digestive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available

PolyOne.

MATERIAL SAFETY DATA SHEET 030RD2045 NEW RED HMF

rsion Number 1.1 vision Date 03/29/2014	Page 5 o Print Date <i>4</i> /7/20
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 E	stremely Hazardous Substance
Unless specific chemicals are	dentified under this section, this product is Not Applicable under this regulati
SARA Title III Section 313 To	oxic Chemicals:
	dentified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are	

PolyOne

MATERIAL SAFETY DATA SHEET 030RD2045 NEW RED HMF

Version Number 1.1 Revision Date 03/29/2014 Page 6 of 6 Print Date 4/7/2014

Chemical Name			CAS-No.	Weight	NPRI ID#
				percent	
Zinc stearate			557-05-1	0.10 - 1.00	
WHMIS Classification	:	Not controlled.			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
ational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.