MATERIAL SAFETY DATA SHEET CEPLA XXXXX

Version Number 1.1 Revision Date 03/29/2014 Page 1 of 7 Print Date 4/7/2014

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012					
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	CEPLA XXXXX			
Product code	:	CC10149382			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

Components CAS No Weight persent

Styrene 100-42-5 0.1 - 1	Components	CAS-No.	Weight percent
	Styrene	100-42-5	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET CEPLA XXXXX

Version Number 1.1 Revision Date 03/29/2014 Page 2 of 7 Print Date 4/7/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET CEPLA XXXXX

Version Number 1.1 Revision Date 03/29/2014

Page 3 of 7 Print Date 4/7/2014

Storage	Keep containers dry and tightly closed to avo and contamination. Keep in a dry, cool place	1
8. EXI	RE CONTROLS/PERSONAL PROTECTION	ON
Respiratory protection	No personal respiratory protective equipment	normally required.
Eye/Face Protection	Safety glasses with side-shields	
Hand protection	Protective gloves	
Skin and body protection	Long sleeved clothing	
Additional Protective Measures	Safety shoes	
General Hygiene Considerations	Handle in accordance with good industrial hy practice. Wash hands before breaks and at the	e :
Engineering measures	Heat only in areas with appropriate exhaust vappropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Styrene	20 ppm	Time Weighted Average (TWA):		ACGIH
	40 ppm	Short Term Exposure Limit (STEL):		ACGIH
	50 ppm 215 mg/m3	Recommended exposure limit (REL):		NIOSH
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		NIOSH
	100 ppm	Time Weighted Average (TWA):		OSHA Z2
	200 ppm	Ceiling Limit Value:		OSHA Z2
	600 ppm	Maximum concentration:		OSHA Z2
	50 ppm 215 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	50 ppm 215 mg/m3	Time Weighted Average (TWA):		MX OEL
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Evapouration rate

: Not applicable

MATERIAL SAFETY DATA SHEET CEPLA XXXXX

: pellets

: very faint

: NO PIGMENT

Version Number 1.1 Revision Date 03/29/2014

Appearance

Colour

Odour

Melting point/range Boiling Point: Water solubility	:	Not determined not applicable insoluble	Vapour density pH		not applicable not applicable
		10. STABILITY AND RI	EACTIVITY		
Stability		: The product is stable if	stored and handled as	presc	cribed.
Hazardous Polymerization		: Will not occur.			
Conditions to avoid		: Keep away from oxidiz decomposition, do not o		ame.	To avoid thermal
Incompatible Materials		: Incompatible with stron	g acids and oxidizing	agen	ts.
Hazardous decomposition products		: Carbon dioxide (CO2), (NOx), other hazardous			

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
100-42-5	Styrene	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory
			system, Liver, central nervous
			system (CNS).

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
100-42-5	Styrene	LC50	12 gm/m3	rat
		Oral LD50	2,650 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
100-42-5	Styrene	no	2B	no

IARC Carcinogen Classifications:



:

:

Specific Gravity

Vapour pressure

Bulk density

Page 4 of 7 Print Date 4/7/2014

Not determined

Not established

: not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET CEPLA XXXXX

Version Number 1.1 Revision Date 03/29/2014 Page 5 of 7 Print Date 4/7/2014

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Styrene 100-42-5 Irritating to eyes, skin, and respiratory tract with many CNS effects such as narcosis, cramps and respiratory tract paralysis.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.

5/7

MATERIAL SAFETY DATA SHEET CEPLA XXXXX

Version Number 1.1 Revision Date 03/29/2014 Page 6 of 7 Print Date 4/7/2014

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Chemical Name CAS-No. Weight percent

Chemiear Name	C/10 110.	weight percent	
STYRENESTYRENE	100-42-5	0.10 - 1.00	

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Styrene	100-42-5	0.10 - 1.00	

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
100-42-5

:

DSL

DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS

: Not determined



MATERIAL SAFETY DATA SHEET **CEPLA XXXXX**

Version Number 1.1 Revision Date 03/29/2014 Page 7 of 7 Print Date 4/7/2014

China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.