PolyOne

## MATERIAL SAFETY DATA SHEET ANTIQUE BROWN PVC

Version Number 1.1 Revision Date 03/13/2014

Page 1 of 8 Print Date 3/28/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

## POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number		1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	ANTIQUE BROWN PVC			
Product code	:	CC10149434			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium stearate	1592-23-0	1 - 5
Carbon black	1333-86-4	1 - 5
Rutile, antimony chromium buff	68186-90-3	1 - 5
Manganese antimony titanium brown rutile	68412-38-4	30 - 60
(C.I. Pigment Yellow 164)		

### **3. HAZARDS IDENTIFICATION**

## **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

## POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.

PolyOne.

# MATERIAL SAFETY DATA SHEET ANTIQUE BROWN PVC

Version Number 1.1 Revision Date 03/13/2014 Page 2 of 8 Print Date 3/28/2014

	: Experience shows no unusual dermatitis hazard from routine handling				
Chronic exposure	: Refer to Section 11 for Toxicological Information.				
Medical Conditions       : None known.         Aggravated by Exposure:					
	4. FIRST AID MEASURES				
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.				
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
	5. FIREFIGHTING MEASURES				
Flash point	: not applicable				
F	. not applicable				
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>				
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne</li> </ul>				
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive</li> </ul>				
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen</li> </ul>				
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>				
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> <li>6. ACCIDENTAL RELEASE MEASURES</li> <li>Wear appropriate personal protection during cleanup, such as</li> </ul>				

PolyOne.

# MATERIAL SAFETY DATA SHEET ANTIQUE BROWN PVC

Version Number 1.1 Revision Date 03/13/2014 Page 3 of 8 Print Date 3/28/2014

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET ANTIQUE BROWN PVC

Version Number 1.1 Revision Date 03/13/2014 Page 4 of 8 Print Date 3/28/2014

Components	Value	Exposure time	Exposure type	List:
Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	1 mg/m3	Recommended exposure limit (REL):	Fume. as Mn	NIOSH
	3 mg/m3	Short Term Exposure Limit (STEL):	Fume. as Mn	NIOSH
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: solid

Evapouration rate

: Not applicable

## **MATERIAL SAFETY DATA SHEET** ANTIQUE BROWN PVC

Version Number 1.1 Revision Date 03/13/2014

Melting point/range

Boiling Point:

Water solubility

Appearance

Colour

Odour

Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

**10. STABILITY AND REACTIVITY** 

## **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
68412-38-4	Manganese antimony	Irritant	Eyes, Skin.
	titanium brown rutile (C.I.		
	Pigment Yellow 164)		


### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

#### **Additional Health Hazard Information:**

Page 5 of 8 Print Date 3/28/2014



Specific Gravity Not determined : :

Bulk density

pН

Vapour pressure

Vapour density

Not established : not applicable : not applicable

: not applicable

PolvOne

## MATERIAL SAFETY DATA SHEET ANTIQUE BROWN PVC

Version Number 1.1 Revision Date 03/13/2014 Page 6 of 8 Print Date 3/28/2014

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
	-

PolyOne.

# MATERIAL SAFETY DATA SHEET ANTIQUE BROWN PVC

Version Number 1.1 Revision Date 03/13/2014 Page 7 of 8 Print Date 3/28/2014

TSCA Status : All components TSCA Inventor		product are	e listed or	n or exen	npt from th	e
US. EPA CERCLA Hazardous Substances (40 CFR	302)					
not applicable						
not applicable						
California Proposition : WARNING! T 65 California to car			s a chemi	ical knov	vn to the S	tate of
SARA Title III Section 302 Extremely Hazardous Su	Ibstance					
Unless specific chemicals are identified under this se	ction. thi	s product i	is Not Ar	plicable	under this	regulatio
	, .	r	I	1		0
SARA Title III Section 313 Toxic Chemicals:						
SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this se	ction, thi	s product i	is Not Ap	plicable	under this	regulatio
	ction, thi	s product i		Weight	percent	regulatio
Unless specific chemicals are identified under this se	ction, thi		).		percent	regulatio
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS		CAS-No 68412-38	). 3-4	Weight 30.00 -	ercent 60.00	regulatio
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III		CAS-No	). 3-4	Weight	ercent 60.00	regulatio
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY		CAS-No 68412-38	). 3-4	Weight 30.00 -	ercent 60.00	regulatio
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III		CAS-No 68412-38	). 3-4	Weight 30.00 -	ercent 60.00	regulatio
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS		CAS-No 68412-38	). 3-4	Weight 30.00 -	ercent 60.00	regulatio
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY		CAS-No 68412-38	). 3-4	Weight 30.00 -	ercent 60.00	regulatio
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI)		CAS-No 68412-38 68186-90	). 3-4 )-3	Weight 30.00 -	percent 60.00 5.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations:		CAS-No 68412-38 68186-90	). 3-4	Weight 30.00 -	ercent 60.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name	CAS-N	CAS-No 68412-38 68186-90	). 3-4 )-3 Weigh percen	Weight 30.00 - 1.00 - : t t	percent 60.00 5.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Manganese antimony titanium brown rutile (C.I.		CAS-No 68412-38 68186-90	). 3-4 )-3 Weigh percen	Weight 30.00 - 1.00 - :	percent 60.00 5.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name	CAS-N	CAS-No 68412-38 68186-90	0. 3-4 )-3 Weigh percen 30.00	Weight 30.00 - 1.00 - : t t t - 60.00	percent 60.00 5.00	
Unless specific chemicals are identified under this se Chemical Name MANGANESE COMPOUNDSMANGANESE COMPOUNDSANTIMONY COMPOUNDS CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name Manganese antimony titanium brown rutile (C.I.	CAS-N	CAS-No 68412-38 68186-90 Jo. 38-4	0. 3-4 )-3 Weigh percen 30.00	Weight 30.00 - 1.00 - : t t - 60.00	percent 60.00 5.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
68412-38-4	
1333-86-4	

PolyOne

## MATERIAL SAFETY DATA SHEET ANTIQUE BROWN PVC

Version Number 1.1 Revision Date 03/13/2014 Page 8 of 8 Print Date 3/28/2014

68186-90-3 DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed
16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.