MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1 Revision Date 03/29/2014

CAS-No.

Product Use

Page 1 of 9 Print Date 4/7/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	CHESTNUT RAILING
Product code	:	CC10149505
Chemical Name	:	Mixture

2. COMPOSITION/INFORMATION ON INGREDIENTS

: Industrial Applications

Mixture

:

Components	CAS-No.	Weight percent
1,3,5-Triazine-2,4,6-triamine,N,N'"-1,2-	106990-43-6	1 - 5
ethanediylbis[N-[3-[[4,6-bis[butyl(1,2,2,6,6-		
pentamethyl-4-piperidinyl)amino]-1,3,5-		
triazin		
Phenol, 2-(2H-benzotriazol-2-yl)-4,6-	25973-55-1	1 - 5
bis(1,1-dimethylpropyl)-		
Carbon black	1333-86-4	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Barium sulfate	7727-43-7	5 - 10
Silica, amorphous, precipitated and gel	112926-00-8	5 - 10
Titanium dioxide	13463-67-7	5 - 10
Iron oxide	1309-37-1	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Ingestion, Skin contact

PolyOne.

MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1 Revision Date 03/29/2014 Page 2 of 9 Print Date 4/7/2014

Inhalation	: Resin particles, like other inert materials, can be mechanically		
	irritating.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to		
<u></u>	eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions	: None known.		
Aggravated by Exposure:			
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIREFIGHTING MEASURES		
Flash point	: not applicable		
Flammable Limits			
Upper explosion limit	: not applicable		
Lower explosion limit	: not applicable		
Auto-ignition temperature	: not applicable		
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.		
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive		
Procedures	pressure mode should be worn to prevent inhalation of airborne		
	contaminants.		
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.		

PolyOne.

MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1 Revision Date 03/29/2014		Page 3 of 9 Print Date <i>4/7/2014</i>
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne.

MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1 Revision Date 03/29/2014 Page 4 of 9 Print Date 4/7/2014

Components	Value	Exposure time	Exposure type	List:
Barium sulfate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

PolvOne

MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1 Revision Date 03/29/2014

Page 5 of 9 Print Date 4/7/2014

Xylenes (o-, m-, p- isomers)	100 ppm	Time Weighted Average (TWA):	ACGIH
	150 ppm	Short Term Exposure Limit (STEL):	ACGIH
	100 ppm 435 mg/m3	PEL:	OSHA Z1
	100 ppm 435 mg/m3	Time Weighted Average (TWA):	OSHA Z1A
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):	OSHA Z1A
	100 ppm 435 mg/m3	Time Weighted Average (TWA):	MX OEL
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 pellets
 BROWN
 very faint
 Not determined
 not applicable
 insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable
- : not app

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No. Chemical Name Effect Target Organ

PolyOne

MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1 Revision Date 03/29/2014 Page 6 of 9 Print Date 4/7/2014

25973-55-1	Phenol, 2-(2H- benzotriazol-2-yl)-4,6- bis(1,1-dimethylpropyl)-	Systemic effects	Kidney, Liver, reproductive system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1330-20-7	Xylenes (o-, m-, p- isomers)	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, blood and blood forming system, Liver, Kidney, central nervous system (CNS), digestive system.
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit
1330-20-7	Xylenes (o-, m-, p-	LC50	5000 ppm/4H	rat
	isomers)	LC50		rat
		Oral	4,300	ratrat
		LD50Oral	mg/kg4,300	rabbit
		LD50	mg/kg	rabbit
		Dermal LD50	> 1,700 mg/kg	
		Dermal LD50	43 g/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

PolvOne

MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1 Revision Date 03/29/2014 Page 7 of 9 Print Date 4/7/2014

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.		
Environmental Toxicity	Chemicals are not readily available as they are bound within the polymer matrix.		
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.		
Additional advice	: no data available		
	13. DISPOSAL CONSIDERATIONS		
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Not regulated for transportation.		
ICAO/IATA	: Refer to specific regulation.		
IMO/IMDG (maritime)	: Refer to specific regulation.		
	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	: Classified as hazardous based on components.		

PolyOne.

MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1 Revision Date 03/29/2014 Page 8 of 9 Print Date 4/7/2014

TSCA Status

All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

Chemical Name	CAS-No.	RQ for component	RQ for
			Mixture/Product
Xylenes (o-, m-, p- isomers)	1330-20-7	100 lbs	2,714 LB

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name		CAS-No.	Weight percent	
	ZINC COMPOUNDS	68187-51-9	10.00 - 30.00	
	XYLENE (MIXED ISOMERS)	1330-20-7	1.00 - 5.00	

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Zinc ferrite brown spinel (C.I. Pigment Yellow 119)	68187-51-9	10.00 - 30.00	
Xylenes (o-, m-, p- isomers)	1330-20-7	1.00 - 5.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1333-86-4	
1309-37-1	

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET CHESTNUT RAILING

Version Number 1.1	Page 9 of 9
Revision Date 03/29/2014	Print Date 4/7/2014
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.