PolvOne.

MATERIAL SAFETY DATA SHEET 030RD2051 RED PVC W/UV

Version Number 1.1 Revision Date 03/29/2014 Page 1 of 7 Print Date 4/7/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone number | : | 1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--|---|--|
| Product name | : | 030RD2051 RED PVC W/UV |
| Product code | : | CC10149635 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Weight percent |
|----------------------------------|-----------|----------------|
| 2-Hydroxy-4-n-octoxybenzophenone | 1843-05-6 | 5 - 10 |
| Iron oxide | 1309-37-1 | 1 - 5 |
| Calcium carbonate | 1317-65-3 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|---------------------|--|
| Acute exposure | |
| Inhalation | : Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Particulates, like other inert materials can be mechanically irritating. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |

PolyOne.

MATERIAL SAFETY DATA SHEET 030RD2051 RED PVC W/UV

Version Number 1.1 Revision Date 03/29/2014 Page 2 of 7 Print Date 4/7/2014

| Gedical Conditions : None known. ggravated by Exposure: | | |
|---|--|--|
| | 4. FIRST AID MEASURES | |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice. | |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. | |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. | |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. | |
| | 5. FIREFIGHTING MEASURES | |
| Flash point | : not applicable | |
| Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. | |
| | 6. ACCIDENTAL RELEASE MEASURES | |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. | |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. | |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. | |

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 030RD2051 RED PVC W/UV

Version Number 1.1 Revision Date 03/29/2014 Page 3 of 7 Print Date 4/7/2014

| | | 7. HANDLING AND STORAGE | |
|-----------------------------------|------|--|--|
| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. | |
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. | |
| 8. EXI | POSU | RE CONTROLS/PERSONAL PROTECTION | |
| Respiratory protection | : | No personal respiratory protective equipment normally required. | |
| Eye/Face Protection | : | Safety glasses with side-shields | |
| Hand protection | : | Protective gloves | |
| Skin and body protection | : | Long sleeved clothing | |
| Additional Protective Measures | : | Safety shoes | |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. | |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. | |

Exposure limit(s)

| Components | Value | Exposure time | Exposure type | List: |
|-------------------|----------|---------------------------|----------------------|---------|
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average | | MX OEL |
| | | (TWA): | | |
| | 20 mg/m3 | Short Term Exposure Limit | | MX OEL |
| | | (STEL): | | |
| Iron oxide | 10 mg/m3 | PEL: | Fume. | OSHA Z1 |
| | 5 mg/m3 | Time Weighted Average | as Fe | MX OEL |
| | | (TWA): | | |
| | 10 mg/m3 | Short Term Exposure Limit | as Fe | MX OEL |
| | | (STEL): | | |
| | 5 mg/m3 | Time Weighted Average | Respirable fraction. | ACGIH |
| | | (TWA): | | |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : solid : pellets Evapouration rate Specific Gravity Not applicableNot determined

PolyOne.

MATERIAL SAFETY DATA SHEET 030RD2051 RED PVC W/UV

Version Number 1.1 Revision Date 03/29/2014

Page 4 of 7 Print Date 4/7/2014

| Colour Odour Melting point/range Boiling Point: Water solubility | RED very faint Not determined not applicable insoluble | Bulk density Vapour pressure Vapour density pH | Not established not applicable not applicable not applicable |
|--|--|---|---|
| | 10. STABILITY AND | REACTIVITY | |
| Stability | : The product is stable | e if stored and handled as | s prescribed. |
| Hazardous Polymerization | : Will not occur. | | |
| Conditions to avoid | : Keep away from oxi decomposition, do n | dizing agents and open f ot overheat. | lame. To avoid thermal |
| Incompatible Materials | or acetal copolymers processing. At proc destructive and invo mechanically clean p quantities of these m | strong oxidizers. Also, a s and with amine contain essing conditions, these r lve rapid degradation. T processing equipment to laterials from coming in a nination of feedstocks. | ing materials during materials are mutually 'horoughly purge and avoid even trace |
| Hazardous decomposition products | (NOx), hydrogen ch smoke are all possib or more) above 392 | °F (200 °C) or short term oduct decomposition and | dous materials, and pproximately 30 minutes heating at 482 °F (250 |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|-----------|--------------------|------------------|-------------------------|
| 1843-05-6 | 2-Hydroxy-4-n- | sensitizer | Skin. |
| | octoxybenzophenone | | |
| 1309-37-1 | Iron oxide | Systemic effects | Respiratory system. |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory |
| | | | system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| | CAS-No. | Chemical Name | Route | Value | Species |
|--|---------|---------------|-------|-------|---------|
|--|---------|---------------|-------|-------|---------|

PolyOne.

MATERIAL SAFETY DATA SHEET 030RD2051 RED PVC W/UV

Version Number 1.1 Revision Date 03/29/2014

Page 5 of 7 Print Date 4/7/2014

| octoxy | benzophenone Dermal LD50 > 10 gm/kg rabbit | | | |
|--|---|--|--|--|
| | 12. ECOLOGICAL INFORMATION | | | |
| Persistence and degradability | : Not readily biodegradable. | | | |
| Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix. | | | | |
| Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix. | | | | |
| Additional advice | : no data available | | | |
| | 13. DISPOSAL CONSIDERATIONS | | | |
| Product | : Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | | |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | | |
| | 14. TRANSPORT INFORMATION | | | |
| U.S. DOT Classification | : Not regulated for transportation. | | | |
| ICAO/IATA | : Refer to specific regulation. | | | |
| IMO/IMDG (maritime) | : Refer to specific regulation. | | | |
| | 15. REGULATORY INFORMATION | | | |
| US Regulations: | | | | |
| OSHA Status | : Classified as hazardous based on components. | | | |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. | | | |
| US. EPA CERCLA Hazardous | Substances (40 CFR 302) | | | |
| not applicable | | | | |
| | | | | |

olvOn<u>e</u>

MATERIAL SAFETY DATA SHEET 030RD2051 RED PVC W/UV

Version Number 1.1 Revision Date 03/29/2014 Page 6 of 7 Print Date 4/7/2014

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight | NPRI ID# |
|---------------|----------|-------------|----------|
| | | percent | |
| Zinc stearate | 557-05-1 | 0.10 - 1.00 | |

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

| CAS-No. |
|-----------|
| 1309-37-1 |
| |

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS | : | Listed |
|-------------------|---|----------------|
| China IECS | : | Listed |
| Europe EINECS | : | Listed |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Listed |
| Philippines PICCS | : | Listed |

16. OTHER INFORMATION

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 030RD2051 RED PVC W/UV

Version Number 1.1 Revision Date 03/29/2014 Page 7 of 7 Print Date 4/7/2014

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.