

MATERIAL SAFETY DATA SHEET

CRYSTALBLUE 966496/UV/MG47FABS

Version Number 1.2 Page 1 of 8
Revision Date 02/06/2012 Print Date 2/6/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

or accident).

Product name : CRYSTALBLUE 966496/UV/MG47FABS

Product code : CC10152337 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Formamide, N,N'-1,6-hexanediylbis[N-	124172-53-8	1 - 5
(2,2,6,6-tetramethyl-4-piperidinyl)-		
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-	52829-07-9	1 - 5
piperidinyl) ester		
Nickel antimony yellow rutile (C.I. Pigment	8007-18-9	1 - 5
Yellow 53)		
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically

irritating.



MATERIAL SAFETY DATA SHEET

CRYSTALBLUE 966496/UV/MG47FABS

 Version Number 1.2
 Page 2 of 8

 Revision Date 02/06/2012
 Print Date 2/6/2012

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to

eyes.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : not applicable

Flammable Limits

Upper explosion limit : not applicable Lower explosion limit : not applicable Autoignition temperature : not applicable

Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.



MATERIAL SAFETY DATA SHEET

CRYSTALBLUE 966496/UV/MG47FABS

Version Number 1.2 Page 3 of 8
Revision Date 02/06/2012 Print Date 2/6/2012

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section

13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective

Measures

: Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



MATERIAL SAFETY DATA SHEET

CRYSTALBLUE 966496/UV/MG47FABS

Version Number 1.2 Page 4 of 8
Revision Date 02/06/2012 Print Date 2/6/2012

Components	Value	Exposure time	Exposure type	List:
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	0.015 mg/m3	Recommended exposure limit (REL):	as Ni	NIOSH
	1 mg/m3	PEL:	as Ni	OSHA Z1
	1 mg/m3	Time Weighted Average (TWA):	as Ni	OSHA Z1A
	0.2 mg/m3	Time Weighted Average (TWA):	Inhalable fraction. as Ni	ACGIH
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Not applicable : solid Evaporation rate Form Not determined Appearance pellets Specific Gravity Bulk density Colour : BLUE : Not established Odour : very faint Vapour pressure : not applicable Melting point/range : Not determined Vapour density : not applicable Boiling Point: : not applicable : not applicable pН

Water solubility : insoluble

10. STABILITY AND REACTIVITY

Stability : Stable



MATERIAL SAFETY DATA SHEET

CRYSTALBLUE 966496/UV/MG47FABS

Version Number 1.2 Page 5 of 8 Revision Date 02/06/2012 Print Date 2/6/2012

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
124172-53-8	Formamide, N,N'-1,6-	Irritant	Eyes.
	hexanediylbis[N-(2,2,6,6-		
	tetramethyl-4-piperidinyl)-		
52829-07-9	Decanedioic acid,	Irritant	Eyes.
	bis(2,2,6,6-tetramethyl-4-		
	piperidinyl) ester		
8007-18-9	Nickel antimony yellow	Irritant	Eyes, Skin.
	rutile (C.I. Pigment		
	Yellow 53)		
		sensitizer	Skin.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
124172-53-8	Formamide, N,N'-1,6-	LC50	> 5.0 mg/l	rat
	hexanediylbis[N-(2,2,6,6-	Oral LD50	> 2,000 mg/kg	rat
	tetramethyl-4-piperidinyl)-			
52829-07-9	Decanedioic acid,	Oral LD50	3,700 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-	Dermal LD50	> 3,100 mg/kg	rabbit
	piperidinyl) ester			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No. Chemical Name OSHA IARC NTP



MATERIAL SAFETY DATA SHEET

CRYSTALBLUE 966496/UV/MG47FABS

Version Number 1.2 Page 6 of 8 Revision Date 02/06/2012 Print Date 2/6/2012

8007-18-9	Nickel antimony yellow rutile	no	1	no
	(C.I. Pigment Yellow 53)			
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Nickel antimony yellow rutile (C.I. Pigment Yellow 53) 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney and muscle effects.

12	ECOL	OCICAI	INFORMATION
L Z.	P. C. C. C. L.	ANTIC AL	HNRUKIVIA HUJIN

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the

polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the

polymer matrix.

Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastic plastics the product can be recycled. Where

possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Refer to specific regulation.

IMO/IMDG (maritime) : Refer to specific regulation.



MATERIAL SAFETY DATA SHEET

CRYSTALBLUE 966496/UV/MG47FABS

 Version Number 1.2
 Page 7 of 8

 Revision Date 02/06/2012
 Print Date 2/6/2012

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : WARNING! This product contains a chemical known to the State of

65 California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
NICKEL COMPOUNDSNICKEL	8007-18-9	1.00 - 5.00
COMPOUNDS ANTIMONY COMPOUNDS		
CHROMIUM III COMPOUNDSCHROMIUM III	68186-90-3	0.10 - 1.00
COMPOUNDSANTIMONY		
COMPOUNDSCHROMIUM COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Nickel antimony yellow rutile (C.I. Pigment	8007-18-9	1.00 - 5.00	
Yellow 53)			
		1.00 - 5.00	
Phthalocyanine blue	147-14-8	1.00 - 5.00	
Rutile, antimony chromium buff	68186-90-3	0.10 - 1.00	



MATERIAL SAFETY DATA SHEET

CRYSTALBLUE 966496/UV/MG47FABS

Version Number 1.2 Page 8 of 8 Revision Date 02/06/2012 Print Date 2/6/2012

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
8007-18-9	
147-14-8	
7631-86-9	

DSL : All of the components of this product are listed on the Canadian

Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL).

Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.