MATERIAL SAFETY DATA SHEET FOLIAGE GREEN 34160 NY

Version Number 1.2 Revision Date 03/29/2014 Page 1 of 7 Print Date 4/7/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone number | : | 1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--|---|--|
| Product name | : | FOLIAGE GREEN 34160 NY |
| Product code | : | CC10154106 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Weight percent |
|----------------------|-----------|----------------|
| Carbon black | 1333-86-4 | 1 - 5 |
| Chromium (III) oxide | 1308-38-9 | 5 - 10 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|----------------------------|---|
| Acute exposure | |
| Inhalation | : Resin particles, like other inert materials, can be mechanically irritating. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Resin particles, like other inert materials, are mechanically irritating to eyes. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |

PolyOne.

MATERIAL SAFETY DATA SHEET FOLIAGE GREEN 34160 NY

Version Number 1.2 Revision Date 03/29/2014 Page 2 of 7 Print Date 4/7/2014

| Aggravated by Exposure: | |
|---|--|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. |
| | 5. FIREFIGHTING MEASURES |
| Flash point | : not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media | not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. |
| Special Fire Fighting Procedures Unusual Fire/Explosion | Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen |
| Hazards | (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. |
| | 7. HANDLING AND STORAGE |
| Handling | : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |

PolyOne

MATERIAL SAFETY DATA SHEET FOLIAGE GREEN 34160 NY

Version Number 1.2 Revision Date 03/29/2014 Page 3 of 7 Print Date 4/7/2014

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| Respiratory protection | : No personal respiratory protective equipment normally require | ed. |
|-----------------------------------|---|----------|
| Eye/Face Protection | : Safety glasses with side-shields | |
| Hand protection | : Protective gloves | |
| Skin and body protection | : Long sleeved clothing | |
| Additional Protective Measures | : Safety shoes | |
| General Hygiene Considerations | : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday | <i>.</i> |
| Engineering measures | : Heat only in areas with appropriate exhaust ventilation. Provid appropriate exhaust ventilation at machinery. | de |

Exposure limit(s)

| Components | Value | Exposure time | Exposure type | List: |
|----------------------|-----------|-----------------------------------|---------------------|----------|
| Carbon black | 3.5 mg/m3 | Recommended exposure limit (REL): | | NIOSH |
| | 0.1 mg/m3 | Recommended exposure limit (REL): | | NIOSH |
| | 3.5 mg/m3 | PEL: | | OSHA Z1 |
| | 3.5 mg/m3 | Time Weighted Average (TWA): | | OSHA Z1A |
| | 3.5 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 7 mg/m3 | Short Term Exposure Limit (STEL): | | MX OEL |
| | 3 mg/m3 | Time Weighted Average (TWA): | Inhalable fraction. | ACGIH |
| Chromium (III) oxide | 0.5 mg/m3 | Recommended exposure limit (REL): | as Cr | NIOSH |
| | 0.5 mg/m3 | PEL: | as Cr | OSHA Z1 |

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour
- : solid: pellets: GREEN: very faint

Evapouration rate Specific Gravity Bulk density Vapour pressure Not applicableNot determinedNot establishednot applicable

MATERIAL SAFETY DATA SHEET FOLIAGE GREEN 34160 NY

Ve Re

| sion Number 1.2 ision Date 03/29/2014 | | | Page 4 of 7 Print Date <i>4/7/2014</i> | |
|---|---|------------------------------|---|--|
| Melting point/range Boiling Point: Water solubility | Not determinednot applicableinsoluble | Vapour density pH | : not applicable : not applicable | |
| | 10. STABILITY A | ND REACTIVITY | | |
| Stability | : The product is st | able if stored and handled a | s prescribed. | |
| Hazardous Polymerization | : Will not occur. | | | |
| Conditions to avoid | : Keep away from | oxidizing agents and open | flame. To avoid thermal | |

| | • | decomposition, do not overheat. |
|----------------------------------|---|--|
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents. |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|-----------|----------------------|------------------|---------------------------|
| 1333-86-4 | Carbon black | Systemic effects | Eyes, Respiratory system. |
| 1308-38-9 | Chromium (III) oxide | Irritant | Eyes, Skin. |
| | | sensitizer | Skin. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|---------------|-------------|---------------|---------|
| 1333-86-4 | Carbon black | Oral LD50 | >15,400 mg/kg | rat |
| | | Dermal LD50 | > 3 gm/kg | rabbit |

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

PolyOne

MATERIAL SAFETY DATA SHEET FOLIAGE GREEN 34160 NY

Version Number 1.2 Revision Date 03/29/2014 Page 5 of 7 Print Date 4/7/2014

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

| | 12. ECOLOGICAL INFORMATION | | | |
|--|---|--|--|--|
| Persistence and degradability : Not readily biodegradable. | | | | |
| Environmental Toxicity | : Chemicals are not readily available as they are bound within the polymer matrix. | | | |
| Bioaccumulation Potential | : Chemicals are not readily available as they are bound within the polymer matrix. | | | |
| Additional advice | : no data available | | | |
| | 13. DISPOSAL CONSIDERATIONS | | | |
| Product | : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | | |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. | | | |
| | 14. TRANSPORT INFORMATION | | | |
| U.S. DOT Classification | : Not regulated for transportation. | | | |
| ICAO/IATA | : Refer to specific regulation. | | | |
| IMO/IMDG (maritime) | : Refer to specific regulation. | | | |
| | 15. REGULATORY INFORMATION | | | |
| US Regulations: | | | | |
| OSHA Status | : Classified as hazardous based on components. | | | |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. | | | |
| US. EPA CERCLA Hazardous | Substances (40 CFR 302) | | | |
| | | | | |
| | 5/7 | | | |

PolyOne

MATERIAL SAFETY DATA SHEET FOLIAGE GREEN 34160 NY

Version Number 1.2 Revision Date 03/29/2014 Page 6 of 7 Print Date 4/7/2014

| Chemical Name | CAS-No. | RQ for component | RQ for Mixture/Product |
|-------------------------|-----------|------------------|---------------------------|
| Chromium (III) oxide | 1308-38-9 | 010 lbs | 107 LB |

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name | CAS-No. | Weight percent |
|------------------------------------|------------|----------------|
| CHROMIUM III COMPOUNDSCHROMIUM | 1308-38-9 | 5.00 - 10.00 |
| COMPOUNDS | | |
| CHROMIUM III COMPOUNDSCHROMIUM III | 68186-90-3 | 0.10 - 1.00 |
| COMPOUNDSANTIMONY | | |
| COMPOUNDSCHROMIUM COMPOUNDS | | |
| ZINC COMPOUNDS | 1314-98-3 | 10.00 - 30.00 |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight | NPRI ID# |
|--------------------------------|------------|---------------|----------|
| | | percent | |
| Chromium (III) oxide | 1308-38-9 | 5.00 - 10.00 | |
| Rutile, antimony chromium buff | 68186-90-3 | 0.10 - 1.00 | |
| Zinc sulfide | 1314-98-3 | 10.00 - 30.00 | |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. | |
|-----------|--|
| 1333-86-4 | |
| 1308-38-9 | |

:

DSL

All components of this product are on the Canadian Domestic

PolvOn<u>e</u>

MATERIAL SAFETY DATA SHEET FOLIAGE GREEN 34160 NY

Version Number 1.2 Revision Date 03/29/2014 Page 7 of 7 Print Date 4/7/2014

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS:ListedChina IECS:ListedEurope EINECS:ListedJapan ENCS:ListedKorea KECI:ListedPhilippines PICCS:Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.