PolyOne

MATERIAL SAFETY DATA SHEET UVPPE 154347

Version Number 1.1 Revision Date 03/13/2014

Product Use

Page 1 of 6 Print Date 3/29/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UVPPE 154347
Product code	:	CC10154347
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Miscellaneous Amine Compounds	0-33-9	5 - 10
Miscellaneous Irritant	0-32-8	10 - 30
Silica, amorphous	7631-86-9	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET UVPPE 154347

Version Number 1.1 Revision Date 03/13/2014 Page 2 of 6 Print Date 3/29/2014

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Auto-ignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET UVPPE 154347

			Print I	Date 3/29/	
Handling		ake measures to prevent the b nly in areas with appropriate e		arge. Heat	
Storage		eep containers dry and tightly nd contamination. Keep in a c		absorption	
8.]	EXPOSURE	CONTROLS/PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protect	ive equipment normally r	equired.	
Eye/Face Protection	: S	afety glasses with side-shields	;		
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clothing			
Additional Protective Measures	: Sa	: Safety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
				Provide	
Exposure limit(s)	aŗ	opropriate exhaust ventilation	at machinery.		
Exposure limit(s) Components Silica, amorphous	ar Value 6 mg/m3	Exposure time Recommended exposure limit (REL):	at machinery.	List:	
Components	Value	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA):		List:	
Components	Value 6 mg/m3	Exposure time Recommended exposure limit (REL): Time Weighted Average		List: NIOSH Z3	
Components	Value 6 mg/m3 0.8 mg/m3	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average	Exposure type	List: NIOSH Z3 MX OEI	
Components	Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	Exposure type Inhalable particulate. Respirable dust.	List: NIOSH Z3 MX OEI	
Components Silica, amorphous	Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type Inhalable particulate. Respirable dust. DPERTIES	List: NIOSH Z3 MX OEI MX OEI	
Components Silica, amorphous Form	Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : solid	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Exposure type Inhalable particulate. Respirable dust. DPERTIES uration rate : Not	List: NIOSH Z3 MX OEI MX OEI	
Components Silica, amorphous Form Appearance	Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : solid : pellet	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO Evapo ts Specifi	Exposure type Inhalable particulate. Respirable dust. DPERTIES uration rate : Not ic Gravity : Not	List: NIOSH Z3 MX OEI MX OEI applicable determined	
Components Silica, amorphous Form Appearance Colour	Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : solid : peller : NO F	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO Evapo ts Specif PIGMENT Bulk of	Exposure type Inhalable particulate. Respirable dust. DPERTIES uration rate : Not ic Gravity : Not lensity : Not	List: NIOSH Z3 MX OEI MX OEI applicable determined established	
Components Silica, amorphous Form Appearance Colour Odour	Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : solid : peller : NO F : very	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO Evapo ts Specif PIGMENT Bulk of faint Vapor	Exposure type Inhalable particulate. Respirable dust. DPERTIES ouration rate : Not ic Gravity : Not lensity : Not ir pressure : not a	List: NIOSH Z3 MX OEI MX OEI applicable determined established applicable	
Components Silica, amorphous Form Appearance Colour	Value 6 mg/m3 0.8 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : solid : pelle : NO F : very : Not c	Exposure time Recommended exposure limit (REL): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO Evapo ts Specif PIGMENT Bulk of faint Vapor	Exposure type Inhalable particulate. Respirable dust. DPERTIES uration rate : Not ic Gravity : Not lensity : Not ur pressure : not a ur density : not a	List: NIOSH Z3 MX OEI MX OEI applicable determined established	



MATERIAL SAFETY DATA SHEET UVPPE 154347

Version Number 1.1 Revision Date 03/13/2014 Page 4 of 6 Print Date 3/29/2014

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
0-33-9	Miscellaneous Amine	Corrosive	Eyes, Skin, Respiratory
	Compounds		system.
		sensitizer	Skin.
0-32-8	Miscellaneous Irritant	sensitizer	Skin.
		Irritant	Eyes, Skin.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
0-33-9	Miscellaneous Amine	LC50		rat
	Compounds	Oral LD50	1,430 mg/kg	rat
		Dermal LD50	913 mg/kg	rabbit

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS



MATERIAL SAFETY DATA SHEET UVPPE 154347

sion Number 1.1 ision Date 03/13/2014	Page 5 Print Date 3/29/2
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Propositio 65	n : Not applicable
SARA Title III Section 302 I	Extremely Hazardous Substance
	e identified under this section, this product is Not Applicable under this regula
SARA Title III Section 313	Foxic Chemicals:
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regula

PolyOne

MATERIAL SAFETY DATA SHEET UVPPE 154347

Version Number 1.1 Revision Date 03/13/2014 Page 6 of 6 Print Date 3/29/2014

National Pollutant Release	Inventory (NPRI)
not applicable	
WHMIS Classification :	D2B
WHMIS Ingredient Disclos	sure List
CAS-No. 7631-86-9	
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS :	Not determined
China IECS :	Not determined
Europe EINECS :	Listed
Japan ENCS :	Not determined
Korea KECI :	Not determined
Philippines PICCS :	Not determined
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.