PolyOne

MATERIAL SAFETY DATA SHEET AOSUR 154806

Version Number 1.1 Revision Date 03/13/2014

Page 1 of 6 Print Date 3/29/2014

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012		
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	AOSUR 154806
Product code	:	CC10154806
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	•	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	5 - 10
Amines, bis(hydrogenated tallow alkyl), oxidized	143925-92-2	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.



MATERIAL SAFETY DATA SHEET AOSUR 154806

Version Number 1.1 Revision Date 03/13/2014 Page 2 of 6 Print Date 3/29/2014

	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature	 not applicable not applicable not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
	 Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	Carbon dioxide blanket, Water spray, Dry powder, Foam.Fullface self-contained breathing apparatus (SCBA) used in positive
Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES Wear appropriate personal protection during cleanup, such as

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET AOSUR 154806

Version Number 1.1 Revision Date 03/13/2014 Page 3 of 6 Print Date 3/29/2014

	7. HANDLING A	ND STORAGE	
Handling		prevent the build up of electrosta appropriate exhaust ventilation.	atic charge. Heat
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.		
8. EX	POSURE CONTROLS/P	PERSONAL PROTECTION	
Respiratory protection	: No personal respir	ratory protective equipment norn	hally required.
Eye/Face Protection	: Safety glasses with	h side-shields	
Hand protection	: Protective gloves		
Skin and body protection	: Long sleeved cloth	ning	
Additional Protective Measures	: Safety shoes		
General Hygiene Considerations		nce with good industrial hygiene ands before breaks and at the end	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		
Exposure limit(s)			
9	. PHYSICAL AND CHE	MICAL PROPERTIES	
			NT . 11 11
Form Appearance	: solid : pellets	Evapouration rate : Specific Gravity :	Not applicable Not determined
Colour	: NO PIGMENT	Bulk density :	Not established
Odour	: very faint	Vapour pressure :	not applicable
Melting point/range	: Not determined	Vapour density :	not applicable
Boiling Point:	: not applicable	pH :	not applicable
	: insoluble		not appricable
Water solubility			
Water solubility			
Water solubility	10. STABILITY AN	D REACTIVITY	
		D REACTIVITY ble if stored and handled as press	cribed.
Water solubility Stability Hazardous Polymerization			cribed.

POLYONE CORPORATION

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET AOSUR 154806

ersion Number 1.1 evision Date 03/13/2014	Page 4 of 6 Print Date 3/29/2014
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	11. TOXICOLOGICAL INFORMATION
	aluated as a whole for health effects. Exposure effects listed are based on existing components which comprise the mixture.
Toxicity Overview	

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5- triazine, reaction products	Irritant	Eyes, Skin, Respiratory system.
143925-92-2	Amines, bis(hydrogenated tallow alkyl), oxidized	sensitizer	Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-	Oral LD50	> 2,000 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-	Dermal LD50	> 3,000 mg/kg	rat
	piperidinyl)-,polymer with			
	2,4,6-trichloro-1,3,5-			
	triazine, reaction products			

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste



MATERIAL SAFETY DATA SHEET **AOSUR 154806**

sion Number 1.1 ision Date 03/13/2014	Page 5 of Print Date 3/29/201
	classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
	ease Inventory (NPRI)

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET AOSUR 154806

Version Number 1.1		Page 6 of 6
Revision Date 03/13/2014		Print Date 3/29/2014
not applicable		
WHMIS Classification	:	D2B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.