PolyOne

MATERIAL SAFETY DATA SHEET **SAND DUNE**

Version Number 1.1 Revision Date 03/13/2014 Page 1 of 8 Print Date 3/29/2014

1. PRODUCT AND COMPANY IDENTIFICATION				
POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure		
number		or accident).		
Product name	:	SAND DUNE		
Product code	:	CC10155352		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	68412-38-4	1 - 5
Calcium stearate	1592-23-0	1 - 5
Rutile, antimony chromium buff	68186-90-3	1 - 5
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion Eyes	May be harmful if swallowed.Resin particles, like other inert materials, are mechanically irritating to



MATERIAL SAFETY DATA SHEET **SAND DUNE**

sion Date 03/13/2014	Page 2 Print Date 3/29/2
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.

PolyOne.

MATERIAL SAFETY DATA SHEET **SAND DUNE**

Version Number 1.1 Revision Date 03/13/2014 Page 3 of 8 Print Date 3/29/2014

Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne.

MATERIAL SAFETY DATA SHEET **SAND DUNE**

Version Number 1.1 Revision Date 03/13/2014 Page 4 of 8 Print Date 3/29/2014


Components	Value	Exposure time	Exposure type	List:
Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	1 mg/m3	Recommended exposure limit (REL):	Fume. as Mn	NIOSH
	3 mg/m3	Short Term Exposure Limit (STEL):	Fume. as Mn	NIOSH
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

PolyOne

MATERIAL SAFETY DATA SHEET **SAND DUNE**

Version Number 1.1 Revision Date 03/13/2014



Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid pellets TAN very faint Not determined not applicable insoluble 	Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not applicable Not determined Not established not applicable not applicable not applicable
	10. STABILITY ANI	D REACTIVITY	

Stability	: The	product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will	not occur.
Conditions to avoid	-	away from oxidizing agents and open flame. To avoid thermal mposition, do not overheat.
Incompatible Materials	: Inco	mpatible with strong acids and oxidizing agents.
Hazardous decomposition products		on dioxide (CO2), carbon monoxide (CO), oxides of nitrogen x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68412-38-4	Manganese antimony	Irritant	Eyes, Skin.
	titanium brown rutile (C.I.		
	Pigment Yellow 164)		
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat

Carcinogenicity

PolyOne

MATERIAL SAFETY DATA SHEET **SAND DUNE**

Version Number 1.1 Revision Date 03/13/2014

Page 6 of 8 Print Date 3/29/2014

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	Chemicals are not readily available as they are bound within the polymer matrix.	
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.	
Additional advice	: no data available	
	13. DISPOSAL CONSIDERATIONS	
Product Contaminated packaging	 Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, 	
	transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	: Not regulated for transportation.	
ICAO/IATA	: Refer to specific regulation.	
IMO/IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **SAND DUNE**

US Regulations: OSHA Status : Classified as ha TSCA Status : All component TSCA Inventor US. EPA CERCLA Hazardous Substances (40 CFR not applicable California Proposition : WARNING! T 65 : California to ca SARA Title III Section 302 Extremely Hazardous Su Unless specific chemicals are identified under this se	s of this p y. 302) This produ use cance ubstance	oroduct are act contains er.	listed on o	r exem l know	n to the S	State of
OSHA Status : Classified as ha TSCA Status : All component TSCA Inventor US. EPA CERCLA Hazardous Substances (40 CFR not applicable California Proposition : WARNING! T 65 California to ca SARA Title III Section 302 Extremely Hazardous Su	s of this p y. 302) This produ use cance ubstance	oroduct are act contains er.	listed on o	r exem l know	n to the S	State of
TSCA Status : All component TSCA Inventor US. EPA CERCLA Hazardous Substances (40 CFR not applicable California Proposition : WARNING! T California to ca	s of this p y. 302) This produ use cance ubstance	oroduct are act contains er.	listed on o	r exem l know	n to the S	State of
TSCA Inventor US. EPA CERCLA Hazardous Substances (40 CFR not applicable California Proposition : WARNING! T 65 California to ca SARA Title III Section 302 Extremely Hazardous Su	y. 302) This produ use cance ubstance	et contains er.	a chemica	l know	n to the S	State of
not applicable California Proposition : WARNING! T 65 : California to ca SARA Title III Section 302 Extremely Hazardous Su	'his produ use cance ubstance	er.				
California Proposition : WARNING! T 65 California to ca SARA Title III Section 302 Extremely Hazardous Su	use cance	er.				
65 California to ca SARA Title III Section 302 Extremely Hazardous Su	use cance	er.				
		s product is	Not Appl	icable	under this	
Unless specific chemicals are identified under this se	ection, thi	s product is	Not Appl	icable	under this	
		- F	- · · · · · · · · · · · · · · · · · · ·			s regulation
						C
SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this se Chemical Name	ection, thi	s product is			under this percent	s regulatio
MANGANESE COMPOUNDSMANGANESE		Ű		.00 - 5		
COMPOUNDSANTIMONY COMPOUNDS						
CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY	68186-90-3 1.00		.00 - 5	5.00		
COMPOUNDSCHROMIUM COMPOUNDS	12737-27-8		0.10 - 1.00			
CHROMIUM III COMPOUNDSCHROMIUM COMPOUNDS		12/3/-2/	-27-8 0.10 -		1.00	
Canadian Regulations:						
National Pollutant Release Inventory (NPRI)		τ	XX7 . 1 . 1 . 4		NDDLI	24
Chemical Name	CAS-N	10.	Weight percent		NPRI II	J#
Aluminum oxide	1344-2	8-1	0.10 - 1.0	00		
Manganese antimony titanium brown rutile (C.I.		12-38-4 1.00 - 5.00				
Pigment Yellow 164)	<u> </u>					
	(010)	1.00 - 5.00 68186-90-3 1.00 - 5.00				
Rutile, antimony chromium buff			1.00 - 5.00 0.10 - 1.00			
I foli chi olinte biown spiner	n chromite brown spinel 12737		0.10 - 1.0	10		

PolyOne

MATERIAL SAFETY DATA SHEET **SAND DUNE**

Version Number 1.1 Revision Date 03/13/2014 Page 8 of 8 Print Date 3/29/2014

WHMIS Classification	:	D2A					
WHMIS Ingredient Discl	losu	ire List					
CAS-No. 68412-38-4 68186-90-3 DSL		All components of this product are on the Canadian Domestic					
	•	Substances List (DSL) or are exempt.					
National Inventories:							
Australia AICS	:	Listed					
China IECS	:	Listed					
Europe EINECS	:	Listed					
Japan ENCS	:	Not determined					
Korea KECI	:	Listed					
Philippines PICCS	:	Not determined					
	16. OTHER INFORMATION						

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.