

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****UV CLEK GREEN 355**Version Number 1.2
Revision Date 02/06/2012Page 1 of 7
Print Date 2/6/2012**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
33587 Walker Road, Avon Lake, OH 44012Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**Product name : UV CLEK GREEN 355
Product code : CC10157424
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-	26741-53-7	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Ingestion, Skin contact**Acute exposure**

Inhalation : Resin particles, like other inert materials, can be mechanically

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

UV CLEK GREEN 355

Version Number 1.2
Revision Date 02/06/2012

Page 3 of 7
Print Date 2/6/2012

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective Measures : Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

UV CLEK GREEN 355

Version Number 1.2
 Revision Date 02/06/2012

Page 4 of 7
 Print Date 2/6/2012

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	6 mg/m ³	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m ³	Time Weighted Average (TWA):		Z3
	10 mg/m ³	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m ³	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m ³	Time Weighted Average (TWA):		ACGIH
	15 mg/m ³	PEL:	Total dust.	OSHA Z1
	10 mg/m ³	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m ³	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m ³	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: solid	Evaporation rate	: Not applicable
Appearance	: pellets	Specific Gravity	: Not determined
Colour	: GREEN	Bulk density	: Not established
Odour	: very faint	Vapour pressure	: not applicable
Melting point/range	: Not determined	Vapour density	: not applicable
Boiling Point:	: not applicable	pH	: not applicable
Water solubility	: insoluble		

10. STABILITY AND REACTIVITY

Stability	: Stable
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

UV CLEK GREEN 355

Version Number 1.2
Revision Date 02/06/2012

Page 5 of 7
Print Date 2/6/2012

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	Irritant	Eyes, Skin, Respiratory system.
26741-53-7	2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-	Toxic	Refer to LC50 / LD50 Data on MSDS..
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	Oral LD50 Dermal LD50	> 2,000 mg/kg > 3,000 mg/kg	rat rat
26741-53-7	2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-	LC50 Oral LD50 Dermal LD50	> 2 gm/m3 5,580 mg/kg > 200 mg/kg	rat rat rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

UV CLEK GREEN 355

Version Number 1.2
Revision Date 02/06/2012

Page 6 of 7
Print Date 2/6/2012

polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.

Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Refer to specific regulation.

IMO/IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable
65

SARA Title III Section 302 Extremely Hazardous Substance

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****UV CLEK GREEN 355**Version Number 1.2
Revision Date 02/06/2012Page 7 of 7
Print Date 2/6/2012

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight percent	NPRI ID#
Phthalocyanine green	1328-53-6	1.00 - 5.00	

WHMIS Classification : D1B

WHMIS Ingredient Disclosure List

CAS-No.
1328-53-6
7631-86-9

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed
China IECS : Listed
Europe EINECS : Listed
Japan ENCS : Not determined
Korea KECI : Not determined
Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.