PolyOne

# MATERIAL SAFETY DATA SHEET **PLUM OPAQUE**

Version Number 1.1 Revision Date 02/01/2012 Page 1 of 6 Print Date 2/1/2012

POLYONE CORPORATI 33587 Walker Road, Avon	ION	UCT AND COMPANY IDENTIFICATION OH 44012
Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PLUM OPAQUE
Product code	:	CC10157503
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET PLUM OPAQUE

Version Number 1.1 Revision Date 02/01/2012 Page 2 of 6 Print Date 2/1/2012

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

**POLYONE CORPORATION** 

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET **PLUM OPAQUE**

Version Number 1.1 Revision Date 02/01/2012 Page 3 of 6 Print Date 2/1/2012

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	No personal respiratory protective equipme	nt normally required.
Eye/Face Protection	Safety glasses with side-shields	
Hand protection	Protective gloves	
Skin and body protection	Long sleeved clothing	
Additional Protective Measures	Safety shoes	
General Hygiene Considerations	Handle in accordance with good industrial l practice. Wash hands before breaks and at	
Engineering measures	Heat only in areas with appropriate exhaust appropriate exhaust ventilation at machiner	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	Total dust.	OSHA Z1A
		(TWA):		
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

Form Appearance Colour Odour	: solid : pellets : PURPLE : very faint	Evaporation rate Specific Gravity Bulk density Vapour pressure	<ul> <li>Not applicable</li> <li>Not determined</li> <li>Not established</li> <li>not applicable</li> </ul>
Melting point/range Boiling Point: Water solubility	<ul><li>Not determined</li><li>not applicable</li><li>insoluble</li></ul>	Vapour density pH	: not applicable : not applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable		

# MATERIAL SAFETY DATA SHEET **PLUM OPAQUE**

Version Number 1.1 Revision Date 02/01/2012 Page 4 of 6 Print Date 2/1/2012

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available

PolyOne.

# MATERIAL SAFETY DATA SHEET **PLUM OPAQUE**

Version Number 1.1 Revision Date 02/01/2012 Page 5 of 6 Print Date 2/1/2012

ike most thermoplastic plastics the product can be recycled. Where ossible recycling is preferred to disposal or incineration. The enerator of waste material has the responsibility for proper waste assification, transportation and disposal in accordance with oplicable federal, state/provincial and local regulations. ecycling is preferred when possible. The generator of waste aterial has the responsibility for proper waste classification, ansportation and disposal in accordance with applicable federal, ate/provincial and local regulations. <b>TRANSPORT INFORMATION</b> ot regulated for transportation. efer to specific regulation. efer to specific regulation. efer to specific regulation. efer to specific regulation.
aterial has the responsibility for proper waste classification, ansportation and disposal in accordance with applicable federal, ate/provincial and local regulations. <b>TRANSPORT INFORMATION</b> ot regulated for transportation. efer to specific regulation. efer to specific regulation. <b>EGULATORY INFORMATION</b>
ot regulated for transportation. efer to specific regulation. efer to specific regulation. EGULATORY INFORMATION
efer to specific regulation. efer to specific regulation. EGULATORY INFORMATION
efer to specific regulation. EGULATORY INFORMATION
EGULATORY INFORMATION
lassified as hazardous based on components.
lassified as hazardous based on components.
All components of this product are listed on or exempt from the SCA Inventory.
aces (40 CFR 302)
ot applicable
Hazardous Substance
d under this section, this product is Not Applicable under this regula

## MATERIAL SAFETY DATA SHEET PLUM OPAQUE

Version Number 1.1 Revision Date 02/01/2012 Page 6 of 6 Print Date 2/1/2012

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) NPRI ID# Chemical Name CAS-No. Weight percent 1344-28-1 0.10 - 1.00 Aluminum oxide WHMIS Classification : D2A DSL DSL status has not been determined. Quantity use in Canada may be : restricted by regulations. National Inventories: Australia AICS Not determined : China IECS Not determined : Europe EINECS Not determined : Japan ENCS : Not determined Korea KECI Not determined : **Philippines PICCS** Not determined :

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.