

### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016

Page 1 of 20 Print Date 11/08/2016

# SAFETY DATA SHEET

#### LTU SANDSTORM 357HP

# **Section 1. Identification**

**GHS** product identifier LTU SANDSTORM 357HP

Chemical name Mixture CAS number Mixture Other means of identification CC10157877

**Product type** solid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

POLYONE CORPORATION Supplier's details

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

**Emergency telephone number** 

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

**OSHA/HCS** status

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product. This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

Not classified.

#### **GHS** label elements



### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 2 of 20 Print Date 11/08/2016

Signal word : No signal word.DANGER!

**Hazard statements**: No known significant effects or critical hazards.

#### **Precautionary statements**

General:Not applicable.Prevention:Not applicable.Response:Not applicable.Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: CC10157877

#### **CAS** number/other identifiers

Ingredient name	<b>%</b>	CAS number
2-Propenenitrile, polymer with Ethenylbenzene	50 - 75	9003-54-7
Titanium dioxide	5 - 10	13463-67-7
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl) ester	3 - 5	52829-07-9
Styrene	0.1 - 0.3	100-42-5
Carbon black	0.1 - 0.3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 3 of 20 Print Date 11/08/2016

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

#### Description of necessary first aid measures

Inhalation

Skin contact

**Ingestion** 

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs. Check for and remove any
		contact lenses. Immediately flush eyes with plenty of water for at least
		15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Call medical doctor or poison control center immediately. Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. No known significant

effects or critical hazards.

Inhalation : No known significant effects or critical hazards. Very toxic by

inhalation. Exposure to decomposition products may cause a health



### LTU SANDSTORM 357HP

Version Number 1.3 Page 4 of 20 Revision Date 10/19/2016 Print Date 11/08/2016

hazard. Serious effects may be delayed following exposure.

**Skin contact** : No known significant effects or critical hazards. No known significant

effects or critical hazards.

**Ingestion**: No known significant effects or critical hazards. No known significant

effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48

hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without

suitable training. No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# **Section 5. Fire-fighting measures**

#### **Extinguishing media**

**Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.In

case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.

**Unsuitable extinguishing media** : None known. None known.

Specific hazards arising from the

chemical

: No specific fire or explosion hazard. No specific fire or explosion

hazard.

**Hazardous thermal**: Decomposition products may include the following materials:



#### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 5 of 20 Print Date 11/08/2016

decomposition products carbon dioxide

carbon monoxide nitrogen oxides

metal oxide/oxidesDecomposition products may include the following

materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of

any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways,

soil or air).

#### Methods and materials for containment and cleaning up

Small spill : Move containers from spill area. Vacuum or sweep up material and



#### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 6 of 20 Print Date 11/08/2016

Large spill

place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures Advice on general occupational hygiene

- : Put on appropriate personal protective equipment (see Section 8).
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.



# LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 7 of 20 Print Date 11/08/2016

# **Section 8. Exposure controls/personal protection**

# **Control parameters**

# Occupational exposure limits

Ingredient name	Exposure limits		
Titanium dioxide	OSHA PEL 1989 (1989-03-01)		
	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust		
	OSHA PEL (1993-06-30)		
	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust		
	NIOSH REL (1994-06-01)		
	ACGIH TLV (1996-05-18)		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 10 mg/m3		
2-Propenenitrile, polymer with			
Ethenylbenzene			
Ci	OCH A DEL 1000 (1000 03 01)		
Styrene	OSHA PEL 1989 (1989-03-01)		
	PEL: Permissible Exposure Level 215 mg/m3 50 ppm Short Term Exposure Limit value for a 15-minute reference		
	period expressed in parts per million or in mg/m3. 425 mg/m3 100		
	ppm OSHA PEL Z2 (1993-06-30)		
	PEL: Permissible Exposure Level 100 ppm		
	Ceiling, is a a limit indicating the maximum concentration of a		
	chemical substances in the breathing zone that should not be		
	exceeded. 200 ppm		
	Acceptable Maximum Peak (AMP) 600 ppm		
	NIOSH REL (1994-06-01)		
	Time Weighted Average (TWA) 215 mg/m3 50 ppm		
	Short Term Exposure Limit value for a 15-minute reference		
	period expressed in parts per million or in mg/m3. 425 mg/m3 100		
	ppm		
	ACGIH TLV (1997-05-21)		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 85 mg/m3 20 ppm		
	TLV-STEL: Threshold Limit Value - Short Time Exposure Level 170 mg/m3 40 ppm		
	TLV-STEL: Threshold Limit Value - Short Time Exposure Lev		



### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 8 of 20 Print Date 11/08/2016

Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl) ester	
Carbon black	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction

#### **Appropriate engineering controls**

Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



#### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 9 of 20 Print Date 11/08/2016

#### Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**

#### Hand protection

chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### **Respiratory protection**

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.



### LTU SANDSTORM 357HP

 Version Number 1.3
 Page 10 of 20

 Revision Date 10/19/2016
 Print Date 11/08/2016

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state : solid [Pellets.]

Color **TAN** Odor Faint odor. **Odor threshold** Not available. Hq Not available. **Melting point** Not available. **Boiling** point Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Not available. Flammability (solid, gas)

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Solubility in water: insoluble in water.

**Partition coefficient: n-** Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7). Stable under recommended storage and handling

conditions (see Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur. Under normal conditions of storage and use, hazardous

reactions will not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents. Keep away from

extreme heat and oxidizing agents.



# LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 11 of 20 Print Date 11/08/2016

**Incompatible materials** : Keep away from strong acids.

Oxidizer.Keep away from strong acids.

Oxidizer.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Information on toxicological effects**

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure		
Styrene	Styrene					
	LD50 Oral	Rat	2,650 mg/kg	-		
	LD50 Oral	Rat	5,000 mg/kg	-		
	LC50 Inhalation	Rat	2,770 ppm	4 h		
	LC50 Inhalation	Rat	11.8 mg/l	4 h		
Carbon black						
	LD50 Oral	Rat	15,400 mg/kg	-		
Decanedioic acid, bis(2,2,6,6-t	etramethyl-4-piperic	linyl) ester				
Titanium dioxide						
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h		
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-		
2-Propenenitrile, polymer with Ethenylbenzene						
	LD50 Oral	Rat	1,800 mg/kg	-		

Conclusion/Summary : Mixture.Not fully tested.

# Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Styrene	Eyes - Mild irritant	Human			-
	Skin - Mild irritant	Rabbit			-
	Skin - Moderate irritant	Rabbit			-
	Eyes - Severe irritant	Rabbit			-



# LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 12 of 20 Print Date 11/08/2016

	Eyes -	Rabbit	24 hrs	-
	Moderate			
	irritant			
Titanium dioxide	Skin - Mild	Human	72 hrs	-
	irritant			

**Conclusion/Summary** 

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Sensitization** 

**Conclusion/Summary** 

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

**Conclusion/Summary**: Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Classification			
Product/ingredient	OSHA	IARC	NTP
name			
Styrene		2B	Reasonably anticipated to be a human carcinogen.
Carbon black		2B	
Titanium dioxide		2B	
2-Propenenitrile, polymer		3	
with Ethenylbenzene			

### **Reproductive toxicity**

Conclusion/Summary : Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.



### LTU SANDSTORM 357HP

Version Number 1.3 Page 13 of 20 Revision Date 10/19/2016 Print Date 11/08/2016

**Aspiration hazard** 

Not available.

Information on the likely routes of

exposure

Not available.

Potential acute health effects

**Eye contact**: No known significant effects or critical hazards. No known significant

effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards. Very toxic by

inhalation. Exposure to decomposition products may cause a health

hazard. Serious effects may be delayed following exposure.

**Skin contact**: No known significant effects or critical hazards. No known significant

effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards. No known significant

effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate effects : Not available.
Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

**Conclusion/Summary** : Mixture.Not fully tested.

General : No known significant effects or critical hazards. Contains material that

can cause target organ damage.

Carcinogenicity : No known significant effects or critical hazards. Contains material

which may cause cancer, based on animal data. Risk of cancer

13/20



# LTU SANDSTORM 357HP

Version Number 1.3 Page 14 of 20 Revision Date 10/19/2016 Print Date 11/08/2016

depends on duration and level of exposure.

Mutagenicity: No known significant effects or critical hazards. No known significant

effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards. No known significant

effects or critical hazards.

**Developmental effects**: No known significant effects or critical hazards. No known significant

effects or critical hazards.

Fertility effects : No known significant effects or critical hazards. No known significant

effects or critical hazards.

#### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Not available.

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Styrene			
	Acute LC50 9,900 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 9.1 mg/l Marine water	Fish - Fish	96 h
	Acute LC50 4,020 μg/l Fresh water	Fish - Fish	96 h
	Acute LC50 4.7 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 4,080 μg/l Fresh water	Fish - Fish	96 h
	Acute LC50 23,000 µg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute EC50 4,700 μg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 59,000 µg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute LC50 52,000 µg/l Marine	Aquatic invertebrates.	48 h
	water	Crustaceans	
	Acute EC50 33 mg/l Fresh water	Aquatic plants - Algae	96 h
	Acute EC50 720 µg/l Fresh water	Aquatic plants - Algae	96 h
	Acute EC50 1,400 μg/l Fresh water	Aquatic plants - Algae	72 h
	Acute EC50 78,000 µg/l Marine	Aquatic plants - Algae	96 h
	water		
	Acute NOEC 63 µg/l Fresh water	Aquatic plants - Algae	4 d
Carbon black			



# LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 15 of 20 Print Date 11/08/2016

	Acute EC50 37.563 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute LC50 61.547 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Decanedioic acid, bis(2,2,6,6-to	etramethyl-4-piperidinyl) ester	T	•
	Acute LC50 4.4 Mg/l	Fish - Bluegill	96 h
	Acute EC50 8.6 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 0.705 Mg/l	Aquatic plants - Green algae	72 h
Titanium dioxide			•
	Acute LC50 > 1,000,000 μg/l Marine water	Fish - Fish	96 h
	Acute LC50 > 1,000 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates.  Daphnia	48 h
	Acute LC50 3 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 15.9 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 3.6 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 11 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 13.4 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 35.306 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
LTU SANDSTORM 357HP			•
Remarks - Acute - Aquatic invertebrates.:	Chemicals are not readily available a	s they are bound within the	e polymer matrix.

Conclusion/Summary

: Chemicals are not readily available as they are bound within the polymer matrix.

# Persistence and degradability

Conclusion/Summary

: Chemicals are not readily available as they are bound within the polymer matrix.



#### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 16 of 20 Print Date 11/08/2016

**Conclusion/Summary** : Chemicals are not readily available as they are bound within the

polymer matrix.

**Bioaccumulative potential** 

Product/ingredient name	LogPow	BCF	Potential
Styrene	2.96	13.49	low
Decanedioic acid,	0.35	-	low
bis(2,2,6,6-tetramethyl-4-			
piperidinyl) ester			
Titanium dioxide		352.00	low

#### Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards. No known significant

effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care



#### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 17 of 20 Print Date 11/08/2016

should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Not classified as dangerous good under transport regulations.

IMO/IMDG (maritime) : Not classified as dangerous good under transport regulations.

# Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

**United States - TSCA 8(c) - Significant adverse reaction (SAR):** 

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Acrylonitrile



### LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 18 of 20 Print Date 11/08/2016

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)

**Hazardous Air Pollutants (HAPs)** 

Clean Air Act Section 602 Class I

**Substances** 

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** 

Chemicals)

**DEA List II Chemicals (Essential** 

**Chemicals**)

Not listed

Not listed

Not listed

: Not listed

: Not listed

### US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

**SARA 311/312** 

**Classification** : Not applicable.

#### Composition/information on ingredients

Name	%	Classification
Styrene	0.1 - 0.3	F, AH, CH
Carbon black	0.1 - 0.3	СН
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl) ester	3 - 5	AH
2-Propenenitrile, polymer with Ethenylbenzene	50 - 75	AH

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting	Styrene	100-42-5	0.1 - 0.3
requirements			
	Rutile, antimony chromium	68186-90-3	5 - 10
	buff		



# LTU SANDSTORM 357HP

Version Number 1.3 Page 19 of 20 Revision Date 10/19/2016 Print Date 11/08/2016

Supplier notification	Rutile, antimony chromium buff	68186-90-3	5 - 10
	Styrene	100-42-5	0.1 - 0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

**Massachusetts** : The following components are listed:

Iron oxide

Titanium dioxide

**New York** : The following components are listed:

Styrene

**New Jersey** : The following components are listed:

Styrene Carbon black Iron oxide Titanium dioxide

2-Propenenitrile, polymer with Ethenylbenzene

**Pennsylvania** : The following components are listed:

Styrene

Titanium dioxide

Iron oxide

Carbon black

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

**International regulations** 

International lists : Australia inventory (AICS): Not determined.

Taiwan inventory (CSNN): Not determined.

Malaysia Inventory (EHS Register): Not determined. EINECS: All components are listed or exempted.

**Japan inventory:** Not determined.

China inventory (IECSC): Not determined.

**Korea inventory:** All components are listed or exempted.



# LTU SANDSTORM 357HP

Version Number 1.3 Revision Date 10/19/2016 Page 20 of 20 Print Date 11/08/2016

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

**Chemical Weapons Convention List Schedule I Chemicals** 

Chemical Weapons Convention List Schedule II Chemicals

Chemical Weapons Convention
List Schedule III Chemicals

Not listed

Not listed

Not listed

# Section 16. Other information

**History** 

Date of printing: 11/08/2016Date of issue/Date of revision: 10/19/2016Date of previous issue: 10/14/2015

Version : 1.3

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.