MATERIAL SAFETY DATA SHEET UV WHITE PVC 140

Version Number 1.3 Revision Date 10/19/2012

Product Use

Page 1 of 8 Print Date 10/22/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV WHITE PVC 140
Product code	:	CC10158211
Chemical Name	:	Mixture
CAS-No.	:	Mixture

- : Mixture
 - Industrial Applications :

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
Phenol, 2-(2H-benzotriazol-2-yl)-4,6- bis(1,1-dimethylpropyl)-	25973-55-1	1 - 5
Calcium carbonate	1317-65-3	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Ingestion, Skin contact

Acute exposure



MATERIAL SAFETY DATA SHEET UV WHITE PVC 140

Inhalation Ingestion Eyes Skin Chronic exposure Medical Conditions Aggravated by Exposure:	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information. None known.
Ingestion Eyes Skin Chronic exposure Medical Conditions	 irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information.
Eyes Skin Chronic exposure Medical Conditions	 Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information.
Skin Chronic exposure Medical Conditions	eyes.Experience shows no unusual dermatitis hazard from routine handlingRefer to Section 11 for Toxicological Information.
Chronic exposure Medical Conditions	 Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information.
Medical Conditions	
Medical Conditions	
	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from
	overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Auto-ignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
6	. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not

2/8



MATERIAL SAFETY DATA SHEET UV WHITE PVC 140

Version Number 1.3 Revision Date 10/19/2012		Page 3 of 8 Print Date 10/22/2012
Methods for cleaning up	:	be allowed to enter drains, water courses or the soil. Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSUF	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET UV WHITE PVC 140

Version Number 1.3 Revision Date 10/19/2012 Page 4 of 8 Print Date 10/22/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 pellets
 WHITE
 very faint
 Not determined
 not applicable
 insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- Not applicableNot determinedNot establishednot applicablenot applicable
- : not applicable

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

MATERIAL SAFETY DATA SHEET UV WHITE PVC 140

 Version Number 1.3
 Page 5 of 8

 Revision Date 10/19/2012
 Print Date 10/22/2012

 Incompatible Materials
 : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-	Irritant	Eyes, Skin, Respiratory
	bis(2,2,6,6-tetramethyl-4-		system.
	piperidinyl)-,polymer with		
	2,4,6-trichloro-1,3,5-		
	triazine, reaction products		
25973-55-1	Phenol, 2-(2H-	Systemic effects	Kidney, Liver, reproductive
	benzotriazol-2-yl)-4,6-		system.
	bis(1,1-dimethylpropyl)-		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
112926-00-8	Silica, amorphous,	Irritant	Respiratory system, Eyes.
	precipitated and gel		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-	Oral LD50	> 2,000 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-	Dermal LD50	> 3,000 mg/kg	rat
	piperidinyl)-,polymer with			
	2,4,6-trichloro-1,3,5-			
	triazine, reaction products			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

PolyOne.

MATERIAL SAFETY DATA SHEET UV WHITE PVC 140

Version Number 1.3 Revision Date 10/19/2012 Page 6 of 8 Print Date 10/22/2012

NTP Carcinogen Classification 1 - The component is known to 2 - The component is reasonabl	
	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.

6/8

PolvOne

MATERIAL SAFETY DATA SHEET UV WHITE PVC 140

Version Number 1.3 Revision Date 10/19/2012 Page 7 of 8 Print Date 10/22/2012

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
7631-86-9	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

:

16. OTHER INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET UV WHITE PVC 140

Version Number 1.3 Revision Date 10/19/2012 Page 8 of 8 Print Date 10/22/2012

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.