

### MATERIAL SAFETY DATA SHEET

## PP SILVER UV

Version Number 1.0 Page 1 of 8
Revision Date 03/01/2012 Print Date 8/23/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

or accident).

Product name : PP SILVER UV
Product code : CC10159136
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components   | CAS-No.   | Weight percent |
|--------------|-----------|----------------|
| Carbon black | 1333-86-4 | 1 - 5          |
| Aluminum     | 7429-90-5 | 10 - 30        |

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically

irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to

eves.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.



### MATERIAL SAFETY DATA SHEET

# PP SILVER UV

 Version Number 1.0
 Page 2 of 8

 Revision Date 03/01/2012
 Print Date 8/23/2012

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : not applicable

Flammable Limits

Upper explosion limit : not applicable Lower explosion limit : not applicable Autoignition temperature : not applicable

Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section

13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat



## MATERIAL SAFETY DATA SHEET

# PP SILVER UV

 Version Number 1.0
 Page 3 of 8

 Revision Date 03/01/2012
 Print Date 8/23/2012

only in areas with appropriate exhaust ventilation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective

Measures

: Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



# MATERIAL SAFETY DATA SHEET

# PP SILVER UV

Version Number 1.0 Revision Date 03/01/2012 Page 4 of 8 Print Date *8/23/2012* 

| Components   | Value     | Exposure time                     | Exposure type                         | List:    |
|--------------|-----------|-----------------------------------|---------------------------------------|----------|
| Aluminum     | 1 mg/m3   | Time Weighted Average (TWA):      | Respirable fraction.                  | ACGIH    |
|              | 10 mg/m3  | Recommended exposure limit (REL): | Total                                 | NIOSH    |
|              | 5 mg/m3   | Recommended exposure limit (REL): | Respirable.                           | NIOSH    |
|              | 5 mg/m3   | Recommended exposure limit (REL): | Welding fume or pyrophoric powder. as | NIOSH    |
|              | 15 mg/m3  | PEL:                              | Total dust. as Al                     | OSHA Z1  |
|              | 5 mg/m3   | PEL:                              | Respirable dust. as Al                | OSHA Z1  |
|              | 15 mg/m3  | Time Weighted Average (TWA):      | Total dust. as Al                     | OSHA Z1A |
|              | 5 mg/m3   | Time Weighted Average (TWA):      | Respirable dust. as Al                | OSHA Z1A |
|              | 5 mg/m3   | Time Weighted Average (TWA):      | Pyrophoric powder. as<br>Al           | OSHA Z1A |
|              | 5 mg/m3   | Time Weighted Average (TWA):      | Fume. as Al                           | OSHA Z1A |
|              | 5 mg/m3   | Time Weighted Average (TWA):      | Welding fume.                         | MX OEL   |
|              | 10 mg/m3  | Time Weighted Average (TWA):      | Dust.                                 | MX OEL   |
|              | 5 mg/m3   | Time Weighted Average (TWA):      | Pyrophoric powder.                    | MX OEL   |
| Carbon black | 3.5 mg/m3 | Recommended exposure limit (REL): |                                       | NIOSH    |
|              | 0.1 mg/m3 | Recommended exposure limit (REL): |                                       | NIOSH    |
|              | 3.5 mg/m3 | PEL:                              |                                       | OSHA Z1  |
|              | 3.5 mg/m3 | Time Weighted Average (TWA):      |                                       | OSHA Z1A |
|              | 3.5 mg/m3 | Time Weighted Average (TWA):      |                                       | MX OEL   |
|              | 7 mg/m3   | Short Term Exposure Limit (STEL): |                                       | MX OEL   |
|              | 3 mg/m3   | Time Weighted Average (TWA):      | Inhalable fraction.                   | ACGIH    |

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : solid Evaporation rate : Not applicable Appearance Specific Gravity : Not determined : pellets Colour : GREY Bulk density : Not established Vapour pressure : very faint : not applicable Odour Melting point/range : Not determined Vapour density : not applicable Boiling Point: : not applicable pН : not applicable

Water solubility : insoluble



### MATERIAL SAFETY DATA SHEET

## PP SILVER UV

 Version Number 1.0
 Page 5 of 8

 Revision Date 03/01/2012
 Print Date 8/23/2012

#### 10. STABILITY AND REACTIVITY

Stability : Stable

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

products (NOx), other hazardous materials, and smoke are all possible.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.   | Chemical Name | Effect           | Target Organ              |  |
|-----------|---------------|------------------|---------------------------|--|
| 1333-86-4 | Carbon black  | Systemic effects | Eyes, Respiratory system. |  |
| 7429-90-5 | Aluminum      | Irritant         | Skin, Respiratory system. |  |
|           |               | Systemic effects | Eyes, Skin, Respiratory   |  |
|           |               |                  | system.                   |  |

## LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No.   | Chemical Name | Route       | Value          | Species |
|-----------|---------------|-------------|----------------|---------|
| 1333-86-4 | Carbon black  | Oral LD50   | > 15,400 mg/kg | rat     |
|           |               | Dermal LD50 | > 3 gm/kg      | rabbit  |

#### **Additional Health Hazard Information:**

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

#### 12. ECOLOGICAL INFORMATION



### MATERIAL SAFETY DATA SHEET

# PP SILVER UV

Version Number 1.0 Page 6 of 8 Print Date 8/23/2012 Revision Date 03/01/2012

Persistence and degradability : Not readily biodegradable.

**Environmental Toxicity** Chemicals are not readily available as they are bound within the

polymer matrix.

**Bioaccumulation Potential** : Chemicals are not readily available as they are bound within the

polymer matrix.

: no data available Additional advice

13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastic plastics the product can be recycled. Where

> possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with

applicable federal, state/provincial and local regulations.

Contaminated packaging Recycling is preferred when possible. The generator of waste

> material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA Refer to specific regulation.

IMO/IMDG (maritime) Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

**OSHA Status** : Classified as hazardous based on components.

**TSCA Status** All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable

65



# MATERIAL SAFETY DATA SHEET

# PP SILVER UV

 Version Number 1.0
 Page 7 of 8

 Revision Date 03/01/2012
 Print Date 8/23/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name                         | CAS-No.   | Weight percent |
|---------------------------------------|-----------|----------------|
| ALUMINUM (FUME OR DUST)ALUMINUM (FUME | 7429-90-5 | 10.00 - 30.00  |
| OR DUST)                              |           |                |

# Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No.   | Weight        | NPRI ID# |
|---------------|-----------|---------------|----------|
|               |           | percent       |          |
| Aluminum      | 7429-90-5 | 10.00 - 30.00 |          |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No.   |
|-----------|
| 7429-90-5 |
| 1333-86-4 |

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Listed

Philippines PICCS : Not determined

## 16. OTHER INFORMATION



## MATERIAL SAFETY DATA SHEET

# PP SILVER UV

Page 8 of 8 Print Date *8/23/2012* Version Number 1.0 Revision Date 03/01/2012

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.