PolyOne

MATERIAL SAFETY DATA SHEET 432 GREY PP

Version Number 1.1 Revision Date 11/14/2012 Page 1 of 6 Print Date 11/14/2012

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone E mergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	432 GREY PP		
Product code	:	CC10159799		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET 432 GREY PP

Version Number 1.1 Revision Date 11/14/2012 Page 2 of 6 Print Date 11/14/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET **432 GREY PP**

Version Number	er 1.1
Revision Date	11/14/2012

Page 3 of 6 Print Date 11/14/2012

Storage		: Keep containers dry and tightly closed to avoid moisture absorptio and contamination. Keep in a dry, cool place.	
8. EXPOSURE CONTROLS/PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.	
Eye/Face Protection	:	Safety glasses with side-shields	
Hand protection	:	Protective gloves	
Skin and body protection	:	Long sleeved clothing	
Additional Protective Measures	:	Safety shoes	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	Total dust.	OSHA Z1A
		(TWA):		
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

Form	: solid	Evaporation rate	: Not applicable
Appearance	: pellets	Specific Gravity	: Not determined
Colour	: GREY	Bulk density	: Not established
Odour	: very faint	Vapour pressure	: not applicable
Melting point/range	: Not determined	Vapour density	: not applicable
Boiling Point:	: not applicable	pН	: not applicable
Water solubility	: insoluble		
	10. STABILITY AN	D REACTIVITY	

PolyOne

MATERIAL SAFETY DATA SHEET 432 GREY PP

Version Number 1.1 Revision Date 11/14/2012

Page 4 of 6 Print Date 11/14/2012

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	no data available

13. DISPOSAL CONSIDERATIONS



MATERIAL SAFETY DATA SHEET 432 GREY PP

Version Number 1.1 Revision Date 11/14/2012	Page 5 of 6 Print Date <i>11/14/2012</i>		
Product	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Not regulated for transportation.		
ICAO/IATA	: Refer to specific regulation.		
IMO/IMDG (maritime)	: Refer to specific regulation.		
	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	: Classified as hazardous based on components.		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardous	Substances (40 CFR 302)		
not applicable			
California Proposition 65	: Not applicable		
SARA Title III Section 302 Ex	remely Hazardous Substance		
Unless specific chemicals are i	lentified under this section, this product is Not Applicable under this regulation		
SARA Title III Section 313 To	xic Chemicals:		
Unless specific chemicals are in Chemical Name	lentified under this section, this product is Not Applicable under this regulation CAS-No. Weight percent		
Chemical Mane	Cristito. Weight percent		
	5/6		

PolyOne

MATERIAL SAFETY DATA SHEET 432 GREY PP

Version Number 1.1 Revision Date 11/14/2012 Page 6 of 6 Print Date 11/14/2012

Chemical Name	CAS-No.	Weight percent
ZINC COMPOUNDS	68187-51-9	1.00 - 5.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI) Chemical Name Aluminum oxide			CAS-No.	Weight percent	NPRI ID#
			1344-28-1 68187-51-9	0.10 - 1.00 1.00 - 5.00	
Zinc ferrite brown spinel (C.I. Pigment Yellow 119)					
WHMIS Classification	:	D2A			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
ational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined	l		
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16. OTHER I	NFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.