PolvOne

MATERIAL SAFETY DATA SHEET **M35 YELLOW PVC 107C**

Version Number 1.0 Revision Date 03/29/2012 Page 1 of 7 Print Date 8/25/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposur or accident).	
Product name	:	M35 YELLOW PVC 107C	
Product code	:	CC10160970	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl	57583-35-4	1 - 5
ester		
Stannane, methyltris(2-	57583-34-3	1 - 5
ethylhexyloxycarbonylmethylthio)-		
Calcium stearate	1592-23-0	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.

PolyOne.

MATERIAL SAFETY DATA SHEET **M35 YELLOW PVC 107C**

Version Number 1.0 Revision Date 03/29/2012 Page 2 of 7 Print Date 8/25/2012

Ingestion Eyes Skin	 May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: not applicable		
Flammable Limits			
Upper explosion limit	: not applicable		
Lower explosion limit	: not applicable		
Autoignition temperature	: not applicable		
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.		
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.		
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. 		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		

PolyOne.

MATERIAL SAFETY DATA SHEET **M35 YELLOW PVC 107C**

sion Number 1.0 /ision Date 03/29/2012	Page 3 o Print Date 8/25/20
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

Components	Value	Exposure time	Exposure type	List:
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

: solid

: pellets

: YELLOW

MATERIAL SAFETY DATA SHEET M35 YELLOW PVC 107C

Version Number 1.0 Revision Date 03/29/2012

Form

Colour

Appearance

Water solubility	: insoluble 10. STABILITY AN	ND REACTIVITY			
Stability	: Stable				
Hazardous Polymerization	: Will not occur.				
Conditions to avoid		Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.			
Incompatible Materials	or acetal copolym processing. At pr destructive and in mechanically clea quantities of these	th strong oxidizers. Also, a ners and with amine contain rocessing conditions, these nvolve rapid degradation. T an processing equipment to e materials from coming in itamination of feedstocks.	ning materials during materials are mutually Fhoroughly purge and avoid even trace		
Hazardous decomposition products	(NOx), hydrogen smoke are all post or more) above 39	CO2), carbon monoxide (C chloride (HCl), other hazar sible. Prolonged heating (a 92 °F (200 °C) or short terr product decomposition and drogen chloride.	rdous materials, and approximately 30 minutes m heating at 482 °F (250		

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4- stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7- oxo-, 2-ethylhexyl ester	Irritant	Eyes, Skin.
57583-34-3	Stannane, methyltris(2- ethylhexyloxycarbonylmet hylthio)-	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

4/7

Page 4 of 7

Print Date 8/25/2012

Not applicable

Not determined

: Not established

olyOne

:

:

Evaporation rate

Specific Gravity

Bulk density

MATERIAL SAFETY DATA SHEET **M35 YELLOW PVC 107C**

Version Number 1.0

Revision Date 03/29/2012

Page 5 of 7 Print Date 8/25/2012

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57583-34-3	Stannane, methyltris(2- ethylhexyloxycarbonylmet hylthio)-	Oral LD50	920 mg/kg	rat
1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.	
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.	
Additional advice	: no data available	
	13. DISPOSAL CONSIDERATIONS	
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

MATERIAL SAFETY DATA SHEET **M35 YELLOW PVC 107C**

Version Number 1.0 Revision Date 03/29/2012 Page 6 of 7 Print Date 8/25/2012

U.S. DOT Classification	: Not reg	gulated for transportation.		
ICAO/IATA	: Refer to	: Refer to specific regulation.		
IMO/IMDG (maritime)	: Refer to	o specific regulation.		
	15. REGU	LATORY INFORMAT	ION	
US Regulations:				
OSHA Status	: Classif	ied as hazardous based or	n components.	
TSCA Status		mponents of this product Inventory.	are listed on or ex	empt from the
US. EPA CERCLA Hazardo	ous Substances (40 CFR 302)		
not applicable				
SARA Title III Section 302	Extremely Haza	rdous Substance		
	-		/	1 1 .1 . 1
Unless specific chemicals ar	e identified und	er this section, this produc	ct is not Applicat	ble under this regula
SARA Title III Section 313	Toxic Chemical	s.		
Unless specific chemicals ar			ct is Not Applicat	le under this regula
Canadian Regulations:		er ans section, ans produ		ie ander uns regula
National Pollutant Re	lease Inventory	(NPRI)		
Chemical Name	inventory	CAS-No.	Weight	NPRI ID#
Aluminum oxide		1344-28-1	0.10 - 1.00	
7 Hummuni Oxide				

PolyOne

MATERIAL SAFETY DATA SHEET **M35 YELLOW PVC 107C**

Version Number 1.0 Revision Date 03/29/2012 Page 7 of 7 Print Date 8/25/2012

WHMIS Ingredient Disclosure List		
CAS-No. 57583-34-3		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.