PolyOne

MATERIAL SAFETY DATA SHEET BISQUE NYLON

Version Number 1.0 Revision Date 05/01/2012 Page 1 of 7 Print Date 8/26/2012

1. PRODUCT AND COMPANY IDENTIFICATION					
POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012					
Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	BISQUE NYLON			
Product code	:	CC10162391			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **BISQUE NYLON**

Version Number 1.0 Revision Date 05/01/2012 Page 2 of 7 Print Date 8/26/2012

Aggravated by Exposure:		
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all ca doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 	
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen 	
Hazards	(NOx), other hazardous materials, and smoke are all possible.	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Heat	



MATERIAL SAFETY DATA SHEET **BISQUE NYLON**

/ersion Number 1.0 Revision Date 05/01/2012		Page 3 of 7 Print Date <i>8/26/2012</i>
Storage	:	only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne.

MATERIAL SAFETY DATA SHEET BISQUE NYLON

Version Number 1.0 Revision Date 05/01/2012

Page 4 of 7 Print Date 8/26/2012

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

Form
Appearance
Colour
Odour
Melting point/range
Boiling Point:
Water solubility

solid
pellets
TAN
very faint
Not determined
not applicable
insoluble

:

:

:

:

:

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

- : Not applicable
- : Not determined
- : Not established
- : not applicable
- not applicable :
- not applicable :

Stability

products

: Stable

- Hazardous Polymerization Will not occur. : Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
- **Incompatible Materials** Incompatible with strong acids and oxidizing agents. :
- Hazardous decomposition Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen : (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET BISQUE NYLON

Version Number 1.0 Revision Date 05/01/2012 Page 5 of 7 Print Date 8/26/2012

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,
	transportation and disposal in accordance with appreadic reactal,

PolyOne.

Page 6 of 7

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET **BISQUE NYLON**

Version Number 1.0

	sta	te/provincial and local regula	ations.	
	14. T	RANSPORT INFORMAT	ION	
U.S. DOT Classification	: No	t regulated for transportation		
ICAO/IATA	: Re	fer to specific regulation.		
IMO/IMDG (maritime)	: Re	fer to specific regulation.		
	15. RI	GULATORY INFORMA	ΓΙΟΝ	
US Regulations:				
OSHA Status	: Cla	ssified as hazardous based o	n components.	
TSCA Status		l components of this product CA Inventory.	are listed on or exe	empt from the
US. EPA CERCLA Hazardo	us Substand	ces (40 CFR 302)		
not applicable				
California Propositio 65	n : No	t applicable		
SARA Title III Section 302 I	Extremely I	Hazardous Substance		
Unless specific chemicals are	e identified	under this section, this produ	act is Not Applicab	le under this regul
SARA Title III Section 313	Foxic Chen	icals:		
Unless specific chemicals are	e identified	under this section, this produ	act is Not Applicab	le under this regul
Canadian Regulations:				
National Pollutant Re	lease Inven	tory (NPRI)		
Chemical Name		CAS-No.	Weight percent	NPRI ID#
Aluminum oxide Rutile, antimony chromiur	- hff	1344-28-1 68186-90-3	0.10 - 1.00 0.10 - 1.00	

PolyOne

MATERIAL SAFETY DATA SHEET BISQUE NYLON

Version Number 1.0 Revision Date 05/01/2012 Page 7 of 7 Print Date 8/26/2012

	WHMIS Classification	:	D2A	
	WHMIS Ingredient Disclosure List			
	CAS-No. 68186-90-3			
	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:				
	Australia AICS	:	Listed	
	China IECS	:	Listed	
	Europe EINECS	:	Listed	
	Japan ENCS	:	Listed	
	Korea KECI	:	Listed	
	Philippines PICCS	:	Listed	
16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.