PolyOne

MATERIAL SAFETY DATA SHEET **MS PINK BK**

Version Number 1.0 Revision Date 05/04/2012 Page 1 of 7 Print Date 8/26/2012

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012				
Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	MS PINK BK		
Product code	:	CC10162515		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

Components	CAS-No.	Weight percent
Aluminum	7429-90-5	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Particulates, like other inert materials can be mechanically irritating.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



MATERIAL SAFETY DATA SHEET MS PINK BK

Version Number 1.0 Revision Date 05/04/2012 Page 2 of 7 Print Date 8/26/2012

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Class D special powder against metal fire, Dry chemical. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Dust containing aluminum powder can be explosive. Do not use a solid water stream as it may scatter and spread fire. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **MS PINK BK**

Version Number 1.0 Revision Date 05/04/2012		Page 3 of 7 Print Date <i>8/26/2012</i>
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves. Refer to equipment supplier to ensure protection.
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET **MS PINK BK**

Version Number 1.0 Revision Date 05/04/2012 Page 4 of 7 Print Date 8/26/2012

Components	Value	Exposure time	Exposure type	List:
Aluminum 1 mg/m3		Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Welding fume or pyrophoric powder. as Al	NIOSH
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	15 mg/m3	Time Weighted Average (TWA):	Total dust. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Respirable dust. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Fume. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Welding fume.	MX OEL
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 powder, granular
 PINK
 very faint
 Not determined
 not applicable
 insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not determined
 not applicable
 not applicable
 not applicable

10. STABILITY AND REACTIVITY		
Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with acids and bases., Oxidizing agents, Halogenated compounds

PolyOne

MATERIAL SAFETY DATA SHEET **MS PINK BK**

Version Number 1.0

Revision Date 05/04/2012

Page 5 of 7 Print Date 8/26/2012

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **MS PINK BK**

on Number 1.0 ion Date 05/04/2012				Pr	Pag int Date 8/2
JS Regulations:					
OSHA Status	: Classified as ha	zardous based	on componen	nts.	
TSCA Status	: All component TSCA Inventor		t are listed of	n or exen	npt from the
JS. EPA CERCLA Hazardou	s Substances (40 CFR	302)			
not applicable					
California Proposition 65	: Not applicable				
	xtremely Hazardous Su	Ibstance			
SARA Title III Section 302 E					
Unless specific chemicals are	oxic Chemicals:	-		-	
Jnless specific chemicals are GARA Title III Section 313 To Jnless specific chemicals are Chemical Name ALUMINUM (FUME OR I	oxic Chemicals: identified under this se	ction, this prod		pplicable	under this repercent
Jnless specific chemicals are SARA Title III Section 313 To Jnless specific chemicals are Chemical Name ALUMINUM (FUME OR I OR DUST)	oxic Chemicals: identified under this se	ction, this prod	<u>uct is Not Aj</u> S-No.	pplicable Weight	under this repercent
Unless specific chemicals are GARA Title III Section 313 To Unless specific chemicals are Chemical Name ALUMINUM (FUME OR I OR DUST) Canadian Regulations:	oxic Chemicals: identified under this se DUST)ALUMINUM (I	ction, this prod	<u>uct is Not Aj</u> S-No.	pplicable Weight	under this repercent
Unless specific chemicals are SARA Title III Section 313 To Unless specific chemicals are Chemical Name ALUMINUM (FUME OR I OR DUST)	oxic Chemicals: identified under this se DUST)ALUMINUM (I	ction, this prod	uct is Not Aj S-No. -90-5 Weigh	pplicable Weight 10.00 -	under this repercent
ALUMINUM (FUME OR I OR DUST) Canadian Regulations: National Pollutant Rele	oxic Chemicals: identified under this se DUST)ALUMINUM (I	ction, this prod CA FUME 7429	uct is Not Aj S-No. -90-5 Weigh percer	pplicable Weight 10.00 -	under this re percent · 30.00
Jnless specific chemicals are GARA Title III Section 313 To Jnless specific chemicals are Chemical Name ALUMINUM (FUME OR I OR DUST) Canadian Regulations: National Pollutant Rele Chemical Name	oxic Chemicals: identified under this se DUST)ALUMINUM (1 ease Inventory (NPRI) 1 : D2B	CAS-No.	uct is Not Aj S-No. -90-5 Weigh percer	pplicable Weight 10.00 -	under this re percent 30.00

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **MS PINK BK**

Version Number 1.0 Revision Date 05/04/2012

Page 7 of 7 Print Date 8/26/2012

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.