MATERIAL SAFETY DATA SHEET **NEW GOLD BOND OPAQUE**

Version Number 1.0 Revision Date 05/09/2012 Page 1 of 7 Print Date 8/26/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	NEW GOLD BOND OPAQUE
Product code :	CC10163010
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **NEW GOLD BOND OPAQUE**

Version Number 1.0 Revision Date 05/09/2012 Page 2 of 7 Print Date 8/26/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

POLYONE CORPORATION

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **NEW GOLD BOND OPAQUE**

Version Number 1.0 Revision Date 05/09/2012 Page 3 of 7 Print Date 8/26/2012

Storage	:	only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.	
8. EXPO	SUE	RE CONTROLS/PERSONAL PROTECTION	
Respiratory protection	:	No personal respiratory protective equipment normally required.	
Eye/Face Protection	:	Safety glasses with side-shields	
Hand protection	:	Protective gloves	
Skin and body protection	:	Long sleeved clothing	
Additional Protective Measures	:	Safety shoes	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	6 mg/m3	Recommended exposure		NIOSH
		limit (REL):		
	0.8 mg/m3	Time Weighted Average		Z3
		(TWA):		
	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	Total dust.	OSHA Z1A
		(TWA):		
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
	_	(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : solid : pellets Evaporation rate Specific Gravity Not applicableNot determined

MATERIAL SAFETY DATA SHEET **NEW GOLD BOND OPAQUE**

Version Number 1.0 Revision Date 05/09/2012

Colour Odour Melting point/range Boiling Point: Water solubility	: ve : No : no	ELLOW ery faint ot determined ot applicable soluble	Bulk density Vapour pressure Vapour density pH	::	Not established not applicable not applicable not applicable
	1(). STABILITY AND RE	EACTIVITY		
Stability	:	Stable			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from oxidizide decomposition, do not o	001	lame.	To avoid thermal
Incompatible Materials	:	Incompatible with stron	g acids and oxidizing	agen	ts.
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), other hazardous			-

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

4/7

<u>PolyOne</u>

Page 4 of 7 Print Date 8/26/2012

PolyOne.

MATERIAL SAFETY DATA SHEET **NEW GOLD BOND OPAQUE**

eadily biodegradable. icals are not readily available as they are bound within the ter matrix. icals are not readily available as they are bound within the ter matrix. a available POSAL CONSIDERATIONS most thermoplastic plastics the product can be recycled. Where ble recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. Hing is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
icals are not readily available as they are bound within the eer matrix. icals are not readily available as they are bound within the eer matrix. a available POSAL CONSIDERATIONS most thermoplastic plastics the product can be recycled. Where ble recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
her matrix. icals are not readily available as they are bound within the her matrix. a available POSAL CONSIDERATIONS most thermoplastic plastics the product can be recycled. Where the recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste Fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. Hing is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
er matrix. a available POSAL CONSIDERATIONS nost thermoplastic plastics the product can be recycled. Where ble recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
POSAL CONSIDERATIONS nost thermoplastic plastics the product can be recycled. Where be recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
nost thermoplastic plastics the product can be recycled. Where ole recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
ble recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
NSPORT INFORMATION
gulated for transportation.
to specific regulation.
to specific regulation.
ULATORY INFORMATION
fied as hazardous based on components.
omponents of this product are listed on or exempt from the Inventory.
(40 CFR 302)

PolvOne.

MATERIAL SAFETY DATA SHEET **NEW GOLD BOND OPAQUE**

Version Number 1.0 Revision Date 05/09/2012 Page 6 of 7 Print Date 8/26/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
ZINC COMPOUNDS	68187-51-9	1.00 - 5.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Zinc ferrite brown spinel (C.I. Pigment Yellow 119)	68187-51-9	1.00 - 5.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
7631-86-9	

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed	
China IECS	: Listed	
Europe EINECS	: Listed	
Japan ENCS	: Not determin	ned
Korea KECI	: Not determin	ned
Philippines PICCS	: Not determine	ned

16. OTHER INFORMATION

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET **NEW GOLD BOND OPAQUE**

Version Number 1.0 Revision Date 05/09/2012 Page 7 of 7 Print Date 8/26/2012

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.