MATERIAL SAFETY DATA SHEET 11054 J D BROWN

Version Number 1.0 Revision Date 06/01/2012

Page 1 of 8 Print Date 8/26/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	11054 J D BROWN
Product code	:	CC10163987
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Calcium carbonate	1317-65-3	1 - 5
Carbon black	1333-86-4	1 - 5
Iron oxide	1309-37-1	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.

PolyOne.

MATERIAL SAFETY DATA SHEET 11054 J D BROWN

Version Number 1.0 Revision Date 06/01/2012 Page 2 of 8 Print Date 8/26/2012

	:	Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	:	Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	:	None known.
		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	::	not applicable not applicable not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Suitable extinguishing media Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive
Special Fire Fighting Procedures Unusual Fire/Explosion	: : : 6. A	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Special Fire Fighting Procedures Unusual Fire/Explosion	: : : 6. A (Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	: : 6. A (: :	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. CCIDENTAL RELEASE MEASURES Wear appropriate personal protection during cleanup, such as

PolyOne.

MATERIAL SAFETY DATA SHEET 11054 J D BROWN

Version Number 1.0 Revision Date 06/01/2012 Page 3 of 8 Print Date 8/26/2012

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne.

MATERIAL SAFETY DATA SHEET 11054 J D BROWN

Version Number 1.0 Revision Date 06/01/2012 Page 4 of 8 Print Date 8/26/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : solid : pellets Evaporation rate Specific Gravity

Not applicableNot determined

MATERIAL SAFETY DATA SHEET 11054 J D BROWN

Version Number 1.0 Revision Date 06/01/2012

Melting point/range

Hazardous Polymerization

Conditions to avoid

Incompatible Materials

Hazardous decomposition

Boiling Point:

Water solubility

Colour

Odour

Stability

products

11. TOXICOLOGICAL INFORMATION	I
This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing	

This mixture has not been evaluated as a whole for health effects. Exposure effects list health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

: BROWN

: very faint

: insoluble

: Stable

Will not occur.

:

:

: Not determined

: not applicable



Print Date 8/26/2012

Page 5 of 8

: : : not applicable

10. STABILITY AND REACTIVITY

decomposition, do not overheat.

Bulk density Vapour pressure Vapour density

Keep away from oxidizing agents and open flame. To avoid thermal

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

pН

: Incompatible with strong acids and oxidizing agents.

Not established not applicable

: not applicable

PolvOne

MATERIAL SAFETY DATA SHEET 11054 J D BROWN

Version Number 1.0 Revision Date 06/01/2012

Page 6 of 8 Print Date 8/26/2012

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	NY
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the
	polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the
	polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where
	possible recycling is preferred to disposal or incineration. The
	generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with
	applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification,
	transportation and disposal in accordance with applicable federal,
	state/provincial and local regulations.
	14. TRANSPORT INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET 11054 J D BROWN

AS. DOT Classification : Not regulated for tran CAO/IATA : Refer to specific regulated (O/IMDG (maritime) : Refer to specific regulated 15. REGULATORY IN S Regulations: OSHA Status : Classified as hazardo TSCA Status : All components of the TSCA Inventory. S. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65 ARA Title III Section 302 Extremely Hazardous Substances network are identified under this section	ulation. ulation. NFORMATIC ous based on co	omponent		pt from the	
CAO/IATA : Refer to specific regund MO/IMDG (maritime) : Refer to specific regund 15. REGULATORY IN S Regulations: OSHA Status : Classified as hazardo TSCA Status : All components of the TSCA Inventory. S. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65 ARA Title III Section 302 Extremely Hazardous Substances	ulation. ulation. NFORMATIC ous based on co	omponent		pt from the	
MO/IMDG (maritime) : Refer to specific regu 15. REGULATORY IN S Regulations: OSHA Status : Classified as hazardo TSCA Status : All components of th TSCA Status : All components of th TSCA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65 ARA Title III Section 302 Extremely Hazardous Substances	ulation. IFORMATIC pus based on c	omponent		pt from the	
15. REGULATORY IN S Regulations: OSHA Status : Classified as hazardo TSCA Status : All components of th TSCA Inventory. S. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65 ARA Title III Section 302 Extremely Hazardous Substances	FORMATIC bus based on c	omponent		pt from the	
S Regulations: OSHA Status : Classified as hazardo TSCA Status : All components of th TSCA Inventory. S. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65 ARA Title III Section 302 Extremely Hazardous Substan	ous based on c	omponent		pt from the	
OSHA Status : Classified as hazardo TSCA Status : All components of th TSCA Inventory. S. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65 ARA Title III Section 302 Extremely Hazardous Substances		-		pt from the	
TSCA Status : All components of th TSCA Inventory. S. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65		-		pt from the	
TSCA Inventory. S. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65	his product are	e listed on	or exem	pt from the	
not applicable California Proposition : Not applicable 65 ARA Title III Section 302 Extremely Hazardous Substan					
California Proposition : Not applicable 65 ARA Title III Section 302 Extremely Hazardous Substar					
65 ARA Title III Section 302 Extremely Hazardous Substan					
65 ARA Title III Section 302 Extremely Hazardous Substan					
nless specific chemicals are identified under this section	nce				
	, this product	is Not Apj	olicable	under this r	egulat
ARA Title III Section 313 Toxic Chemicals:					
nless specific chemicals are identified under this section	this product	is Not An	licable	under this r	oulat
Chemical Name	CAS-No		Weight		guiut
ZINC COMPOUNDS	68187-5	1-9	10.00 -	30.00	
anadian Regulations:					
National Pollutant Release Inventory (NPRI)					
	AS-No.	Weight percent		NPRI ID#]
Zinc ferrite brown spinel (C.I. Pigment Yellow681119)681	187-51-9	10.00 -			1

PolvOne

MATERIAL SAFETY DATA SHEET 11054 J D BROWN

Version Number 1.0 Revision Date 06/01/2012 Page 8 of 8 Print Date 8/26/2012

WHMIS Ingredient Disclosure List CAS-No. 1333-86-4 1309-37-1 7631-86-9 DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS : Listed China IECS : Listed Europe EINECS : Listed Japan ENCS Not determined : Korea KECI Listed : Philippines PICCS : Listed **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.