MATERIAL SAFETY DATA SHEET 149B SHALE N NG-02 EF

Version Number 1.0 Revision Date 06/26/2012

Page 1 of 8 Print Date 8/27/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	149B SHALE N NG-02 EF	
Product code	CC10165243	
Chemical Name	Mixture	
CAS-No.	Mixture	
Product Use	Industrial Applications	

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products	70624-18-9	1 - 5
2,4,8,10-Tetraoxa-3,9- diphosphaspiro[5.5]undecane, 3,9-bis[2,4- bis(1,1-dimethylethyl)phenoxy]-	26741-53-7	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Rutile, antimony chromium buff	68186-90-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:

: Inhalation, Ingestion, Skin contact

Acute exposure

PolyOne.

MATERIAL SAFETY DATA SHEET **149B SHALE N NG-02 EF**

sion Date 06/26/2012	Page 2 Print Date 8/27/2
Inhalation	: Resin particles, like other inert materials, can be mechanically
Ingestion	irritating. : May be harmful if swallowed.
Eyes	Resin particles, like other inert materials, are mechanically irritating to
2.) • 5	eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
T 1 1 4	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Autoignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
	Waar appropriate personal protection during cleanup, such as
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

PolyOne.

MATERIAL SAFETY DATA SHEET **149B SHALE N NG-02 EF**

Version Number 1.0 Revision Date 06/26/2012	Page 3 of 8 Print Date 8/27/2012
Methods for cleaning up	 be allowed to enter drains, water courses or the soil. Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

PolyOne

MATERIAL SAFETY DATA SHEET 149B SHALE N NG-02 EF

Version Number 1.0 Revision Date 06/26/2012 Page 4 of 8 Print Date *8/27/2012*

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony	0.5 mg/m3	Recommended exposure	as Cr	NIOSH
chromium buff		limit (REL):		
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid : pellets : GREY : very faint : Not determined : not applicable : insoluble

: Stable

Will not occur.

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

- : Not applicable : Not determined : Not established
- : not applicable not applicable
- : not applicable
- :
- **10. STABILITY AND REACTIVITY**
- Stability
 - :
- Hazardous Polymerization Conditions to avoid
 - : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

PolvOne

MATERIAL SAFETY DATA SHEET 149B SHALE N NG-02 EF

Version Number 1.0 Revision Date 06/26/2012 Page 5 of 8 Print Date 8/27/2012

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
70624-18-9	1,6-Hexanediamine, N,N'-	Irritant	Eyes, Skin, Respiratory
	bis(2,2,6,6-tetramethyl-4-		system.
	piperidinyl)-,polymer with		
	2,4,6-trichloro-1,3,5-		
	triazine, reaction products		
26741-53-7	2,4,8,10-Tetraoxa-3,9-	Toxic	Refer to LC50 / LD50 Data on
	diphosphaspiro[5.5]undeca		MSDS
	ne, 3,9-bis[2,4-bis(1,1-		
	dimethylethyl)phenoxy]-		
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
70624-18-9	1,6-Hexanediamine, N,N'-	Oral LD50	> 2,000 mg/kg	rat
	bis(2,2,6,6-tetramethyl-4-	Dermal LD50	> 3,000 mg/kg	rat
	piperidinyl)-,polymer with			
	2,4,6-trichloro-1,3,5-			
	triazine, reaction products			
26741-53-7	2,4,8,10-Tetraoxa-3,9-	LC50	> 2 gm/m3	rat
	diphosphaspiro[5.5]undeca	Oral LD50	5,580 mg/kg	rat
	ne, 3,9-bis[2,4-bis(1,1-	Dermal LD50	> 200 mg/kg	rabbit
	dimethylethyl)phenoxy]-			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 149B SHALE N NG-02 EF

Version Number 1.0 Revision Date 06/26/2012 Page 6 of 8 Print Date *8/27/2012*

IARC Carcinogen Classifications:1 - The component is carcinogenic to humans.2A - The component is probably carcinogenic to humans.2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION				
Persistence and degradability : Not readily biodegradable.				
Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.				
Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.				
Additional advice	: no data available			
	13. DISPOSAL CONSIDERATIONS			
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			
U.S. DOT Classification	: Not regulated for transportation.			
ICAO/IATA	: Refer to specific regulation.			
IMO/IMDG (maritime)	: Refer to specific regulation.			
	15. REGULATORY INFORMATION			
US Regulations:				
OSHA Status	: Classified as hazardous based on components.			
TSCA Status	: All components of this product are listed on or exempt from the			

TSCA Inventory.

PolvOne

MATERIAL SAFETY DATA SHEET 149B SHALE N NG-02 EF

Version Number 1.0 Revision Date 06/26/2012 Page 7 of 8 Print Date 8/27/2012

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent	
CHROMIUM III COMPOUNDSCHROMIUM III	68186-90-3	5.00 - 10.00	
COMPOUNDSANTIMONY			
COMPOUNDSCHROMIUM COMPOUNDS			

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Rutile, antimony chromium buff	68186-90-3	5.00 - 10.00	

WHMIS Classification : D1B

WHMIS Ingredient Disclosure List

CAS-No.	
68186-90-3	
7631-86-9	

:

: Listed

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS

7/8

PolyOne

MATERIAL SAFETY DATA SHEET 149B SHALE N NG-02 EF

Version Number 1.0 Revision Date 06/26/2012 Page 8 of 8 Print Date 8/27/2012

China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.