PolvOne

### MATERIAL SAFETY DATA SHEET BROWN SIDE SHIELD

Version Number 1.0 Revision Date 07/23/2012

Page 1 of 8 Print Date 8/28/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BROWN SIDE SHIELD
Product code	:	CC10166719
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	0.1 - 1
Carbon black	1333-86-4	1 - 5
Iron oxide	1309-37-1	10 - 30
Rutile, antimony chromium buff	68186-90-3	10 - 30

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

# MATERIAL SAFETY DATA SHEET **BROWN SIDE SHIELD**

Version Number 1.0 Revision Date 07/23/2012 Page 2 of 8 Print Date 8/28/2012

Medical Conditions	:	None known.
Aggravated by Exposure:		
		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits		
Upper explosion limit	:	not applicable
Lower explosion limit	:	not applicable
Autoignition temperature Suitable extinguishing media	•	not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Suitable extinguishing media	•	Carbon dioxide blanker, water spray, Dry powder, Poani.
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures		pressure mode should be worn to prevent inhalation of airborne
		contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

PolyOne.

# MATERIAL SAFETY DATA SHEET **BROWN SIDE SHIELD**

Version Number 1.0 Revision Date 07/23/2012 Page 3 of 8 Print Date 8/28/2012

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

<u>PolyOne</u>

### MATERIAL SAFETY DATA SHEET BROWN SIDE SHIELD

Version Number 1.0 Revision Date 07/23/2012 Page 4 of 8 Print Date 8/28/2012

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour : solid: pellets: BROWN: very faint

Evaporation rate Specific Gravity Bulk density Vapour pressure Not applicableNot determinedNot establishednot applicable

# <u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET BROWN SIDE SHIELD

POLYONE CORPORATION

Version Number 1.0 Revision Date 07/23/2012

]	Boiling Point: :	no	ot determined t applicable soluble	Vapour density pH	:	not applicable not applicable
		10	. STABILITY AND RE	ACTIVITY		
S	Stability	:	Stable			
]	Hazardous Polymerization	:	Will not occur.			
(	Conditions to avoid	:	Keep away from oxidizit decomposition, do not o		ne.	To avoid thermal
]	Incompatible Materials	:	Incompatible with strong	g acids and oxidizing ag	ent	s.
	Hazardous decomposition products	:	Carbon dioxide (CO2), c (NOx), other hazardous			U

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

Page 5 of 8 Print Date 8/28/2012

### MATERIAL SAFETY DATA SHEET BROWN SIDE SHIELD

Version Number 1.0 Revision Date 07/23/2012

Page 6 of 8 Print Date 8/28/2012

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	<ul> <li>Like most thermoplastic plastics the product can be recycled. When possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> <li>Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification,</li> </ul>
	transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
	: Refer to specific regulation.

PolyOne.

# MATERIAL SAFETY DATA SHEET **BROWN SIDE SHIELD**

Version Number 1.0 Revision Date 07/23/2012 Page 7 of 8 Print Date 8/28/2012

IMO/IMDG (maritime)	:	Refer to specific	e regulati	on.				
	15	5. REGULATOR	Y INFO	RMATIO	N			
US Regulations:								
OSHA Status	:	Classified as ha	zardous t	based on co	mponen	ts.		
TSCA Status	:	All components TSCA Inventory		broduct are	listed or	n or exem	npt from t	he
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 3	302)					
not applicable								
California Proposition 65	:	Not applicable						
Unless specific chemicals are is	denti	ified under this se	- 4 <sup>1</sup> 41- 1					
SARA Title III Section 313 To			cuon, tni	s product 1s	s Not Ap	plicable	under thi	s regulatio
SARA Title III Section 313 To Unless specific chemicals are in	oxic (	Chemicals:		s product is	s Not Ap	oplicable	under thi	-
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name	oxic ( denti	Chemicals:	ction, thi	s product is	s Not Ap	pplicable Weight	under thi percent	-
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOUN COMPOUNDSANTIMONY	oxic ( denti NDS	Chemicals: ified under this se CHROMIUM III	ction, thi	s product is	s Not Ap	plicable	under thi percent	-
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOU	oxic ( denti NDS	Chemicals: ified under this se CHROMIUM III	ction, thi	s product is	s Not Ap	pplicable Weight	under thi percent	-
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOUN COMPOUNDSANTIMONY	oxic ( denti NDS	Chemicals: ified under this se CHROMIUM III	ction, thi	s product is	s Not Ap	pplicable Weight	under thi percent	-
SARA Title III Section 313 To Unless specific chemicals are id Chemical Name CHROMIUM III COMPOUN COMPOUNDSANTIMONY COMPOUNDSCHROMIUM Canadian Regulations:	oxic ( denti NDS 4 4 CC	Chemicals: ified under this se CHROMIUM III OMPOUNDS	ction, thi	s product is	s Not Ap	pplicable Weight	under thi percent	-
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOU COMPOUNDSANTIMONY COMPOUNDSCHROMIUM	oxic ( denti NDS 4 4 CC	Chemicals: ified under this se CHROMIUM III OMPOUNDS	ction, thi	s product is CAS-No. 68186-90-	s Not Ap -3 Weigh	plicable Weight 10.00 -	under thi percent	s regulatio
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOUN COMPOUNDSANTIMONY COMPOUNDSCHROMIUM Canadian Regulations: National Pollutant Relea	nxic ( denti NDS MCC	Chemicals: ified under this se CHROMIUM III OMPOUNDS	ction, thi	s product is CAS-No. 68186-90-	s Not Ap -3 Weigh percen	plicable Weight 10.00 -	under thi percent 30.00	s regulatio
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOUN COMPOUNDSANTIMONY COMPOUNDSCHROMIUM Canadian Regulations: National Pollutant Relea Chemical Name	nxic ( denti NDS MCC	Chemicals: ified under this se CHROMIUM III OMPOUNDS	CAS-N	s product is CAS-No. 68186-90-	s Not Ap -3 Weigh percen	plicable Weight 10.00 - t t	under thi percent 30.00	s regulatio
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOUN COMPOUNDSANTIMONY COMPOUNDSCHROMIUM Canadian Regulations: National Pollutant Relea Chemical Name	oxic C denti NDS 7 M CC ase Ii	Chemicals: ified under this se CHROMIUM III OMPOUNDS	CAS-N	s product is CAS-No. 68186-90-	s Not Ap -3 Weigh percen	plicable Weight 10.00 - t t	under thi percent 30.00	s regulatio
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOUN COMPOUNDSANTIMONY COMPOUNDSCHROMIUM Canadian Regulations: National Pollutant Relea Chemical Name Rutile, antimony chromium I	oxic ( denti NDS M CC ase In buff	Chemicals: ified under this set CHROMIUM III OMPOUNDS	CAS-N	s product is CAS-No. 68186-90-	s Not Ap -3 Weigh percen	plicable Weight 10.00 - t t	under thi percent 30.00	s regulatio
SARA Title III Section 313 To Unless specific chemicals are in Chemical Name CHROMIUM III COMPOUN COMPOUNDSANTIMONY COMPOUNDSCHROMIUM Canadian Regulations: National Pollutant Relea Chemical Name Rutile, antimony chromium I WHMIS Classification	oxic ( denti NDS M CC ase In buff	Chemicals: ified under this set CHROMIUM III OMPOUNDS	CAS-N	s product is CAS-No. 68186-90-	s Not Ap -3 Weigh percen	plicable Weight 10.00 - t t	under thi percent 30.00	s regulatio

PolyOne.

## MATERIAL SAFETY DATA SHEET BROWN SIDE SHIELD

Version Number 1.0 Revision Date 07/23/2012

\_

Page 8 of 8 Print Date 8/28/2012

1333-86-4 1309-37-1 68186-90-3		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed
16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.