

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****GOLDEN YELLOW P123C UV SS**Version Number 1.0
Revision Date 07/25/2012Page 1 of 8
Print Date 8/28/2012**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
33587 Walker Road, Avon Lake, OH 44012Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**Product name : GOLDEN YELLOW P123C UV SS
Product code : CC10166845
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

| Components | CAS-No. | Weight percent |
|---|------------|----------------|
| 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products | 70624-18-9 | 1 - 5 |
| Molybdate orange (Lead chromate pigment) | 12656-85-8 | 0.1 - 1 |
| Chrome yellow (Lead chromate pigment) | 1344-37-2 | 10 - 30 |
| Titanium dioxide | 13463-67-7 | 10 - 30 |

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Ingestion, Skin contact**Acute exposure**Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
Ingestion : May be harmful if swallowed.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

GOLDEN YELLOW P123C UV SS

Version Number 1.0
Revision Date 07/25/2012

Page 2 of 8
Print Date 8/28/2012

Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : not applicable
Flammable Limits :
 Upper explosion limit : not applicable
 Lower explosion limit : not applicable
Autoignition temperature : not applicable
Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

GOLDEN YELLOW P123C UV SS

Version Number 1.0
Revision Date 07/25/2012

Page 3 of 8
Print Date 8/28/2012

plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

GOLDEN YELLOW P123C UV SS

Version Number 1.0
Revision Date 07/25/2012

Page 4 of 8
Print Date 8/28/2012

| Components | Value | Exposure time | Exposure type | List: | |
|---------------------------------------|--|-----------------------------------|-----------------------------------|-------------|---------|
| Chrome yellow (Lead chromate pigment) | 0.005 mg/m3 | Time Weighted Average (TWA): | | OSHA | |
| | 0.0025 mg/m3 | OSHA Action level: | | OSHA | |
| | 0.05 mg/m3 | Time Weighted Average (TWA): | as Pb | ACGIH | |
| | 0.05 mg/m3 | Time Weighted Average (TWA): | | OSHA | |
| | 0.03 mg/m3 | OSHA Action level: | | OSHA | |
| | 0.05 mg/m3 | Time Weighted Average (TWA): | as Pb | OSHA Z1A | |
| | 0.15 mg/m3 | Time Weighted Average (TWA): | Dust and fume. as Pb | MX OEL | |
| | Molybdate orange (Lead chromate pigment) | 0.5 mg/m3 | Recommended exposure limit (REL): | as Cr | NIOSH |
| | | 0.5 mg/m3 | PEL: | as Cr | OSHA Z1 |
| | 0.005 mg/m3 | Time Weighted Average (TWA): | | OSHA | |
| | 0.0025 mg/m3 | OSHA Action level: | | OSHA | |
| | 0.05 mg/m3 | Time Weighted Average (TWA): | as Pb | ACGIH | |
| | 0.05 mg/m3 | Time Weighted Average (TWA): | | OSHA | |
| | 0.03 mg/m3 | OSHA Action level: | | OSHA | |
| | 0.05 mg/m3 | Time Weighted Average (TWA): | as Pb | OSHA Z1A | |
| | 0.15 mg/m3 | Time Weighted Average (TWA): | Dust and fume. as Pb | MX OEL | |
| | Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | ACGIH | |
| | | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A | |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL | |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL | |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------|--------------|------------------|-------------------|
| Form | : solid | Evaporation rate | : Not applicable |
| Appearance | : pellets | Specific Gravity | : Not determined |
| Colour | : YELLOW | Bulk density | : Not established |
| Odour | : very faint | Vapour pressure | : not applicable |

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

GOLDEN YELLOW P123C UV SS

Version Number 1.0

Revision Date 07/25/2012

Page 5 of 8

Print Date 8/28/2012

Melting point/range : Not determined Vapour density : not applicable
 Boiling Point: : not applicable pH : not applicable
 Water solubility : insoluble

10. STABILITY AND REACTIVITY

Stability : Stable
 Hazardous Polymerization : Will not occur.
 Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
 Incompatible Materials : Incompatible with strong acids and oxidizing agents.
 Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|---|------------------|--|
| 70624-18-9 | 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products | Irritant | Eyes, Skin, Respiratory system. |
| 12656-85-8 | Molybdate orange (Lead chromate pigment) | Irritant | Eyes, Skin. |
| | | Systemic effects | central nervous system (CNS), reproductive system. |
| 1344-37-2 | Chrome yellow (Lead chromate pigment) | Systemic effects | central nervous system (CNS), reproductive system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|------------|---|--------------------------|--------------------------------|------------|
| 70624-18-9 | 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-,polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products | Oral LD50 Dermal LD50 | > 2,000 mg/kg > 3,000 mg/kg | rat rat |

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

GOLDEN YELLOW P123C UV SS

Version Number 1.0
Revision Date 07/25/2012

Page 6 of 8
Print Date 8/28/2012

| | | | | |
|------------|--|-----------|-------------|-----|
| 12656-85-8 | Molybdate orange (Lead chromate pigment) | Oral LD50 | 5,000 mg/kg | rat |
|------------|--|-----------|-------------|-----|

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|--|------|------|-----|
| 12656-85-8 | Molybdate orange (Lead chromate pigment) | yes | 1 | no |
| 1344-37-2 | Chrome yellow (Lead chromate pigment) | yes | 1 | no |
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Molybdate orange (Lead chromate pigment) 12656-85-8 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

Additional Health Hazard Information:

Chrome yellow (Lead chromate pigment) 1344-37-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.
- Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.
- Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

- Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

GOLDEN YELLOW P123C UV SS

Version Number 1.0
Revision Date 07/25/2012

Page 7 of 8
Print Date 8/28/2012

classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.
ICAO/IATA : Refer to specific regulation.
IMO/IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)
not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name | CAS-No. | Weight percent |
|---------------|---------|----------------|
|---------------|---------|----------------|

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

GOLDEN YELLOW P123C UV SS

Version Number 1.0
 Revision Date 07/25/2012

Page 8 of 8
 Print Date 8/28/2012

| Chemical Name | CAS-No. | Weight percent |
|---|------------|----------------|
| CHROMIUM VI COMPOUNDS CHROMIUM VI COMPOUNDS CHROMIUM COMPOUNDS LEAD COMPOUNDS, INORGANIC | 1344-37-2 | 10.00 - 30.00 |
| CHROMIUM III COMPOUNDS CHROMIUM III COMPOUNDS LEAD COMPOUNDS | 12656-85-8 | 0.10 - 1.00 |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight percent | NPRI ID# |
|--|------------|----------------|----------|
| Chrome yellow (Lead chromate pigment) | 1344-37-2 | 10.00 - 30.00 | |
| Molybdate orange (Lead chromate pigment) | 12656-85-8 | 0.10 - 1.00 | |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| |
|------------|
| CAS-No. |
| 1344-37-2 |
| 12656-85-8 |

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

- Australia AICS : Listed
- China IECS : Listed
- Europe EINECS : Listed
- Japan ENCS : Not determined
- Korea KECI : Not determined
- Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.