PolyOne

## MATERIAL SAFETY DATA SHEET **DEER HIDE 3**

Version Number 1.0 Revision Date 07/31/2012 Page 1 of 7 Print Date 8/28/2012

POLYONE CORPORATI 33587 Walker Road, Avor		OH 44012
Felephone E <b>mergency telephone</b>	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DEER HIDE 3
Product code	:	CC10167054
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

Components	CAS-No.	Weight percent
Formamide, N,N'-1,6-hexanediylbis[N-	124172-53-8	1 - 5
(2,2,6,6-tetramethyl-4-piperidinyl)-		
Titanium dioxide	13463-67-7	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

# MATERIAL SAFETY DATA SHEET **DEER HIDE 3**

Version Number 1.0 Revision Date 07/31/2012 Page 2 of 7 Print Date 8/28/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



## MATERIAL SAFETY DATA SHEET **DEER HIDE 3**

sion Number 1.0 vision Date 07/31/2012			Print	Page 3 t Date 8/28/2	
Handling		ake measures to prevent the bunch in areas with appropriate experiences.		charge. Heat	
Storage		: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8.	EXPOSURE	CONTROLS/PERSONAL I	PROTECTION		
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shields			
Hand protection	: P	Protective gloves			
Skin and body protection	: L	Long sleeved clothing			
Additional Protective Measures	: S	Safety shoes			
General Hygiene Considerations		andle in accordance with good ractice. Wash hands before bro			
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		. Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A	
	10	Time Weighted Assesses	•• <b>T</b> :	MV OFI	

-	(TWA):		
10 mg/m3	Time Weighted Average	as Ti	MX OEL
	(TWA):		
20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
-	(STEL):		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
  pellets
  TAN
  very faint
  Not determined
  not applicable
  insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  not applicable
  not applicable
  not applicable

### **10. STABILITY AND REACTIVITY**

**POLYONE CORPORATION** 



## MATERIAL SAFETY DATA SHEET **DEER HIDE 3**

Version Number 1.0 Revision Date 07/31/2012

Page 4 of 7 Print Date 8/28/2012

Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
124172-53-8	Formamide, N,N'-1,6-	Irritant	Eyes.
	hexanediylbis[N-(2,2,6,6-		
	tetramethyl-4-piperidinyl)-		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
124172-53-8	Formamide, N,N'-1,6- hexanediylbis[N-(2,2,6,6- tetramethyl-4-piperidinyl)-	LC50 Oral LD50	> 5.0 mg/l > 2,000 mg/kg	rat rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne.

# MATERIAL SAFETY DATA SHEET **DEER HIDE 3**

Version Number 1.0 Revision Date 07/31/2012 Page 5 of 7 Print Date 8/28/2012

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	<ul> <li>Chemicals are not readily available as they are bound within the polymer matrix.</li> </ul>
Bioaccumulation Potential	<ul> <li>Chemicals are not readily available as they are bound within the polymer matrix.</li> </ul>
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	

PolyOne.

## MATERIAL SAFETY DATA SHEET **DEER HIDE 3**

Version Number 1.0 Revision Date 07/31/2012 Page 6 of 7 Print Date 8/28/2012

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulationChemical NameCAS-No.Weight percentZINC COMPOUNDS68187-51-91.00 - 5.00

Canadian Regulations:

Chemical Name		CAS-No.	Weight percent	NPRI ID#
Zinc ferrite brown spinel (C.I. Pigment Yellow 119)		68187-51-9	1.00 - 5.00	
WHMIS Classification	: D2A			
DSL	Inventories or a product is on the	are exempt. Howe	oduct are listed on ver, at least one co Domestic Substan- ted by regulations.	omponent of th ces List (NDS
ational Inventories:				
Australia AICS	: Not determined	1		
China IECS	: Not determined	1		
Europe EINECS	: Listed			
Japan ENCS	: Not determined	1		
Korea KECI	: Not determined	1		
Philippines PICCS	: Not determined	1		
	16. OTHER I	NFORMATION		

PolyOne

## MATERIAL SAFETY DATA SHEET **DEER HIDE 3**

Version Number 1.0 Revision Date 07/31/2012

Page 7 of 7 Print Date 8/28/2012

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.