PolvOne

MATERIAL SAFETY DATA SHEET LT PURPLE 265C

Version Number 1.1 Revision Date 08/30/2012

Page 1 of 7 Print Date 8/31/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	LT PURPLE 265C
Product code :	CC10168734
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Talc	14807-96-6	0.1 - 1
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET *LT PURPLE 265C*

Version Number 1.1 Revision Date 08/30/2012 Page 2 of 7 Print Date 8/31/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET LT PURPLE 265C

Version Number 1.1 Revision Date 08/30/2012	Page 3 of 7 Print Date <i>8/31/2012</i>
Handling	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOS	URE CONTROLS/PERSONAL PROTECTION
Respiratory protection	No personal respiratory protective equipment normally required.
Eye/Face Protection	Safety glasses with side-shields
Hand protection	Protective gloves
Skin and body protection	Long sleeved clothing
Additional Protective Measures	Safety shoes
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET *LT PURPLE 265C*

Version Number 1.1 Revision Date 08/30/2012 Page 4 of 7 Print Date 8/31/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Talc	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	2 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	2 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : pellets
 : PURPLE
 : very faint
 : Not determined
 : not applicable
 : insoluble

: solid

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
not applicable
not applicable
not applicable

ccur.
r from oxidizing agents and open flame. To avoid thermal tion, do not overheat.
ble with strong acids and oxidizing agents.

PolvOne

MATERIAL SAFETY DATA SHEET LT PURPLE 265C

Version Number 1.1 Revision Date 08/30/2012

Page 5 of 7 Print Date 8/31/2012

products

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system,
			Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14807-96-6	Talc	no	2B	no
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	Not readily biodegradable.	
Environmental Toxicity	Chemicals are not readily available as they are bound within the polymer matrix.	
Bioaccumulation Potential	Chemicals are not readily available as they are bound within the polymer matrix.	
Additional advice	no data available	
	13. DISPOSAL CONSIDERATIONS	
Product	Like most thermoplastic plastics the product can be recycled. Where	



MATERIAL SAFETY DATA SHEET LT PURPLE 265C

sion Number 1.1 ision Date 08/30/2012	Page 6 Print Date 8/31/20
Contaminated packaging	 possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Propositior 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulat
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulat
Unless specific chemicals are	

PolyOne

MATERIAL SAFETY DATA SHEET *LT PURPLE 265C*

Version Number 1.1 Revision Date 08/30/2012 Page 7 of 7 Print Date 8/31/2012

National Pollutant Relea	se Iı	nventory (NPRI)	
not applicable			
WHMIS Classification	:	D2A	
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Not determined	
China IECS	:	Not determined	
Europe EINECS	:	Not determined	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	
		16. OTHER INFORMATION	t

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.