## MATERIAL SAFETY DATA SHEET **DK ARMORY BLUE 4LY**

Version Number 1.0 Revision Date 10/10/2012

Page 1 of 6 Print Date 10/10/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DK ARMORY BLUE 4LY
Product code	:	CC10170433
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Barium sulfate	7727-43-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact				
Acute exposure					
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.				
Ingestion	: May be harmful if swallowed.				
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.				
Skin	: Experience shows no unusual dermatitis hazard from routine handling.				
Chronic exposure	: Refer to Section 11 for Toxicological Information.				

PolyOne.

# MATERIAL SAFETY DATA SHEET **DK ARMORY BLUE 4LY**

Version Number 1.0 Revision Date 10/10/2012 Page 2 of 6 Print Date 10/10/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne

## MATERIAL SAFETY DATA SHEET **DK ARMORY BLUE 4LY**

Version Number 1.0 Revision Date 10/10/2012 Page 3 of 6 Print Date 10/10/2012

Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.		
8. EXI	OSUI	RE CONTROLS/PERSONAL PROTECTION		
Respiratory protection	:	No personal respiratory protective equipment normally required.		
Eye/Face Protection	:	Safety glasses with side-shields		
Hand protection	:	Protective gloves		
Skin and body protection	:	Long sleeved clothing		
Additional Protective Measures	:	Safety shoes		
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.		
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Barium sulfate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
5 mg/m3		Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid
  : pellets
  : BLUE
  : very faint
  : Not determined
  : not applicable
  : insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  not applicable
  not applicable
  not applicable

#### **10. STABILITY AND REACTIVITY**

PolyOne

## MATERIAL SAFETY DATA SHEET **DK ARMORY BLUE 4LY**

Version Number 1.0 Revision Date 10/10/2012 Page 4 of 6 Print Date 10/10/2012

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ		
7727-43-7	Barium sulfate	Irritant	Respiratory system.		
		Systemic effects	Eyes, Respiratory system.		

	12	2. ECOLOGICAL INFORMATION	T
Persistence and degradability	:	Not readily biodegradable.	
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.	
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.	
Additional advice	:	no data available	
			T
	1	3. DISPOSAL CONSIDERATIONS	l
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	

PolyOne.

# MATERIAL SAFETY DATA SHEET **DK ARMORY BLUE 4LY**

Version Number 1.0 Revision Date 10/10/2012 Page 5 of 6 Print Date 10/10/2012

U.S. DOT Classification		Not regulated fo	r transpo	ortation.			
	•	-	-				
ICAO/IATA	:	Refer to specific	regulati	on.			
MO/IMDG (maritime)	:	Refer to specific	regulati	on.			
	15.	REGULATOR	Y INFO	RMATIC	DN		
US Regulations:							
OSHA Status	:	Classified as haz	zardous b	based on c	omponen	ts.	
TSCA Status	:	All components TSCA Inventory		broduct are	e listed or	n or exe	mpt from the
US. EPA CERCLA Hazardo	us Subs	tances (40 CFR 3	302)				
not applicable							
California Propositio 65		Not applicable					
SARA Title III Section 302	Extreme	ly Hazardous Su	bstance				
Unless specific chemicals are	e identif	ied under this see	ction, thi	s product	is Not Ap	plicable	e under this regu
SARA Title III Section 313	Towio C	homicala					
Unless specific chemicals are Chemical Name	e identif	ied under this se	ction, thi	s product		<u>^</u>	e under this regu t percent
ZINC COMPOUNDS				1314-98-		1.00 -	5.00
Canadian Regulations:							
	lease In	ventory (NPRI)	1				
National Pollutant Re			CAS-N	lo.	Weigh percen		NPRI ID#
National Pollutant Re Chemical Name						ı	
			147-14 1314-9		0.10 -		

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET **DK ARMORY BLUE 4LY**

Version Number 1.0 Revision Date 10/10/2012 Page 6 of 6 Print Date 10/10/2012

WHMIS Classificati	on :	Not controlled.	
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Listed	
China IECS	:	Listed	
Europe EINECS	:	Listed	
Japan ENCS	:	Listed	
Korea KECI	:	Listed	
Philippines PICCS	:	Listed	
		16. OTHER INFORMATION	╉

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.