PolyOne

MATERIAL SAFETY DATA SHEET 695400 BROWN

Version Number 1.0 Revision Date 10/19/2012

Page 1 of 7 Print Date 10/19/2012

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012					
Felephone E mergency telephone n umber	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	695400 BROWN			
Product code	:	CC10170825			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

Components	CAS-No.	Weight percent
Styrene	100-42-5	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET 695400 BROWN

Version Number 1.0 Revision Date 10/19/2012 Page 2 of 7 Print Date 10/19/2012

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET 695400 BROWN

Version Number 1.0 Revision Date 10/19/2012

Page 3 of 7 Print Date 10/19/2012

Storage	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.				
8. EX	8. EXPOSURE CONTROLS/PERSONAL PROTECTION				
Respiratory protection	: No personal respiratory protective equipment normally required.				
Eye/Face Protection	: Safety glasses with side-shields				
Hand protection	: Protective gloves				
Skin and body protection	: Long sleeved clothing				
Additional Protective Measures	: Safety shoes				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Styrene	20 ppm	Time Weighted Average (TWA):		ACGIH
	40 ppm	Short Term Exposure Limit (STEL):		ACGIH
	50 ppm 215 mg/m3	Recommended exposure limit (REL):		NIOSH
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		NIOSH
	100 ppm	Time Weighted Average (TWA):		OSHA Z2
	200 ppm	Ceiling Limit Value:		OSHA Z2
	600 ppm	Maximum concentration:		OSHA Z2
	50 ppm 215 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	50 ppm 215 mg/m3	Time Weighted Average (TWA):		MX OEL
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Evaporation rate

: Not applicable

4/7

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET 695400 BROWN

Version Number 1.0 Revision Date 10/19/2012

Appearance

Colour

Odour Melting point/range Boiling Point: Water solubility	: N : no	ery faint ot determined ot applicable isoluble	Vapour pressure Vapour density pH	:	not applicable not applicable not applicable
	1	0. STABILITY AN	D REACTIVITY		
Stability	:	The product is stat	ble if stored and handled as	presc	cribed.
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from o decomposition, do	xidizing agents and open fl not overheat.	lame.	To avoid thermal
T		×			

: pellets

: BROWN

Incompatible Materials: Incompatible with strong acids and oxidizing agents.Hazardous decomposition
products: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ	
100-42-5	Styrene	Irritant	Eyes, Respiratory system.	
		Systemic effects	Eyes, Skin, Respiratory	
			system, Liver, central nervous	
			system (CNS).	

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
100-42-5	Styrene	LC50	12 gm/m3	rat
		Oral LD50	2,650 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
100-42-5	Styrene	no	2B	no

IARC Carcinogen Classifications:



:

:

Specific Gravity

Bulk density

Page 4 of 7 Print Date 10/19/2012

Not determined

Not established

PolyOne

MATERIAL SAFETY DATA SHEET 695400 BROWN

Version Number 1.0 Revision Date 10/19/2012 Page 5 of 7 Print Date 10/19/2012

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Styrene 100-42-5 Irritating to eyes, skin, and respiratory tract with many CNS effects such as narcosis, cramps and respiratory tract paralysis.

Persistence and degradability : Not readily biodegradable.			
: Chemicals are not readily available as they are bound within the polymer matrix.			
: Chemicals are not readily available as they are bound within the polymer matrix.			
: no data available			
13. DISPOSAL CONSIDERATIONS			
: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
14. TRANSPORT INFORMATION			
: Not regulated for transportation.			
: Refer to specific regulation.			
: Refer to specific regulation.			
15. REGULATORY INFORMATION			
OSHA Status : Classified as hazardous based on components.			

MATERIAL SAFETY DATA SHEET 695400 BROWN

Version Number 1.0 Revision Date 10/19/2012 Page 6 of 7 Print Date 10/19/2012

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Chemical Name CAS-No. Weight percent

	CAS-NO.	weight percent
STYRENESTYRENE	100-42-5	0.10 - 1.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Styrene	100-42-5	0.10 - 1.00	

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
100-42-5

:

: Listed

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS



MATERIAL SAFETY DATA SHEET 695400 BROWN

Version Number 1.0 Revision Date 10/19/2012

Page 7 of 7 Print Date 10/19/2012

China IECS:ListedEurope EINECS:ListedJapan ENCS:ListedKorea KECI:ListedPhilippines PICCS:Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.