PolvOne.

MATERIAL SAFETY DATA SHEET SILVER METALLIC

Version Number 1.0 Revision Date 10/17/2012

Page 1 of 8 Print Date 10/17/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SILVER METALLIC
Product code	:	CC10171022
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Rutile (TiO2)	1317-80-2	1 - 5
Aluminum	7429-90-5	5 - 10
Mica	12001-26-2	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET SILVER METALLIC

Version Number 1.0 Revision Date 10/17/2012 Page 2 of 8 Print Date 10/17/2012

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures Unusual Fire/Explosion Hazards	 pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET SILVER METALLIC

/ersion Number 1.0 Revision Date 10/17/2012		Page 3 of 8 Print Date 10/17/2012	
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	
Storage	:	 Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. 	
8. EXI	POSUI	RE CONTROLS/PERSONAL PROTECTION	
Respiratory protection	:	No personal respiratory protective equipment normally required.	
Eye/Face Protection	:	Safety glasses with side-shields	
Hand protection	:	Protective gloves	
Skin and body protection	:	Long sleeved clothing	
Additional Protective Measures	:	Safety shoes	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	
Exposure limit(s)			

PolyOne.

MATERIAL SAFETY DATA SHEET SILVER METALLIC

Version Number 1.0 Revision Date 10/17/2012 Page 4 of 8 Print Date 10/17/2012

Components	Value	Exposure time	Exposure type	List:
Aluminum	1 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Welding fume or pyrophoric powder. as Al	NIOSH
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	15 mg/m3	Time Weighted Average (TWA):	Total dust. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Respirable dust. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Fume. as Al	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Welding fume.	MX OEL
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder.	MX OEL
Mica	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	3 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	3 mg/m3	Time Weighted Average (TWA):		MX OEL
Rutile (TiO2)	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour

: solid : pellets : GREY

Bulk density

Evaporation rate: Not applicableSpecific Gravity: Not determinedDulls demaits: Not actablished : Not established

12. ECOLOGICAL INFORMATION

= 10	
5/8	

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET SILVER METALLIC

: very faint

: insoluble

:

:

·

:

:

: Not determined

Will not occur.

: not applicable

Version Number 1.0 Revision Date 10/17/2012

Melting point/range

Hazardous Polymerization

Conditions to avoid

Incompatible Materials

Hazardous decomposition

Boiling Point:

Water solubility

Odour

Stability

products

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing
health data for the individual components which comprise the mixture.

11. TOXICOLOGICAL INFORMATION

10. STABILITY AND REACTIVITY

decomposition, do not overheat.

Vapour pressure

Keep away from oxidizing agents and open flame. To avoid thermal

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

Vapour density

pН

The product is stable if stored and handled as prescribed.

Incompatible with strong acids and oxidizing agents.

Page 5 of 8

Print Date 10/17/2012

not applicable

not applicable

: not applicable

:

:

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory
			system.
12001-26-2	Mica	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1317-80-2	Rutile (TiO2)	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

MATERIAL SAFETY DATA SHEET SILVER METALLIC

Version Number 1.0 Page 6 of 8 Print Date 10/17/2012 Revision Date 10/17/2012 Persistence and degradability : Not readily biodegradable. Environmental Toxicity Chemicals are not readily available as they are bound within the : polymer matrix. **Bioaccumulation Potential** : Chemicals are not readily available as they are bound within the polymer matrix. Additional advice : no data available 13. DISPOSAL CONSIDERATIONS Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging Recycling is preferred when possible. The generator of waste : material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification : Not regulated for transportation. ICAO/IATA Refer to specific regulation. ÷ IMO/IMDG (maritime) Refer to specific regulation. ÷ **15. REGULATORY INFORMATION US Regulations: OSHA Status** : Classified as hazardous based on components. TSCA Status All components of this product are listed on or exempt from the : TSCA Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : WARNING! This product contains a chemical known to the State of 65 California to cause cancer.

MATERIAL SAFETY DATA SHEET SILVER METALLIC

Version Number 1.0 Revision Date 10/17/2012 Page 7 of 8 Print Date 10/17/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
ALUMINUM (FUME OR DUST)ALUMINUM (FUME	7429-90-5	5.00 - 10.00
OR DUST)		

Canadian Regulations:

 National Pollutant Release Inventory (NPRI)

 Chemical Name
 CAS-No.
 Weight percent

 Aluminum
 7429-90-5
 5.00 - 10.00

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
7429-90-5
12001-26-2

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET SILVER METALLIC

Version Number 1.0 Revision Date 10/17/2012 Page 8 of 8 Print Date *10/17/201*2

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.