PolyOne

MATERIAL SAFETY DATA SHEET GREEN NYLON

Version Number 1.0 Revision Date 11/13/2012 Page 1 of 6 Print Date 11/14/2012

POLYONE CORPORATI 33587 Walker Road, Avoi		OH 44012
Telephone E mergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREEN NYLON
Product code	:	CC10172402
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

Components	CAS-No.	Weight percent
Rutile, antimony chromium buff	68186-90-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **GREEN NYLON**

Version Number 1.0 Revision Date 11/13/2012 Page 2 of 6 Print Date 11/14/2012

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET GREEN NYLON

Version Number 1.0 Revision Date 11/13/2012

Page 3 of 6 Print Date 11/14/2012

orage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.		
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid
 : pellets
 : GREEN
 : very faint
 : Not determined
 : not applicable
 : insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable

10. STABILITY AND REACTIVITY



MATERIAL SAFETY DATA SHEET **GREEN NYLON**

Version Number 1.0 Revision Date 11/13/2012		Page 4 of 6 Print Date 11/14/2012
Stability	The product is stable if stored and handled as pre	scribed.
Hazardous Polymerization	Will not occur.	
Conditions to avoid	Keep away from oxidizing agents and open flame decomposition, do not overheat.	2. To avoid thermal
Incompatible Materials	Incompatible with strong acids and oxidizing age	nts.
Hazardous decomposition products	Carbon dioxide (CO2), carbon monoxide (CO), o (NOx), other hazardous materials, and smoke are	U U
	OXICOLOGICAL INFORMATION	

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	C	hemical Name	Effect	Target Organ		
68186-90-3 Rutile, antimony chromium buff		Irritant	Eyes, Skin, Respiratory system.			
		12. ECOLOGIC	AL INFORMATIO	DN		
Persistence and degrad	ability	: Not readily bio	odegradable.			
·			Chemicals are not readily available as they are bound within the polymer matrix.			
Bioaccumulation Potential		: Chemicals are not readily available as they are bound within the polymer matrix.				
Additional advice	: no data availal	no data available				
		13. DISPOSAL	CONSIDERATION	NS		
Product		possible recyc generator of w classification,	ling is preferred to c aste material has the transportation and d	ne product can be recycled. Where lisposal or incineration. The e responsibility for proper waste lisposal in accordance with and local regulations.		
mate		material has th transportation	e responsibility for	ble. The generator of waste proper waste classification, ordance with applicable federal,		

PolyOne.

MATERIAL SAFETY DATA SHEET **GREEN NYLON**

Version Number 1.0 Revision Date 11/13/2012 Page 5 of 6 Print Date 11/14/2012

		4. TRANSPOR						
U.S. DOT Classification	:	Not regulated f	or transpo	rtation.				
ICAO/IATA	:	Refer to specifi	c regulation	on.				
IMO/IMDG (maritime)	:	Refer to specifi	c regulation	on.				
	15	5. REGULATO	RY INFO	RMATION	N			
US Regulations:								
OSHA Status	:	Classified as ha	azardous b	based on con	mponen	ts.		
TSCA Status	:	All component TSCA Inventor		oroduct are	listed or	or exer	npt from the	
US. EPA CERCLA Hazardo	us Sub	stances (40 CFR	302)					
not applicable								
California Proposition	n :	Not applicable						
65								
SARA Title III Section 302 I	Extrem	ely Hazardous S	ubstance					
Unless specific chemicals are	e identi	fied under this se	ection, this	s product is	Not Ap	plicable	under this r	egula
CADA T'4. III C. (*	P	71						
SARA Title III Section 313								
Unless specific chemicals are			ection, this					egula
Unless specific chemicals are Chemical Name	e identi	ified under this se		CAS-No.		Weight	t percent	egula
Unless specific chemicals are	e identi UNDS	ified under this se					t percent	egula
Unless specific chemicals are Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMON COMPOUNDSCHROMIU	e identi UNDS VY	ified under this se		CAS-No. 68186-90-	3	Weight 5.00 -	t percent 10.00	egula
Unless specific chemicals are Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMON	e identi UNDS VY	ified under this se		CAS-No.	3	Weight	t percent 10.00	egula
Unless specific chemicals are Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMON COMPOUNDSCHROMIU	e identi UNDS VY	ified under this se		CAS-No. 68186-90-	3	Weight 5.00 -	t percent 10.00	egula
Unless specific chemicals are Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMON COMPOUNDSCHROMIU ZINC COMPOUNDS	e identi UNDS VY JM CC	ified under this searching of the search	I	CAS-No. 68186-90-	3	Weight 5.00 -	t percent 10.00	egula
Unless specific chemicals are Chemical Name CHROMIUM III COMPO COMPOUNDSANTIMON COMPOUNDSCHROMIU ZINC COMPOUNDS Canadian Regulations:	e identi UNDS VY JM CC	ified under this searching of the search	I	CAS-No. 68186-90- 1314-98-3	3	Weight 5.00 - 1.00 -	t percent 10.00	_

PolyOne

MATERIAL SAFETY DATA SHEET GREEN NYLON

Version Number 1.0 Revision Date 11/13/2012

Page 6 of 6 Print Date 11/14/2012

Rutile, antimony chromium buff	68186-90-3	5.00 - 10.00	
Zinc sulfide	1314-98-3	1.00 - 5.00	

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	-
147-14-8	
68186-90-3	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.