PolvOne

MATERIAL SAFETY DATA SHEET COASTAL CEDAR CONC 2

Version Number 1.0 Revision Date 11/13/2012

Page 1 of 8 Print Date 11/13/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	COASTAL CEDAR CONC 2
Product code	:	CC10172419
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

: Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Manganese antimony titanium brown rutile	68412-38-4	1 - 5
(C.I. Pigment Yellow 164)		
Calcium carbonate	1317-65-3	1 - 5
Iron oxide	1309-37-1	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the enduser (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.

PolyOne.

MATERIAL SAFETY DATA SHEET COASTAL CEDAR CONC 2

Version Number 1.0 Revision Date 11/13/2012 Page 2 of 8 Print Date 11/13/2012

	: Experience shows no unusual dermatitis hazard from routine handling		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIREFIGHTING MEASURES		
Flash point	: not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 		
Upper explosion limit Lower explosion limit Auto-ignition temperature	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne 		
Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive 		
Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen 		
Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 		
Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES Wear appropriate personal protection during cleanup, such as 		

PolyOne.

MATERIAL SAFETY DATA SHEET COASTAL CEDAR CONC 2

Version Number 1.0 Revision Date 11/13/2012 Page 3 of 8 Print Date 11/13/2012

and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS/PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection : Safety glasses with side-shields Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide	Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Respiratory protection: No personal respiratory protective equipment normally required.Eye/Face Protection: Safety glasses with side-shieldsHand protection: Protective glovesSkin and body protection: Long sleeved clothingAdditional Protective: Safety shoesMeasures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.Engineering measures: Heat only in areas with appropriate exhaust ventilation. Provide	Storage	:	
Eye/Face Protection:Safety glasses with side-shieldsHand protection:Protective glovesSkin and body protection:Long sleeved clothingAdditional Protective:Safety shoesMeasures:Safety shoesGeneral Hygiene:Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.Engineering measures:Heat only in areas with appropriate exhaust ventilation. Provide	8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Hand protection:Protective glovesSkin and body protection:Long sleeved clothingAdditional Protective:Safety shoesMeasures:Safety shoesGeneral Hygiene:Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.Engineering measures:Heat only in areas with appropriate exhaust ventilation. Provide	Respiratory protection	:	No personal respiratory protective equipment normally required.
Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide	Eye/Face Protection	:	Safety glasses with side-shields
Additional Protective : Safety shoes Measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide	Hand protection	:	Protective gloves
Measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide	Skin and body protection	:	Long sleeved clothing
Considerationspractice. Wash hands before breaks and at the end of workday.Engineering measures: Heat only in areas with appropriate exhaust ventilation. Provide		:	Safety shoes
		:	
	Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne.

MATERIAL SAFETY DATA SHEET COASTAL CEDAR CONC 2

Version Number 1.0 Revision Date 11/13/2012 Page 4 of 8 Print Date 11/13/2012

Components	Value	Exposure time	Exposure type	List:
Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164)	1 mg/m3	Recommended exposure limit (REL):	Fume. as Mn	NIOSH
,	3 mg/m3	Short Term Exposure Limit (STEL):	Fume. as Mn	NIOSH
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1
	5 mg/m3	Ceiling Limit Value:	as Mn	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: : solid
: pellets
: BROWN
: very faint
: Not determined
: not applicable

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
not applicable
not applicable
not applicable

MATERIAL SAFETY DATA SHEET COASTAL CEDAR CONC 2

Version Number 1.0 Revision Date 11/13/2012

Page 5 of 8 Print Date 11/13/2012

Water solubility : insoluble 10. STABILITY AND REACTIVITY				
	IV. STADILITT AND REACTIVITT			
Stability	: The product is stable if stored and handled as prescribed.			
Hazardous Polymerization	: Will not occur.			
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.			
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.			
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68412-38-4	Manganese antimony	Irritant	Eyes, Skin.
	titanium brown rutile (C.I.		
	Pigment Yellow 164)		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne.

MATERIAL SAFETY DATA SHEET COASTAL CEDAR CONC 2

Version Number 1.0 Revision Date 11/13/2012 Page 6 of 8 Print Date 11/13/2012

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	

PolvOne

MATERIAL SAFETY DATA SHEET COASTAL CEDAR CONC 2

Version Number 1.0 Revision Date 11/13/2012 Page 7 of 8 Print Date 11/13/2012

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
ZINC COMPOUNDS	68187-51-9	10.00 - 30.00
MANGANESE COMPOUNDSMANGANESE	68412-38-4	1.00 - 5.00
COMPOUNDSANTIMONY COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Zinc ferrite brown spinel (C.I. Pigment Yellow	68187-51-9	10.00 - 30.00	
119)			
Manganese antimony titanium brown rutile (C.I.	68412-38-4	1.00 - 5.00	
Pigment Yellow 164)			
		1.00 - 5.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
68412-38-4	
1309-37-1	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed



MATERIAL SAFETY DATA SHEET COASTAL CEDAR CONC 2

Version Number 1.0 Revision Date 11/13/2012 Page 8 of 8 Print Date 11/13/2012

Japan ENCS	: Not determined	
Korea KECI	: Listed	
Philippines PICCS	: Listed	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.