

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****NAT CAPSTOCK CONC RG**Version Number 1.0
Revision Date 12/04/2012Page 1 of 9
Print Date 12/5/2012**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
33587 Walker Road, Avon Lake, OH 44012

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure number or accident).**

Product name : NAT CAPSTOCK CONC RG
Product code : CC10173544
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Talc	14807-96-6	0.1 - 1
Calcium oxide	1305-78-8	1 - 5
Quartz	14808-60-7	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Silica, amorphous, precipitated and gel	112926-00-8	5 - 10
Silica, cristobalite	14464-46-1	10 - 30
Silica, amorphous, diatomaceous earth	68855-54-9	30 - 60

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Ingestion, Skin contact**Acute exposure**

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
Ingestion : May be harmful if swallowed.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

NAT CAPSTOCK CONC RG

Version Number 1.0
Revision Date 12/04/2012

Page 2 of 9
Print Date 12/5/2012

Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIREFIGHTING MEASURES

Flash point : not applicable
Flammable Limits :
Upper explosion limit : not applicable
Lower explosion limit : not applicable
Auto-ignition temperature : not applicable
Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

NAT CAPSTOCK CONC RG

Version Number 1.0
Revision Date 12/04/2012

Page 3 of 9
Print Date 12/5/2012

plastic, cardboard or metal containers for disposal.

7. HANDLING AND STORAGE

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

NAT CAPSTOCK CONC RG

Version Number 1.0
Revision Date 12/04/2012

Page 4 of 9
Print Date 12/5/2012

Components	Value	Exposure time	Exposure type	List:
Calcium oxide	2 mg/m3	Time Weighted Average (TWA):		ACGIH
	2 mg/m3	Recommended exposure limit (REL):		NIOSH
	5 mg/m3	PEL:		OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	2 mg/m3	Time Weighted Average (TWA):		MX OEL
Quartz	0.025 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	0.05 mg/m3	Recommended exposure limit (REL):	Respirable dust.	NIOSH
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3
	0.1 mg/m3	Time Weighted Average (TWA):		MX OEL
Silica, amorphous, diatomaceous earth	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Silica, amorphous, precipitated and gel	6 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Silica, cristobalite	0.025 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	0.05 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.05 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.15 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3
	0.05 mg/m3	Time Weighted Average (TWA):		MX OEL
Talc	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	2 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

NAT CAPSTOCK CONC RG

Version Number 1.0

Revision Date 12/04/2012

Page 5 of 9

Print Date 12/5/2012

	2 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3
Xylenes (o-, m-, p-isomers)	100 ppm	Time Weighted Average (TWA):		ACGIH
	150 ppm	Short Term Exposure Limit (STEL):		ACGIH
	100 ppm 435 mg/m3	PEL:		OSHA Z1
	100 ppm 435 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	100 ppm 435 mg/m3	Time Weighted Average (TWA):		MX OEL
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: solid	Evaporation rate	: Not applicable
Appearance	: pellets	Specific Gravity	: Not determined
Colour	: NO PIGMENT	Bulk density	: Not established
Odour	: very faint	Vapour pressure	: not applicable
Melting point/range	: Not determined	Vapour density	: not applicable
Boiling Point:	: not applicable	pH	: not applicable
Water solubility	: insoluble		

10. STABILITY AND REACTIVITY

Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

NAT CAPSTOCK CONC RG

Version Number 1.0

Revision Date 12/04/2012

Page 6 of 9

Print Date 12/5/2012

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin.
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1330-20-7	Xylenes (o-, m-, p-isomers)	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, blood and blood forming system, Liver, Kidney, central nervous system (CNS), digestive system.
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.
14464-46-1	Silica, cristobalite	Systemic effects	Respiratory system.
		Irritant	Eyes, Skin, Respiratory system.
68855-54-9	Silica, amorphous, diatomaceous earth	Irritant	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1330-20-7	Xylenes (o-, m-, p-isomers)	LC50	5000 ppm/4H	rat
		LC50		rat
		Oral	4,300	rat
		LD50Oral	mg/kg4,300	rabbit
		LD50	mg/kg	rabbit
		Dermal LD50	> 1,700 mg/kg	
		Dermal LD50	43 g/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14807-96-6	Talc	no	2B	no
14808-60-7	Quartz	no	1	no
14464-46-1	Silica, cristobalite	no	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

NAT CAPSTOCK CONC RG

Version Number 1.0
Revision Date 12/04/2012

Page 7 of 9
Print Date 12/5/2012

2A - The component is probably carcinogenic to humans.
2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

Additional Health Hazard Information:

Silica, cristobalite 14464-46-1 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.
- Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.
- Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

- Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA : Refer to specific regulation.
- IMO/IMDG (maritime) : Refer to specific regulation.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

NAT CAPSTOCK CONC RG

Version Number 1.0
Revision Date 12/04/2012

Page 8 of 9
Print Date 12/5/2012

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight percent	NPRI ID#
Xylenes (o-, m-, p- isomers)	1330-20-7	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1305-78-8
14808-60-7
68855-54-9
14464-46-1

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

NAT CAPSTOCK CONC RG

Version Number 1.0
Revision Date 12/04/2012

Page 9 of 9
Print Date 12/5/2012

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed
China IECS : Listed
Europe EINECS : Listed
Japan ENCS : Not determined
Korea KECI : Listed
Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.