

#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 1 of 17 Print Date 11/08/2016

## SAFETY DATA SHEET

#### NAV8960K DK SHADOW GRAY 2000

### **Section 1. Identification**

GHS product identifier : NAV8960K DK SHADOW GRAY 2000

Chemical name: MixtureCAS number: MixtureOther means of identification: CC10175216

**Product type** : solid

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

#### Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and

other users of this product.

Classification of the substance or

mixture

Not classified.

**GHS** label elements

Signal word : No signal word.

1/17



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 2 of 17 Print Date 11/08/2016

**Hazard statements**: No known significant effects or critical hazards.

#### **Precautionary statements**

General:Not applicable.Prevention:Not applicable.Response:Not applicable.Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

### Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: CC10175216

#### CAS number/other identifiers

Ingredient name	%	CAS number
2-Propenenitrile, polymer with Ethenylbenzene	50 - 75	9003-54-7
Titanium dioxide	3 - 5	13463-67-7
Carbon black	1 - 3	1333-86-4
2-(2-Hydroxy-5-tert-octylphenyl)benzotriazole	1 - 3	3147-75-9
Styrene	0.1 - 0.3	100-42-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Page 3 of 17 Revision Date 10/19/2016 Print Date 11/08/2016

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses.

Get medical attention if irritation occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical

surveillance for 48 hours.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Get medical attention if symptoms occur.

**Ingestion** : Wash out mouth with water. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by

medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016

Page 4 of 17 Print Date 11/08/2016

No action shall be taken involving any personal risk or without **Protection of first-aiders** 

suitable training.

See toxicological information (Section 11)

### **Section 5. Fire-fighting measures**

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.

None known.

Specific hazards arising from the chemical

**Hazardous thermal** decomposition products No specific fire or explosion hazard.

Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of For emergency responders any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

**Environmental precautions** Avoid dispersal of spilled material and runoff and contact with soil,

> waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 5 of 17 Print Date 11/08/2016

#### Methods and materials for containment and cleaning up

Small spill : Move containers from spill area. Vacuum or sweep up material and

place in a designated, labeled waste container. Dispose of via a

licensed waste disposal contractor.

Large spill : Move containers from spill area. Prevent entry into sewers, water

courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### **Precautions for safe handling**

Protective measures

Advice on general occupational

hygiene

: Put on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
2-Propenenitrile, polymer with	
Ethenylbenzene	



### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 6 of 17 Print Date 11/08/2016

Styrene	OSHA PEL 1989 (1989-03-01)		
	PEL: Permissible Exposure Level 215 mg/m3 50 ppm		
	Short Term Exposure Limit value for a 15-minute reference		
	period expressed in parts per million or in mg/m3. 425 mg/m3 100		
	ppm		
	OSHA PEL Z2 (1993-06-30)		
	PEL: Permissible Exposure Level 100 ppm		
	Ceiling, is a a limit indicating the maximum concentration of a		
	chemical substances in the breathing zone that should not be		
	exceeded. 200 ppm		
	Acceptable Maximum Peak (AMP) 600 ppm		
	NIOSH REL (1994-06-01)		
	Time Weighted Average (TWA) 215 mg/m3 50 ppm		
	Short Term Exposure Limit value for a 15-minute reference		
	period expressed in parts per million or in mg/m3. 425 mg/m3 100		
	ppm		
	ACGIH TLV (1997-05-21)		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 85 mg/m3 20 ppm		
	TLV-STEL: Threshold Limit Value - Short Time Exposure Level		
	170 mg/m3 40 ppm		
Carbon black	OSHA PEL 1989 (1989-03-01)		
	PEL: Permissible Exposure Level 3.5 mg/m3		
	OSHA PEL (1993-06-30)		
	PEL: Permissible Exposure Level 3.5 mg/m3		
	NIOSH REL (1994-06-01)		
	Time Weighted Average (TWA) 3.5 mg/m3		
	Time Weighted Average (TWA)		
	ACGIH TLV (2010-12-06)		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction		
2 (2 H-1 5 t- 1			
2-(2-Hydroxy-5-tert-			
octylphenyl)benzotriazole			
	0.0774 7777 1000 (1000 02 04)		
Titanium dioxide	OSHA PEL 1989 (1989-03-01)		
	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust		
	OSHA PEL (1993-06-30)		
	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust		
	NIOSH REL (1994-06-01)		
	ACGIH TLV (1996-05-18)		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 10 mg/m3		
	1 crimosore Exposure Ecver to mg me		



### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1	Page 7 of 17
Revision Date 10/19/2016	Print Date 11/08/2016

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
<b>Individual protection measures</b>		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
<b>Body protection</b>	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Page 8 of 17 Revision Date 10/19/2016 Print Date 11/08/2016

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state solid [Pellets.] Color **GREY** Odor Faint odor. **Odor threshold** Not available. Hq Not available. **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. Not available. **Burning rate Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Solubility in water: insoluble in water.

**Partition coefficient: n-** Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

**Conditions to avoid** : Keep away from extreme heat and oxidizing agents.

**Incompatible materials** : Keep away from strong acids.

Oxidizer.

**Hazardous decomposition**: Under normal conditions of storage and use, hazardous decomposition



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 9 of 17 Print Date 11/08/2016

products

products should not be produced.

## Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure		
2-Propenenitrile, polymer with	2-Propenenitrile, polymer with Ethenylbenzene					
	LD50 Oral	Rat	1,800 mg/kg	-		
Titanium dioxide						
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h		
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-		
Carbon black						
	LD50 Oral	Rat	15,400 mg/kg	-		
2-(2-Hydroxy-5-tert-octylphen	yl)benzotriazole					
	LD50 Oral	Rat	1,000 mg/kg	-		
Styrene	Styrene					
	LD50 Oral	Rat	2,650 mg/kg	-		
	LD50 Oral	Rat	5,000 mg/kg	-		
	LC50 Inhalation	Rat	2,770 ppm	4 h		
	LC50 Inhalation	Rat	11.8 mg/l	4 h		

Conclusion/Summary

Mixture.Not fully tested.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Styrene	Eyes - Mild	Human			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit			-
	Moderate				
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
	Eyes -	Rabbit		24 hrs	-
	Moderate				

9/17



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Page 10 of 17 Revision Date 10/19/2016 Print Date 11/08/2016

irritant

Conclusion/Summary

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

Sensitization

**Conclusion/Summary** 

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

Conclusion/Summary : Mixture. Not fully tested.

Carcinogenicity

**Conclusion/Summary** : Mixture.Not fully tested.

Classification

Classification			
Product/ingredient	OSHA	IARC	NTP
name			
2-Propenenitrile, polymer		3	
with Ethenylbenzene			
Titanium dioxide		2B	
Carbon black		2B	
Styrene		2B	

#### **Reproductive toxicity**

**Conclusion/Summary** : Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture. Not fully tested.

**Specific target organ toxicity (single exposure)** 

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Page 11 of 17 Revision Date 10/19/2016 Print Date 11/08/2016

Information on the likely routes of

exposure

Not available.

#### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

#### Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

#### **Potential chronic health effects**

**Conclusion/Summary** : Mixture.Not fully tested.

General: No known significant effects or critical hazards.Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### **Acute toxicity estimates**

Not available.



### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 12 of 17 Print Date 11/08/2016

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Titanium dioxide			
	Acute LC50 > 1,000,000 μg/l	Fish - Fish	96 h
	Marine water		
	Acute LC50 > 1,000 mg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 3 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
	Acute LC50 15.9 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
	Acute LC50 3.6 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
	Acute LC50 11 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
	Acute LC50 13.4 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
	Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute EC50 35.306 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Carbon black			
	Acute EC50 37.563 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute LC50 61.547 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Styrene			
	Acute LC50 9,900 μg/l Fresh water	Fish - Fish	96 h
	Acute LC50 9.1 mg/l Marine water	Fish - Fish	96 h
	Acute LC50 4,020 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 4.7 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 4,080 μg/l Fresh water	Fish - Fish	96 h



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 13 of 17 Print Date 11/08/2016

	Acute LC50 23,000 µg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia		
	Acute EC50 4,700 µg/l Fresh water	Aquatic invertebrates.	48 h	
		Daphnia		
	Acute LC50 59,000 µg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia		
	Acute LC50 52,000 µg/l Marine	Aquatic invertebrates.	48 h	
	water	Crustaceans		
	Acute EC50 33 mg/l Fresh water	Aquatic plants - Algae	96 h	
	Acute EC50 720 µg/l Fresh water	Aquatic plants - Algae	96 h	
	Acute EC50 1,400 µg/l Fresh water	Aquatic plants - Algae	72 h	
	Acute EC50 78,000 µg/l Marine	Aquatic plants - Algae	96 h	
	water			
	Acute NOEC 63 µg/l Fresh water	Aquatic plants - Algae	4 d	
NAV8960K DK SHADOW GRAY 2000				
Remarks - Acute - Aquatic	Chemicals are not readily available as they are bound within the polymer matrix.			
invertebrates.:				

Conclusion/Summary

Chemicals are not readily available as they are bound within the polymer matrix.

Persistence and degradability

**Conclusion/Summary** : Chemicals are not readily available as they are bound within the

polymer matrix.

**Conclusion/Summary** : Chemicals are not readily available as they are bound within the

polymer matrix.

**Bioaccumulative potential** 

Product/ingredient name	LogPow	BCF	Potential
Titanium dioxide		352.00	low
Styrene	2.96	13.49	low

#### **Mobility in soil**

Soil/water partition coefficient

(KOC)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 14 of 17 Print Date 11/08/2016

should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

### Section 14. Transport information

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Not classified as dangerous good under transport regulations.

IMO/IMDG (maritime) : Not classified as dangerous good under transport regulations.

### Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 15 of 17 Print Date 11/08/2016

(PAIR): Not listed

**United States - TSCA 8(c) - Significant adverse reaction (SAR):** 

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Acrylonitrile

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

**Clean Air Act Section 602 Class I** 

**Substances** 

Clean Air Act Section 602 Class II

Substances

**DEA List I Chemicals (Precursor** 

Chemicals)

**DEA List II Chemicals (Essential** 

**Chemicals**)

Not listed

Not listed

Not listed

: Not listed

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

**SARA 311/312** 

**Classification** : Not applicable.

#### Composition/information on ingredients

Name	%	Classification
2-Propenenitrile, polymer with Ethenylbenzene	50 - 75	AH
Carbon black	1 - 3	СН
2-(2-Hydroxy-5-tert- octylphenyl)benzotriazole	1 - 3	AH
Styrene	0.1 - 0.3	F, AH, CH



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Page 16 of 17 Revision Date 10/19/2016 Print Date 11/08/2016

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	Styrene	100-42-5	0.1 - 0.3
requirements	Rutile, antimony chromium buff	68186-90-3	10 - 25
Supplier notification	Styrene	100-42-5	0.1 - 0.3
	Rutile, antimony chromium buff	68186-90-3	10 - 25

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

Massachusetts : The following components are listed:

Titanium dioxide Carbon black

**New York** : The following components are listed:

Styrene

**New Jersey** : The following components are listed:

2-Propenenitrile, polymer with Ethenylbenzene

Titanium dioxide

Styrene Carbon black

**Pennsylvania** : The following components are listed:

Styrene

Titanium dioxide

Carbon black

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

**International regulations** 

International lists : Australia inventory (AICS): Not determined.

**Taiwan inventory (CSNN):** Not determined.

Malaysia Inventory (EHS Register): Not determined.



#### NAV8960K DK SHADOW GRAY 2000

Version Number 1.1 Revision Date 10/19/2016 Page 17 of 17 Print Date 11/08/2016

**EINECS:** All components are listed or exempted.

Japan inventory: Not determined.

China inventory (IECSC): Not determined.

**Korea inventory:** All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

**Chemical Weapons Convention** 

**List Schedule I Chemicals** 

**Chemical Weapons Convention** 

**List Schedule II Chemicals** 

**Chemical Weapons Convention** 

**List Schedule III Chemicals** 

Not listed

Not listed

Not listed

# Section 16. Other information

History

Date of printing: 11/08/2016Date of issue/Date of revision: 10/19/2016Date of previous issue: 01/23/2013Version: 1.1

version . 1.1

**Key to abbreviations**: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.