PolyOne

MATERIAL SAFETY DATA SHEET ORANGE NYLON

Version Number 1.0 Revision Date 04/10/2013 Page 1 of 7 Print Date 4/10/2013

1.	PROD	UCT AND COMPANY IDENTIFICATION			
POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012					
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	ORANGE NYLON			
Product code	:	CC10179033			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	1 - 5
Rutile, antimony chromium buff	68186-90-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **ORANGE NYLON**

Version Number 1.0 Revision Date 04/10/2013 Page 2 of 7 Print Date 4/10/2013

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET **ORANGE NYLON**

Version Number 1.0 Revision Date 04/10/2013 Page 3 of 7 Print Date 4/10/2013

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	No personal respiratory protective equipment	at normally required.
Eye/Face Protection	Safety glasses with side-shields	
Hand protection	Protective gloves	
Skin and body protection	Long sleeved clothing	
Additional Protective Measures	Safety shoes	
General Hygiene Considerations	Handle in accordance with good industrial h practice. Wash hands before breaks and at t	
Engineering measures	Heat only in areas with appropriate exhaust appropriate exhaust ventilation at machinery	
Eurocum limit(a)		

Exposure limit(s)

PolyOne

MATERIAL SAFETY DATA SHEET ORANGE NYLON

Version Number 1.0 Revision Date 04/10/2013 Page 4 of 7 Print Date 4/10/2013

: Not applicable

: Not determined

: Not established

: not applicable

: not applicable not applicable

:

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Evaporation rate

Bulk density

pН

Specific Gravity

Vapour pressure

Vapour density

: solid

: pellets

: ORANGE

: very faint

: Not determined

: not applicable

Form
Appearance
Colour
Odour
Melting point/range
Boiling Point:
Water solubility

: insoluble

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET ORANGE NYLON

Version Number 1.0 Revision Date 04/10/2013 Page 5 of 7 Print Date 4/10/2013

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	no data available
	13	B. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where
		possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with

PolyOne.

MATERIAL SAFETY DATA SHEET **ORANGE NYLON**

Version Number 1.0 Revision Date 04/10/2013 Page 6 of 7 Print Date 4/10/2013

	1	14. TRANSPORT	INFOR	MATION	1		
U.S. DOT Classification	: Not regulated for transportation.						
ICAO/IATA	:	: Refer to specific regulation.					
IMO/IMDG (maritime)	:	Refer to specific	regulatio	on.			
	1	5. REGULATOR	Y INFO	RMATIO	N		
US Regulations:							
OSHA Status	:	Classified as haz	zardous b	ased on co	omponent	s.	
TSCA Status	:	All components TSCA Inventory		roduct are	listed on	or exen	npt from the
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR 3	302)				
not applicable							
California Proposition 65	:	Not applicable					
SARA Title III Section 302 Ex	trem	ely Hazardous Su	bstance				
Unless specific chemicals are	ident	ified under this see	ction, this	product i	s Not Ap	plicable	under this regul
SARA Title III Section 313 To Unless specific chemicals are			ction, this	product i	s Not Ap	olicable	under this regula
Chemical Name				CAS-No).	Weight	percent
CHROMIUM III COMPOU COMPOUNDSANTIMON COMPOUNDSCHROMIU	Y			68186-90)-3	10.00 -	30.00
Canadian Regulations:							
	ase I	nventory (NPRI)					
Chemical Name			CAS-N		Weight		NPRI ID#

PolyOne

MATERIAL SAFETY DATA SHEET ORANGE NYLON

Version Number 1.0 Revision Date 04/10/2013

_

Page 7 of 7 Print Date 4/10/2013

WHMIS Classification	:	D2A	
WHMIS Ingredient Disclosure List			
CAS-No. 68186-90-3			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Listed	
China IECS	:	Listed	
Europe EINECS	:	Listed	
Japan ENCS	:	Listed	
Korea KECI	:	Listed	
Philippines PICCS	:	Listed	
16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.