## MATERIAL SAFETY DATA SHEET GREY 404C ACRYLIC

Version Number 1.0 Revision Date 04/24/2013

Page 1 of 7 Print Date 4/24/2013

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GREY 404C ACRYLIC
Product code	:	CC10180087
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact
: Resin particles, like other inert materials, can be mechanically irritating.
: May be harmful if swallowed.
: Resin particles, like other inert materials, are mechanically irritating to eyes.
: Experience shows no unusual dermatitis hazard from routine handling.
: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET GREY 404C ACRYLIC

Version Number 1.0 Revision Date 04/24/2013 Page 2 of 7 Print Date 4/24/2013

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>not applicable</li> <li>not applicable</li> <li>not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

**POLYONE CORPORATION** 

<u>PolyOne</u>.

## MATERIAL SAFETY DATA SHEET GREY 404C ACRYLIC

Version Number 1.0 Revision Date 04/24/2013 Page 3 of 7 Print Date 4/24/2013

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	: No personal	respiratory protective equipment normally required.
Eye/Face Protection	: Safety glass	es with side-shields
Hand protection	: Protective g	loves
Skin and body protection	: Long sleeve	ed clothing
Additional Protective Measures	: Safety shoe	S
General Hygiene Considerations		ccordance with good industrial hygiene and safety ash hands before breaks and at the end of workday.
Engineering measures	•	n areas with appropriate exhaust ventilation. Provide exhaust ventilation at machinery.
$\mathbf{F}$ and $\mathbf{I}$ $\mathbf{I}$		

Exposure limit(s)

PolyOne.

## **MATERIAL SAFETY DATA SHEET GREY 404C ACRYLIC**

Version Number 1.0 Revision Date 04/24/2013 Page 4 of 7 Print Date 4/24/2013

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Colour
Odour
Melting point/range
Boiling Point:
Water solubility

:	solid
:	pellets
:	GREY
:	very faint
:	Not determined
:	not applicable
:	insoluble

Evapouration rate Specific Gravity:Not determinedBulk density:Not establishedVapour pressure:not applicableVapour density:not applicable pH

- : Not applicable
- : not applicable

### **10. STABILITY AND REACTIVITY**

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

## MATERIAL SAFETY DATA SHEET GREY 404C ACRYLIC

Version Number 1.0 Revision Date 04/24/2013 Page 5 of 7 Print Date 4/24/2013

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	Not readily bio	odegradable.
Environmental Toxicity	Chemicals are polymer matri	not readily available as they are bound within the x.
Bioaccumulation Potential	Chemicals are polymer matri	not readily available as they are bound within the x.
Additional advice	no data availa	ble
	3. DISPOSAL	CONSIDERATIONS
Product	possible recyc	rmoplastic plastics the product can be recycled. Where ling is preferred to disposal or incineration. The
	classification,	vaste material has the responsibility for proper waste transportation and disposal in accordance with eral, state/provincial and local regulations.
Contaminated packaging	classification, applicable fed Recycling is p material has th	transportation and disposal in accordance with

PolyOne.

# MATERIAL SAFETY DATA SHEET GREY 404C ACRYLIC

Version Number 1.0 Revision Date 04/24/2013 Page 6 of 7 Print Date 4/24/2013

	1	14. TRANSPORT	<b>INFOR</b>	MATIO	N			
U.S. DOT Classification	:	Not regulated fo	or transpo	rtation.				
ICAO/IATA	:	Refer to specific	e regulatio	on.				
IMO/IMDG (maritime)	:	Refer to specific	e regulatio	on.				
	1	5. REGULATOR	Y INFO	RMATIO	ON			
US Regulations:								
OSHA Status	:	Classified as haz	zardous b	ased on c	omponen	ts.		
TSCA Status	:	All components TSCA Inventory		roduct ar	e listed or	or exen	npt from the	;
US. EPA CERCLA Hazardous	s Sub	ostances (40 CFR 3	302)					
not applicable								
California Proposition	:	Not applicable						
65								
SARA Title III Section 302 Ex	trem	ely Hazardous Su	bstance					
Unless specific chemicals are	dent	ified under this see	ction, this	s product	is Not Ap	plicable	under this r	egula
SARA Title III Section 313 To	oxic (	Chemicals:						
Unless specific chemicals are i	dent	ified under this see	ction, this					egulat
Chemical Name CHROMIUM III COMPOUNDSCHROMIUM III COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS				CAS-No. 68186-90-3		Weight percent 1.00 - 5.00		
Canadian Regulations:								
	ase I	nventory (NPRI)						
National Pollutant Rele	ube 1	, , ,	CAS-N		Weigh		NPRI ID#	

PolyOne

## MATERIAL SAFETY DATA SHEET GREY 404C ACRYLIC

Version Number 1.0 Revision Date 04/24/2013 Page 7 of 7 Print Date 4/24/2013

ined. Quantity use i	n Canada may
ined. Quantity use i	n Canada may
ined. Quantity use i	n Canada may
ined. Quantity use i	n Canada may
ined. Quantity use i	n Canada may

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.