MATERIAL SAFETY DATA SHEET UVPPE - V4

Version Number 1.0 Revision Date 05/29/2013

Page 1 of 7 Print Date 5/29/2013

1. PRODUCT AND COMPANY IDENTIFICATION					
POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012					
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	UVPPE - V4			
Product code	:	CC10181765			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	11097-59-9	1 - 5
1,6-Hexanediamine, N,N'-bis(2,2,6,6- tetramethyl-4-piperidinyl)-, polymers with morpholine-2,4,6-trichloro-1,3,5-triazine reaction pr	193098-40-7	5 - 10
Aluminum oxide	1344-28-1	1 - 5
Silica, amorphous	7631-86-9	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation

: Resin particles, like other inert materials, can be mechanically irritating.



MATERIAL SAFETY DATA SHEET UVPPE - V4

May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating te eyes. Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information. None known. 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information. None known. 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. Wash off with soap and plenty of water. If skin irritation persists
Experience shows no unusual dermatitis hazard from routine handling Refer to Section 11 for Toxicological Information. None known. 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. Wash off with soap and plenty of water. If skin irritation persists
None known. 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. Wash off with soap and plenty of water. If skin irritation persists
 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. Wash off with soap and plenty of water. If skin irritation persists
Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. Wash off with soap and plenty of water. If skin irritation persists
 overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. Wash off with soap and plenty of water. If skin irritation persists
persist or in all cases of doubt seek medical advice.Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.Wash off with soap and plenty of water. If skin irritation persists
least 15 minutes. If eye irritation persists, seek medical attention. Wash off with soap and plenty of water. If skin irritation persists
5. FIREFIGHTING MEASURES
not applicable
not applicable
not applicable
not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Carbon dioxide blanket, water spray, bry powder, i bani.
Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.
CCIDENTAL RELEASE MEASURES
Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.



MATERIAL SAFETY DATA SHEET UVPPE - V4

ion Number 1.0 sion Date 05/29/2013		Page 3 Print Date 5/29/2
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

MATERIAL SAFETY DATA SHEET UVPPE - V4

Version Number 1.0 Revision Date 05/29/2013 Page 4 of 7 Print Date <u>5/29/2013</u>

Components	Value	Exposure time	Exposure type	List:
Aluminum oxide	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

solid
pellets
NO PIGMENT
very faint
Not determined
not applicable
insoluble

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not established
not applicable
not applicable
not applicable

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

PolyOne.

MATERIAL SAFETY DATA SHEET UVPPE - V4

Version Number 1.0 Revision Date 05/29/2013 Page 5 of 7 Print Date 5/29/2013

CAS-No.	Chemical Name	Effect	Target Organ
11097-59-9	Aluminate (Al(OH)63-), (OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	Irritant	Eyes, Skin.
193098-40-7	1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-, polymers with morpholine-2,4,6- trichloro-1,3,5-triazine reaction pr	Irritant	Eyes, Respiratory system.
		Toxic	Refer to LC50 / LD50 Data on MSDS
1344-28-1	Aluminum oxide	Systemic effects	Eyes, Skin, Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
193098-40-7	1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-, polymers with morpholine-2,4,6- trichloro-1,3,5-triazine reaction pr	LC50	2.8 mg/l	rat

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste



MATERIAL SAFETY DATA SHEET UVPPE - V4

ion Number 1.0 sion Date 05/29/2013					F	Page Print Date 5/29,
	tr	ansportation a	e responsibility and disposal in and local regu	accordance v		
	14. '	FRANSPOR	T INFORMA	TION		
U.S. DOT Classification	: N	ot regulated f	or transportation	n.		
ICAO/IATA	: R	efer to specifi	c regulation.			
IMO/IMDG (maritime)	: R	efer to specifi	c regulation.			
	15. R	EGULATO	RY INFORMA	TION		
US Regulations:						
OSHA Status	: C	lassified as ha	azardous based	on compone	nts.	
TSCA Status		Il component SCA Inventor	ts of this produ- y.	ct are listed of	on or exe	mpt from the
US. EPA CERCLA Hazardo	ous Substar	nces (40 CFR	302)			
not applicable						
California Propositio 65	n : N	ot applicable				
SARA Title III Section 302	Extremely	Hazardous S	ubstance			
Unless specific chemicals ar	e identified	d under this se	ection, this proc	luct is Not A	pplicabl	e under this regu
SARA Title III Section 313	Toxic Cha	micals				
			notion this prov	huat is Not A	nnliachl	o under this requ
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulat Chemical Name CAS-No. Weight percent						
ALUMINUM OXIDE (FIBROUS FORMS) 1344-28-1 1.00 - 5.00						
Canadian Regulations:						
National Pollutant Re	lease Inve	ntory (NPRI)				
Chemical Name		• . /	CAS-No.	Weig perce		NPRI ID#

POLYONE CORPORATION

PolyOne

MATERIAL SAFETY DATA SHEET UVPPE - V4

Version Number 1.0 Revision Date 05/29/2013

_

Page 7 of 7 Print Date 5/29/2013

WHMIS Classification	:	D2B				
WHMIS Ingredient Disc	WHMIS Ingredient Disclosure List					
CAS-No. 1344-28-1 7631-86-9						
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
National Inventories:						
Australia AICS	:	Not determined				
China IECS	:	Not determined				
Europe EINECS	:	Listed				
Japan ENCS	:	Not determined				
Korea KECI	:	Not determined				
Philippines PICCS	:	Not determined				
		16 OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.